



Overview

Model Name	Rack ATS, 230V, 32A, IEC 309 in, (16) C13 (2) C19 out
Includes	RS-232 configuration cable , Rack Mounting brackets , Serial configuration cable
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Algeria , Andorra , Angola , Argentina , Armenia , Australia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Canada , Cayman Islands , Central African Republic , Chad , China , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , <![CDATA[Cote D'Ivoire]]> , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guinea , Hungary , Iceland , India , Indonesia , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Malaysia , Mali , Malta , Mauritania , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Philippines , Poland , Portugal , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , United States , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Nominal Output Voltage	230V
Maximum Total Current Draw per Phase	32 A
Output Connections	(16) IEC 320 C13 (Battery Backup) , (2) IEC 320 C19 (Battery Backup)
Always on Outlets	0
Overload Protection	Yes

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	IEC 309 32A 2P+E
Cord Length	2.44 meters
Number of Power Cords	2
Maximum Line Current per phase	32 A
Maximum Input Current per phase	32 A

Load Capacity	0 VA
---------------	------

Physical

Net Weight	6.94 kg
Maximum Height	88.0 mm
Maximum Width	432.0 mm
Maximum Depth	236.0 mm
Shipping Weight	9.43 kg
Shipping Height	210.0 mm
Shipping Width	584.0 mm
Shipping Depth	356.0 mm
Color	Black

Environmental

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000 meters

Conformance

Approvals	EN 55022 Class A , FCC Part 15 Class A
Standard warranty	2 years repair or replace