



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Input voltage	200 V 230 V 240 V
Output voltage	200 V 230 V 240 V
Plug standard	IEC 60309 32 A 2P + E
Number of rack unit	1U
Cable length	3.66 M
Provided equipment	Installation guide Safety guide

Physical

Colour	Black
Height	4.4 Cm
Width	43.8 Cm
Depth	9.3 Cm
Net weight	2.78 Kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Permissible voltage	200...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	4 IEC 60320 C19
--------------------------------	-----------------

Conformance

Product certifications	CE IRAM VDE
------------------------	-------------------

Packing Units

Package 1 Weight	3.75 Kg
Package 1 Height	20.8 Cm
Package 1 width	47.8 Cm
Package 1 Length	18 Cm
SCC14	10731304327827
Number of Units in Package 3	60

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**