



### Overview

Description	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Model Name	Power Cord, Locking C19 to BS1363A (UK), 3.0m
Standard Lead Time	Usually in Stock
Product Distribution	United Kingdom

### Purchase

Product Distribution	APC  AP8756
----------------------	---

### Output

Nominal Output Voltage	240V
Maximum Total Current Draw per Phase	13 A
Output Connections	(1) IEC 320 C19 (Battery Backup)
Cord Length	3.05 meters

### Input

Input Connections	British BS1363A
Cord Length	3 meters
Number of Power Cords	1
Maximum Line Current per phase	13 A
Maximum Input Current per phase	13 A

### Physical

Net Weight	0.44 kg
------------	---------

Maximum Height	230 mm
Maximum Width	230 mm
Maximum Depth	50 mm
Shipping Weight	0.44 kg
Shipping Height	230 mm
Shipping Width	230 mm
Shipping Depth	50 mm
Color	Black

### Environmental

Operating Environment	0 - 70 °C
Operating Relative Humidity	20 - 80 %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 70 °C
Storage Relative Humidity	20 - 80 %
Storage Elevation	0-15000 meters

### Conformance

Approvals	BSI 1363 , VDE
Standard warranty	2 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs