
Product data sheet Characteristics

APCRBC118

APC Replacement Battery Cartridge #118



	rv	

Model Name	APC Replacement Battery Cartridge #118
Includes	All required connectors , Battery recycling guide , Installation guide , Reusable packaging
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Andorra , Australia , Austria , Belgium , Bosnia And Herzegovina , Bulgaria , Canada , Croatia , Cyprus , Czech Republic , Denmark , Estonia , Finland , France , Germany , Gibraltar , Greece , Hungary , Iceland , Ireland , Italy , Latvia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malta , Moldova, Republic Of , Netherlands , New Zealand , Norway , Poland , Portugal , Romania , Russian Federation , Slovakia (Slovak Republic) , Slovenia , Spain , Sweden , Switzerland , Ukraine , United States

Output

Battery Output Voltage	120		

Batteries & Runtime

Battery Volt-Amp-Hour Capacity	600
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Enclosed battery cartridge
Battery mounting	3 - 5
Included Battery Modules	0
Battery Slots Empty	0
RBC Quantity	1
Battery blocks per string	10

Physical

. Hyoroun		
Net Weight	22.27 kg	net a
Maximum Height	76.0 mm	
Maximum Width	203.0 mm	
Maximum Depth	584.0 mm	tr i
Shipping Weight	25.18 kg	
Shipping Width	393.0 mm	iš G
Shipping Height	228.0 mm	Ë
Shipping Depth	761.0 mm	<u> </u>

Rack Height	0 U
Units per Pallet	12.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters

Conformance

Standard warranty	1 year repair or replace
,	

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs