



Overview

Model Name	APC Back-UPS 400, 230V, BS1363
Includes	User Manual , Wall-mounting template
Standard Lead Time	Usually in Stock
Product Distribution	Bahrain , Gambia , Ghana , Ireland , Kenya , Kuwait , Malawi , Nigeria , Oman , Qatar , Saudi Arabia , Sierra Leone , TANZANIA, UNITED REPUBLIC OF , Uganda , United Arab Emirates , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	240 Watts / 400 VA
Max Configurable Power (Watts)	240 Watts / 400 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (sync to mains)	Standby
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) BS 1363 (Battery Backup) , (4) BS 1363 (Surge Protection)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	British BS1363A
Cord Length	1.83 meters
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 hour(s)
Replacement Battery	APCRBC106
RBC Quantity	1

Communications & Management

Available SmartSlot™ Interface Quantity	0
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	310 joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Network line - 10/100 Base-T Ethernet (RJ-45 connector)

Physical

Maximum Height	86.0 mm
Maximum Width	230.0 mm
Maximum Depth	285.0 mm
Rack Height	0 U
Net Weight	5.4 kg
Shipping Weight	5.6 kg
Shipping Height	132.0 mm
Shipping Width	300.0 mm
Shipping Depth	366.0 mm
Master Carton Units	2.0
Master Carton Dimensions (Length x Width x Height)	15.0 inches
Master Carton Weight	12.2 kg
Color	Charcoal
SCC Codes	1073130423340 1
Units per Pallet	48.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-15000 meters
Storage Temperature	0 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	BSI 1363 , CE , ENERGY STAR (EU)
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 50000 GBP

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs