# Product data sheet Characteristics

# BR900MI

Back UPS Pro BR 900VA, 6 Outlets, AVR, LCD Interface



#### Overview

		2
Lead time	Usually in Stock	olicat

#### General

Provided equipment	User manual USB cable

#### Physical

,		
Depth	31 cm	
Height	19 cm	
Net weight	7.1 kg	
Width	9.1 cm	

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing	
Plug standard	IEC 60320 C14	
Input voltage limits	176294 V	
Maximum input current	10 A	
Switching current capacity	10 A	
Input voltage	230 V	

## Output

Rated power in W	540 W	
Maximum configurable power in W	540 W	
Output frequency	50/60 Hz +/- 1 Hz sync to mains	<u>.</u>
UPS type	Line interactive	<u>.</u>
Wave type	Stepped approximation to a sinewave	
Nb of power socket outlets	6 IEC 60320 C13	Ties to the state of the state
Output voltage	230 V	

## Conformance

Product certifications	A-Tick
	C-Tick
	CE
	EAC
	RCM
	TISI
Marking	GS Mark
Equipment protection policy	Lifetime: 200000 AUD Lifetime: 150000 euros Lifetime: 75000 GBP

## Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage altitude	0.0015240.00 m
Acoustic level	45 dBA
Heat dissipation	16.4 Btu/h

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	12 h
Number of battery replacement quantity	1
Liquid value	0

# Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Data line protection	RJ45 network line - 10/100/1000 Base-T Ethernet

# Packing Units

Package 1 Weight	8 kg
Package 1 Height	25.5 cm
Package 1 width	44 cm
Package 1 Length	14.3 cm
SCC14	10731304346941
Number of Units in Package 2	2
Package 2 Weight	16.85 kg
Package 2 Height	228.60 mm
Package 2 width	457.20 mm
Package 2 Length	279.40 mm

## Offer Sustainability

EU RoHS Directive	Under investigation	
Contractual warranty		
Warranty	2 years repair or replace, 3 years repair or replace for European Union countries	