

# Product datasheet

Specifications



## APC Easy Rack PDU, Metered, 0U, 1 Phase, 3.7kW, 230V, 16A, 18 x C13 and 3 x C19 outlets, IEC60309 2P+E inlet

EPDU1116M

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 2P + E
Number of rack unit	0U
Cable length	3.00 m
Number of cables	1
Provided equipment	Installation guide User manual Vertical mounting brackets

### Physical

Colour	Black
Height	90.2 cm
Width	6.2 cm
Depth	4.44 cm
Net weight	2.5 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

### Output

Number of power socket outlets	18 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

## Conformance

Product certifications	CE TÜV
------------------------	-----------

## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	132 cm
Package 1 Width	16 cm
Package 1 Length	11 cm
Package 1 Weight	2.994 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

## Recommended replacement(s)