



General

Provided equipment	Rack mounting brackets Temperature/humidity sensor USB cable
Camera frame rate	Up to 30 fps
Product compatibility	Rack sensor pod 150 Room sensor pod 155
Display resolution	Up to 1280x1024
Universal sensor supported	0-5V Door contact Dry contact Humidity Smoke Fluid spot leak Temperature Vibration
Number of universal sensor ports	6
Number of sensor pods supported	12
Number of universal sensors supported	78
Number of supported camera	4

Physical

Colour	Black
Depth	17.8 cm
Height	4.3 cm
Mounting location	Front Rear
Net weight	2.45 kg
Width	43.2 cm
Mounting position	Horizontal

Conformance

Standards	CSA C22.2 No. 60950-1-03 FCC part 15 class A
-----------	---

ICES-003
UL 60950-1

Product certifications	2014/30/EU AS/NZS 3548 (C-Tick) class A CE EMC directive 2004/108/EC VCCI class A
------------------------	---

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.00...15240.00 m

Communication

Communication network type	RJ45 10/100/1000 Base-T
Communication port protocol	A-Link DHCP HTTPS IPv4 SNMP v1 SNMP v3 SSH v2 TCP/IP
