

# Product data sheet

Specifications



## Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32



AP7586

### Overview

Lead time Usually in Stock

### Main

Main Output Voltage 230 V

Main Input Voltage 200 V  
208 V  
230 V

Number of rack unit 2U

Cable length 8.53 m

Number of cables 1

### General

Provided equipment Installation guide  
Rack mounting brackets

### Physical

Colour Black

Depth 8.9 cm

Height 8.9 cm

Net weight 4.1 kg

Width 43.7 cm

### Input

Input current limits 32 A

Load capacity 7360 VA

Network frequency 50/60 Hz

Number of input connectors 1 hard wire 3-wire

### Output

Number of power socket outlets 4 IEC 60309

### Conformance

Product certifications CE

## Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	5 kg
Package 1 Height	15.2 cm
Package 1 width	52.1 cm
Package 1 Length	52.1 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------