

SC450RM1U

APC Smart-UPS SC 450VA 120V - 1U Rackmount/Tower



Overview

Description	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Model Name	APC Smart-UPS SC 450VA 120V - 1U Rackmount/Tower
Includes	CD with software , Rack Mounting brackets , Smart UPS signalling RS-232 cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Aruba , Bahamas , Barbados , Belize , Bermuda , Canada , Cayman Islands , Colombia , Costa Rica , Cuba , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Puerto Rico , Saudi Arabia , Trinidad And Tobago , Turks And Caicos Islands , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES)

Output

Output Power Capacity	280 Watts / 450 VA
Max Configurable Power (Watts)	280 Watts / 450 VA
Nominal Output Voltage	120V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) NEMA 5-15R (Battery Backup)

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P
Cord Length	6 feet (1.83 meters)
Input voltage range for main operations	82 - 144 V
Input voltage adjustable range for mains operation	75 - 154V
Maximum Input Current	0 A

Input Breaker Capacity	0 A
------------------------	-----

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	5 hour(s)
Replacement Battery	RBC18
RBC Quantity	1

Communications & Management

Interface Port(s)	DB-9 RS-232
Available SmartSlot™ Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Optional

Surge Protection and Filtering

Surge energy rating	400 Joules
Filtering	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ-11 Modem/Fax protection (four wire dual line) , RJ45 10/100 Base-T Ethernet protection

Physical

Maximum Height	1.72 inches (44.0 mm)
Maximum Width	17.0 inches (432.0 mm)
Maximum Depth	15.17 inches (385.0 mm)
Rack Height	1 U
Net Weight	23.7 lbs (10.77 kg)
Shipping Weight	27.1 lbs (12.32 kg)
Shipping Height	6.46 inches (164.0 mm)
Shipping Width	18.73 inches (476.0 mm)
Shipping Depth	23.17 inches (589.0 mm)
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Grey
Units per Pallet	24.0

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)
Audible noise at 1 meter from surface of unit	38.000 dB
Online Thermal Dissipation	38.000 BTU/hr

Conformance

Approvals	CSA , FCC Part 15 Class A , UL 1778
-----------	-------------------------------------

Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : \$150000
