



Easy PDU, Switched,ZeroU,16A,230V,(20)C13 & (4)C19, IEC309

EPDU1116S

Call for More Information

- Easy Switched Rack Power Distribution Units (Rack PDU) provide on/off outlet switching, advanced power management, load monitoring and much more features than the average power strip.
- Includes: Installation guide, User Manual, Vertical mounting brackets

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	16
Output Connections	(20) IEC 320 C13 (4) IEC 320 C19

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 309 16A 2P+E
Cord Length	3meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	1738MM, 173.8CM
Maximum Width	55MM, 5.5CM
Maximum Depth	62MM, 6.2CM
Net Weight	7.3KG
Shipping weight	8.5KG
Shipping Height	1950MM, 195.0CM
Shipping Width	160MM, 16.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Easy PDU, Switched,ZeroU,16A,230V,(20)C13 & (4)C19, IEC309 | EPDU1116S | Downloaded on 10/13/2020 (EST)

Physical	
Shipping Depth	110MM, 11.0CM
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000meters

Conformance	
Approvals	CE, EAC, TUV
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.