

SRT5KRMXLI-6W

APC Smart-UPS SRT 5000VA 230V Rack Mount with 6 year warranty package



Overview

Model Name	APC Smart-UPS SRT 5000VA 230V Rack Mount with 6 year warranty package
Includes	Documentation CD
Standard Lead Time	Usually in Stock
Product Distribution	Austria

Output

Output Power Capacity	4500 Watts / 5000 VA
Max Configurable Power (Watts)	4500 Watts / 5000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240V
Crest Factor	3 : 1
Crest Factor	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(2) IEC Jumpers (Battery Backup)
Bypass	Internal Bypass (Automatic and Manual)

Input

Nominal Input Voltage	230V
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	Hard Wire 3 wire (1PH+N+G)
Input voltage range for main operations	160 - 275 V
Other Input Voltages	220

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	1.5 hour(s)
Replacement Battery	APCRBC140
RBC Quantity	1

Nominal Battery Voltage	192V
-------------------------	------

Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T
Available SmartSlot™ Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	480 Joules
---------------------	------------

Physical

Maximum Height	130.0 mm
Maximum Width	432.0 mm
Maximum Depth	720.0 mm
Rack Height	3 U
Net Weight	54.43 kg
Shipping Weight	66.86 kg
Shipping Height	330.0 mm
Shipping Width	610.0 mm
Shipping Depth	960.0 mm
Color	Black
Units per Pallet	6.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	55.000 dB
Online Thermal Dissipation	931.000 BTU/hr
Protection Class	IP 20

Conformance

Approvals	CE
Standard warranty	6 years (requires registration)

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs