

Product data sheet

Specifications



APC Smart-UPS On-Line, 2200VA,
Lithium-ion, Rackmount 4U, 230V,
6x C13+2x C19 IEC outlets,
SmartSlot, Extended long runtime,
Rail kit included

SRTL2200RM4UXLI

Overview

Presentation	High density, double-conversion on-line power protection with long runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Plug standard	IEC 60320 C20
Output connection type	6 IEC 60320 C13
Number of rack unit	4U
Cable length	1.83 m
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)

General

Product web sub-family	Lithium-Ion
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black with silver front bezel
Height	17.1 cm
Width	43.2 cm
Depth	63.9 cm

Net weight	44.5 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...275 V

Output

Maximum configurable power in W	1980 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Built-in bypass
Maximum configurable power in VA	2200 VA

Conformance

Product certifications	CE
Marking	CE Mark

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	48 V
Battery charger power	158 W rated
Battery power in VAH	2400 VAh capacity

2880 VAh runtime

Battery life	5...10 year(s)
---------------------	----------------

Battery option	XBP48RM2U-LI 1 5760 VAh XBP48RM2U-LI 2 8640 VAh
-----------------------	--

Extended runtime	1
-------------------------	---

Communications & Management

Free slots	1
-------------------	---

Control panel	Multifunction LCD status and control console
----------------------	--

Alarm	Audible and visible alarms prioritized by severity
--------------	--

Emergency power off	Yes
----------------------------	-----

Surge Protection and Filtering

Surge energy rate	432 J
--------------------------	-------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Offer Sustainability

EU RoHS Directive	Under investigation
--------------------------	---------------------

Contractual warranty

Warranty	5 year repair or replace
-----------------	--------------------------

Recommended replacement(s)