





PM5T-UK

Overvie	

Lead time Usually in Stock

Main

IVIAIII	
Main Input Voltage	230 V
Input Connection Type	BS1363A British
Cable length	1.83 m
Number of cables	1
Provided equipment	User manual

Physical

Colour	White
Height	5.6 cm
Width	38.5 cm
Depth	7.3 cm
Net weight	0.69 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50 Hz +/- 5 Hz
Maximum input current	13 A
Switching current capacity	13 A

Output

Number of power socket outlets	5
Outlet standard	BS 1363 United Kingdom

Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	090 %
Operating altitude	010000 ft
Ambient air temperature for storage	-540 °C
Storage Relative Humidity	095 % Non-condensing
Storage altitude	0.0015240.00 m

Surge Protection and Filtering

Common mode rejection	40 dB
Peak current	24 kA common mode 12 kA normal mode
Surge energy rate	918 J
Data line protection	RJ11 modem/fax protection

Packing Units

Package 1 Weight	0.8 kg
Package 1 Height	5.8 cm
Package 1 Width	40.5 cm
Package 1 Length	13 cm
SCC14	10731304313868
Number of Units in Package 2	12
Package 2 Weight	8.28 kg
Package 2 Height	431.80 mm
Package 2 Width	381.00 mm
Package 2 Length	279.40 mm
Number of Units in Package 3	216

Offer Sustainability

Overtein etcle effect etcle	Crear Program and dat
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
	EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

|--|--|