AP9640

UPS Network Management Card 3



\sim					
•	11	\sim	r\ /	10	A
	w		ıv		V١

1 10	11 " : 0: 1	<u>a</u>
Lead time	Usually in Stock	<u>o</u> .
		<u>a</u>

General

0 0 1 1 0 1 0 1		Ţ
Provided equipment	User manual USB cable	
	USB cable	¥ g

Physical

Depth	11.4 cm	
Height	3.8 cm	
Net weight	0.08 kg	-
Width	12.1 cm	

Conformance

Overview		
Lead time	Usually in Stock	
0		
General		
Provided equipment	User manual USB cable	
Physical		
Depth	11.4 cm	_
Height	3.8 cm	
Net weight	0.08 kg	
Width	12.1 cm	
Conformance		
Standards	EN 55022 class A	
Standards	EN 55024	
	ICES-003	
Product certifications	AS/NZS 3548 (C-Tick) class A	
	FCC part 15 class A	
	GOST VCCI class A	
	VCCI class A	
Environmental		
Ambient air temperature for operation	045 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-545 °C	
Storage altitude	0.0015240.00 m	
Communications & Management		
Authentication	Radius	
Communication network type	RJ45 10/100/1000 Base-T	
Oct 5, 2020		

Environmental

Ambient air temperature for operation	045 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-545 °C	
Storage altitude	0.0015240.00 m	

Communications & Management

Authentication	Radius
Communication network type	RJ45 10/100/1000 Base-T

Communication port protocol	HTTP
	HTTPS
	IPv4
	IPv6
	NTP
	SMTP
	SNMP v1
	SNMP v2c
	SNMP v3
	SSH v1
	SSH v2
	SSL
	TCP/IP
	Telnet

Packing Units

Package 1 Weight	0.34 kg	
Package 1 Height	5.1 cm	
Package 1 width	23.5 cm	
Package 1 Length	15.9 cm	

Offer Sustainability

EU RoHS Directive	Under investigation

Contractual warranty

Warranty	2 years repair or replace
•	· · · · ·