

Day/Night H.264 HD Outdoor Dome Cameras

AVIGILON

Avigilon offers the broadest range of high definition cameras in the industry – from 1 – 5 MP and 4 – 7K (based on horizontal resolution) – and are available in a variety of formats, including dome, panoramic and fixed. Whether it's a small storefront that requires a few cameras or a large complex system requiring complete coverage of numerous areas, you can trust that you're getting the best solution for your security needs.

The innovative H.264 HD outdoor dome cameras are just one way Avigilon can help provide the very best monitoring and protection.



The H.264 HD outdoor dome cameras are a great solution for monitoring both daytime and nighttime activities, with peace of mind due to their vandal resistant construction. They feature an integrated lens for remote focus and zoom control and are ONVIF compliant for no-hassle integration. The outdoor dome cameras operate on Avigilon's H3 platform, providing these models with improved low light performance with wide dynamic range support and enhanced HDSM™ software features. P-Iris control also allows the cameras to automatically set their iris position to maximize image quality in all lighting conditions, while onboard storage capabilities let you manage storage directly on the cameras using a standard SD memory card. These cameras are extremely versatile and can work in almost any location, including banks, schools, retail outlets, municipal grounds and buildings, hotels, bars and restaurants.

KEY FEATURES

Progressive scan CMOS sensor
Unsurpassed image quality
Available with 3-9 mm F1.2 or 9-22 mm F1.6 P-Iris lens with remote focus and zoom
Up to 30 images per second
Wide Dynamic Range
SD card slot for onboard storage support
H.264 and Motion JPEG compression
ONVIF API compliance with version 1.02, 2.00 and Profile S
Zoom and content adaptive integrated IR (Infrared) LEDs provide uniform illumination in the dark, even at 0 lux, up to a maximum of 15 m (50 ft) away
Power over Ethernet, 24 VAC or 12 VDC power input
Analog Video Output
Vandal resistant construction and IP66 compliant


Specifications

H.264 HD OUTDOOR
DOME CAMERAS


		1.3 MP (LIGHTCATCHER™)	1.0 MP	2.0 MP	3.0 MP	5.0 MP		
IMAGE PERFORMANCE	Image Sensor	1/3" progressive scan CMOS		1/2.7" progressive scan CMOS		WDR 1/3" progressive scan CMOS		
	Active Pixels	1280 (H) x 1024 (V)		1280 (H) x 720 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)		
	Imaging Area	4.8 mm (H) x 3.84 mm (V); 0.189" (H) x 0.151" (V)		5.9 mm (h) x 3.3 mm (V); 0.231" (H) x 0.129" (V)		4.5 mm (H) x 3.4 mm (V); 0.177" (H) x 0.133" (V)		
	Minimum Illumination	3-9 mm lens:	0.02 lux (F1.2) in color mode; 0.002 lux (F1.2) in monochrome mode		0.2 lux (F1.2) in color mode; 0.02 lux (F1.2) in monochrome mode		0.3 lux (F1.2) in color mode; 0.03 lux (F1.2) in monochrome mode	
		9-22 mm lens:	0.04 lux (F1.6) in color mode; 0.004 lux (F1.6) in monochrome mode		0.4 lux (F1.6) in color mode; 0.04 lux (F1.6) in monochrome mode		0.6 lux (F1.6) in color mode; 0.06 lux (F1.6) in monochrome mode	
	Dynamic Range	71 dB		69 dB		100 dB		
	Image Rate	30 (all resolutions)				20 (at full resolution)	13 (at full resolution)	
	Resolution Scaling	Down to 768 x 432				Down to 480 x 360		
LENS	Lens	3-9 mm, F1.2, P-Iris, remote focus and zoom						
		9-22 mm, F1.6, P-Iris, remote focus and zoom						
	Angle of View	3-9 mm lens:	30° - 88°		35° - 98°		28° - 84°	
		9-22 mm lens:	13° - 30°		15° - 35°		12° - 28°	
IMAGE CONTROL	Image Compression Method	H.264 (MPEG-4 Part 10/AVC), Motion JPEG						
	Streaming	Multi-stream H.264 and Motion JPEG						
	Motion Detection	Selectable sensitivity and threshold						
	Electronic Shutter Control	Automatic, Manual (1/6 to 1/2000 sec)	Automatic, Manual (1/6 to 1/8000 sec)					
	Iris Control	Automatic, Manual						
	Day/Night Control	Automatic, Manual						
	Flicker Control	50 Hz, 60 Hz						
	White Balance	Automatic, Manual						
	Backlight Compensation	Adjustable						
	Privacy Zones	Up to 64 zones						
	Audio Compression Method	G.711 PCM 8 kHz						
	Audio Input/Output	Line level input and output, A/V mini-jack (3.5 mm)						
	Video Output	NTSC/PAL, A/V mini-jack (3.5 mm)						
	External I/O Terminals	Alarm In, Alarm Out						
	IR Illumination (option)	3-9 mm lens: (Surface Mount Indoor Camera without LightCatcher Technology) 850 nm wavelength, 15 m (50 ft) max. distance of IR illumination at 0 lux						
NETWORK	Network	100BASE-TX						
	Cabling Type	CAT5						
	Connector	RJ-45						
	API	ONVIF compliance version 1.02, 2.00, Profile S (www.onvif.org)						
	Security	Password protection, HTTPS encryption, digest authentication, WS authentication, user access log, 802.1x port based authentication						
	Protocol	IPv4, HTTP, HTTPS, SOAP, DNS, NTP, RTSP, RTCP, RTP, TCP/UDP, IGMP, ICMP, DHCP, Zeroconf, ARP						
	Streaming Protocols	RTP/UDP, RTP/UDP multicast, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/RTSP/HTTPS/TCP, HTTP						
	MECHANICAL			SURFACE MOUNT OUTDOOR DOME CAMERA		PENDANT DOME CAMERA		
Dimensions (ØxH)		152.3 mm x 109.9 mm; 6.0" x 4.3"			167 mm x 157 mm; 6.6" x 6.2"			
Weight		1.28 kg (2.82 lbs)			2.1 kg (4.6 lbs)			
Dome Bubble		Polycarbonate, clear						
Body		Aluminum						
Housing		Surface mount, vandal resistant			Pendant mount, vandal resistant			
Finish		Powder coat, cool gray 2						
Adjustment Range		360° pan, 180° tilt (122° tilt with -IR option), 180° azimuth						
Onboard Storage		SD/SDHC/SDXC slot – minimum class 4; class 6 or better recommended						
ELECTRICAL		Power Consumption	9 W (10 W for -IR option)					
	Power Source	VDC: 12 V +/- 10%, 10 W min (10 W min with -IR option)		VAC: 24 V +/- 10%, 12 VA min (12 VA min with -IR option)				
	Power Connector	2-pin terminal block						
	RTC Backup Battery	3V Manganese Lithium						
ENVIRONMENTAL	Operating Temperature	-30 °C to +50 °C (-22 °F to 122 °F)						
	Storage Temperature	-10 °C to +70 °C (14 °F to 158 °F)						
	Humidity	0-95% non-condensing						
CERTIFICATIONS	Certifications	UL	cUL	CE	ROHS	WEEE	RCM	EAC
	Safety	UL 60950-1		CSA 60950-1		IEC/EN 60950-1		IEC 62471 (only for models with IR-Illuminators)
	Environmental	UL/CSA/IEC 60950-22		IEC 60529 IP66 Rating		IK10 Impact Rating		
	Electromagnetic Emissions	FCC Part 15 Subpart B Class B		IC ICES-003 Class B		EN 55022 Class B		EN 61000-6-3
	Electromagnetic Immunity	EN 55024				EN 61000-6-1		

Outline Dimensions

H3-DO



H3-DP



Ordering Information

SURFACE MOUNT OUTDOOR DOME CAMERAS

1.0-H3-DO1	1.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera
1.0-H3-DO1-IR	1.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera with IR Illuminator
1.0-H3-DO2	1.0 Megapixel Day/Night H.264 HD 9-22 mm Outdoor Dome Camera
1.3L-H3-DO1	1.3 Megapixel H.264 HD 3-9 mm Outdoor Dome Camera with LightCatcher Technology
1.3L-H3-DO2	1.3 Megapixel H.264 HD 9-22 mm Outdoor Dome Camera with LightCatcher Technology
2.0-H3-DO1	2.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera
2.0-H3-DO1-IR	2.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera with IR Illuminator
2.0-H3-DO2	2.0 Megapixel Day/Night H.264 HD 9-22 mm Outdoor Dome Camera
3.0W-H3-DO1	3.0 Megapixel WDR Day/Night H.264 HD 3-9 mm Outdoor Dome Camera
3.0W-H3-DO1-IR	3.0 Megapixel WDR Day/Night H.264 HD 3-9 mm Outdoor Dome Camera with IR Illuminator
3.0W-H3-DO2	3.0 Megapixel WDR Day/Night H.264 HD 9-22 mm Outdoor Dome Camera
5.0-H3-DO1	5.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera
5.0-H3-DO1-IR	5.0 Megapixel Day/Night H.264 HD 3-9 mm Outdoor Dome Camera with IR Illuminator
5.0-H3-DO2	5.0 Megapixel Day/Night H.264 HD 9-22 mm Outdoor Dome Camera
H3-DOP-SMOKE	Dome Camera Cover with Smoked Bubble

PENDANT DOME CAMERAS

1.0-H3-DP1	1.0 Megapixel Day/Night H.264 HD 3-9mm Pendant Dome Camera
1.0-H3-DP2	1.0 Megapixel Day/Night H.264 HD 9-22mm Pendant Dome Camera
1.3L-H3-DP1	1.3 Megapixel H.264 HD 3-9 mm Pendant Dome Camera with LightCatcher Technology
1.3L-H3-DP2	1.3 Megapixel H.264 HD 9-22 mm Pendant Dome Camera with LightCatcher Technology
2.0-H3-DP1	2.0 Megapixel Day/Night H.264 HD 3-9mm Pendant Dome Camera
2.0-H3-DP2	2.0 Megapixel Day/Night H.264 HD 9-22mm Pendant Dome Camera
3.0W-H3-DP1	3.0 Megapixel WDR Day/Night H.264 HD 3-9mm Pendant Dome Camera
3.0W-H3-DP2	3.0 Megapixel WDR Day/Night H.264 HD 9-22mm Pendant Dome Camera
5.0-H3-DP1	5.0 Megapixel Day/Night H.264 HD 3-9mm Pendant Dome Camera
5.0-H3-DP2	5.0 Megapixel Day/Night H.264 HD 9-22mm Pendant Dome Camera
H3-DOP-SMOKE	Dome Camera Cover with Smoked Bubble
MNT-PEND-WALL	Indoor/Outdoor Pendant Mount Bracket