

AXIS P3915-R Mk II Network Camera

Onboard HDTV 1080p surveillance with audio and Zipstream

AXIS P3915-R Mk II Network Camera is specifically designed for video surveillance in vehicles and rolling stock. The compact, discreet, and rugged camera is IP66/IP67-rated, and can withstand tough conditions such as vibration, shock and temperature fluctuations. Optional accessories for outdoor installation and wider field of view available. The camera provides HDTV 1080p with WDR and Lightfinder to ensure high image quality in mixed and low-light conditions. Traffic Light mode enables the camera to distinguish traffic light colors in dark scenes. Audio-in and I/O capabilities optimize smart surveillance in the driver's compartment. AXIS P3915-R Mk II supports Zipstream, which significantly reduces bandwidth and storage requirements.

- > **Rugged design with EN 50155:2017 Class OT2/ST2 compliance**
- > **Compliance with strict standards in transportation industry**
- > **WDR - forensic capture and Lightfinder**
- > **Zipstream**
- > **Traffic Light mode**
- > **Audio-in and I/O ports**



AXIS P3915-R Mk II Network Camera

Models	AXIS P3915-R Mk II: RJ45 AXIS P3915-R Mk II: M12	Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation	
Camera			
Image sensor	1/2.9" Progressive scan RGB CMOS	Data streaming Event data	
Lens	3.6 mm, F2.0 Horizontal field of view: 87° Vertical field of view: 47° M12 mount, fixed iris See Optional accessories for exchangeable lenses	Built-in installation aids Pixel counter	
Light sensitivity	HDTV 1080p 25/30 fps with Lightfinder Color: 0.15 lux at 50 IRE F2.0 Color: 0.06 lux at 30 IRE F2.0	General	
Shutter time	1/32500 s to 2 s	Casing Aluminum and polycarbonate casing	
Camera angle adjustment	Pan: ±30°, tilt: 15-90°, rotation: ±175°	Sustainability PVC free	
Video			
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Mounting Inside vehicles and rolling stock	
Resolution	1920x1080 to 160x90	Memory 512 MB RAM, 256 MB Flash	
Wide dynamic range	WDR - forensic capture	Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 3.3 W, max 3.9 W	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	Connectors RJ45: male, 10BASE-T/100BASE-TX M12: female, rugged, D-coded with rotatable coupling nut All connectors support PoE 3.5 mm audio in connector, mono, I/O 4-pin, 1 input, 1 output + 12 V DC/15 mA	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com	
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, 20 individual privacy mask, mirroring of images, Traffic Light mode	Operating conditions Normal: -40 °C to 60 °C (-22 °F to 140 °F) Maximum (intermittent): 70 °C (158 °F) Arctic Temperature Control: start-up at -40 °C (-40 °F) Humidity: 10-100% RH	
Pan/Tilt/Zoom	Digital PTZ, preset positions Guard tour, control queue	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)	
Audio			
Audio streaming	Audio in, simplex	Approvals EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498, EAC	
Audio compression	AAC- LC 8/16/32 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Safety IEC/EN/UL 62368-1, EN 45545, UN ECE R118, parts of NFPA 130 ^c	
Audio input	External microphone input or line input	Environment IEC/EN 61373 Category 1 Class B, IEC/EN 60529 IP66/67, NEMA 250 Type 4X, IEC/EN 62262 IK08, IEC 60721-3-5 Class 5M3 (vibration and shock), EN 50155:2017 Class OT2/ST2 (EN 50155:2007 Class TX), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78	
Network			
Security	Password protection, IP address filtering, HTTPS ^a encryption, network access control, digest authentication, user access log, centralized certificate management	Dimensions Height: 49 mm (1 15/16 in), ø 109 mm (4 3/16 in)	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Weight RJ45: 255 g (0.56 lb) M12: 264 g (0.58 lb)	
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	Included accessories Installation guide, Windows decoder 1-user license, drill hole template, top cover tool, lens tool, Allen key Resistorex [®]	
Analytics	Included AXIS Video Motion Detection, active tampering alarm ^b , audio detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Optional accessories Lenses 2.1 mm, F2.2: horizontal field of view 147° 2.8 mm, F2.0: horizontal field of view 115° 6 mm, F1.6: horizontal field of view 52° 8 mm, F1.6: horizontal field of view 40° Other AXIS T94D01S Mount Bracket, AXIS T94D02S Mount Bracket, Network coupler IP66, Network cable coupler indoor For more accessories, see www.axis.com	
Event triggers	Analytics, time scheduled, edge storage events Audio level, external input	Video management software AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/support/downloads	
Event actions	Record video and audio: SD card and network share Upload images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
		Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	

- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).
- For detection of tampering attempts in static and non-crowded scenes.
- ASTM E162 and the non-flaming parts of ASTM E662

Environmental responsibility:

www.axis.com/environmental-responsibility