

AXIS Q1932-E PT Mount Thermal Camera

Designed for pan/tilt motors

The bullet-style, outdoor-ready AXIS Q1932-E PT Mount offers the possibility of mounting the camera on a pan/tilt motor to increase installation flexibility. The thermal resolution of 640x480 and a range of lenses make it easy to detect and identify people, objects and incidents in complete darkness or difficult conditions. A noise filter gives improved thermal image contrast while keeping noise levels low, without adding blur and ghost effects. AXIS Q1932-E PT Mount withstands harsh weather conditions and has a built-in heater for the window. Additionally, it offers Power over Ethernet (IEEE 802.3af) and support for a memory card slot.

- > [VGA thermal imaging](#)
- > [PT mount-ready](#)
- > [Intelligent video applications included](#)
- > [Shock detection](#)
- > [Multiple lens options](#)



AXIS Q1932-E PT Mount Thermal Camera

Models	AXIS Q1932-E PT Mount 10/19/35 or 60 mm	Casing	IP66- and NEMA 4X-rated metal casing (Aluminium) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B
Camera		Memory	256 MB RAM, 128 MB Flash
Image sensor	Uncooled Micro bolometer 640x480, pixel size: 17 µm Spectral range: 8-14 µm	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 10 W 8-28 V DC: max 11 W 20-24 V AC (50/60 Hz): max 15 VA Power supply not included.
Lens	10 mm: Horizontal angle of view: 57°, F1.2 19 mm: Horizontal angle of view: 32°, F1.0 35 mm: Horizontal angle of view: 18°, F1.2 60 mm: Horizontal angle of view: 10°, F1.25	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for power RS485/RS422 for pan/tilt control
Sensitivity	NETD < 70 mK	Edge storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Pan/Tilt/Zoom	Preset positions, Guard tour, Driver selection, Control queue	Operating conditions	-40 °C to 60 °C (-40 °F to 142 °F) Humidity 10–100% RH (condensing)
Video		Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline and Main Profiles Motion JPEG	Approvals	EN 50121-4, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, IEC 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3 EN 55022 Class A, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, C-tick AS/NZS CISPR22 Class A, KCC KN22 Class A, KN24
Resolutions	Sensor is 640x480. Image can be scaled up to 800x600 (SVGA)	Dimensions	309 x 105 mm (12 3/16 x 4 1/8 in)
Frame rate	Up to 8.3 fps and 30 fps	Weight	10/19 mm: 1800 g (4.0 lb) Mount 35 mm: 1900 g (4.2 lb) Mount 60 mm: 2000 g (4.4 lb)
Video streaming	At least three H.264 and Motion JPEG streams using the same palette, simultaneous and individually configured in max. resolution at 30 fps Controllable frame rate and bandwidth, VBR/CBR H.264	Included accessories	Installation Guide, Windows decoder 1-user license, Torx T20 screw driver
Image settings	Compression, Brightness, Contrast, Exposure control, Rotation, Mirroring of images, Multiple palettes, Text and image overlay, Privacy mask	Optional accessories	Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS YP3040 Pan-Tilt Motor, AXIS YP3040 Wall Bracket, AXIS T8310 Control Board
Network		Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
System integration		Export control	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	a.	<i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>
Analytics	AXIS Video Motion Detection 2, AXIS Cross Line Detection, Shock detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	More information is available at www.axis.com	
Event triggers	Analytics, Temperature, External input, Time scheduled, Edge storage events PTZ preset		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Guard tour		
Data streaming	Event data		
General			