

AXIS Q8665-E PTZ Network Camera

Look quickly through a clean window

AXIS Q8665-E offers a quick pan functionality of 100°/second as well as tilting at 40°/second. Compared to a standard PTZ dome, it tilts upwards 40° and can be mounted on top of columns, enabling 360° field of view without anything interfering the line of sight. Compliant with IP66 and NEMA 4X for protection against dust, rain and snow. AXIS Q8665-E is equipped with a wiper to remove excess water or rain. In places with high risk for dust, salt, sand and emission of soot from vehicles, an accessory washer can be purchased to spray cleaning fluid to secure clean window.

- > **Continuous pan, 360° endless**
- > **High speed pan/tilt**
- > **18x optical zoom in HDTV 1080p**
- > **Water and dust resistant**
- > **-40 °C to 55 °C (-40 °F to 131 °F)**



AXIS Q8665-E PTZ Network Camera

Models	AXIS Q8665-E 24 V AC AXIS Q8665-E 120 V AC AXIS Q8665-E 230 V AC	Built-in installation aids	Pixel counter
Camera		General	
Image sensor	Progressive scan RGB CMOS 1/2.9"	Casing	IP66- and NEMA 4X-rated metal casing (aluminum) and ABS Color: RAL 9002 Wiper included
Lens	4.7–84.6 mm, F1.6 – 2.8 Horizontal angle of view: 59 – 4° Autofocus, Automatic day/night	Memory	256 MB RAM, 128 MB Flash
Day and night	Automatically removable infrared-cut filter in night mode	Power	24 V AC: 4 A 120 V AC, 230 V AC: Max: 55 W Typical: 40 W
Light sensitivity	Color: 0.5 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	Connectors	RJ45 10BASE-T/100BASE-TX Network connector Terminal blocks: Power connector CN1, Signal connector REL1 in CN4
Shutter time	1/28000 s to 2 s	Edge storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Pan/Tilt/Zoom	Preset positions, Guard tour, Driver selection, Control queue Pan: Continuous Tilt: +90° to -40° 18x optical zoom and 12x digital zoom Pan speed: 0.02°/s to 100°/s Tilt speed: 0.02°/s to 40°/s Preset accuracy: 0.02°	Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 10–100% RH (condensing) Arctic Temperature Control enables camera start-up at temperatures as low as -40 °C/°F
Video		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Video compression	H.264 (MPEG-4 Part 10/AVC), H.264 Main and Baseline Profile Motion JPEG	Approvals	EMC EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A ITE, ICES-003 Class A, C-tick AS/NZS CISPR 22 Class A, EN 50121-4 120 V AC and 230 V AC: KCC KN22 Class A, KN24
Resolutions	1920x1080 HDTV 1080p to 160x90	Environment	IEC/EN 60529 IP66, NEMA 250 4x
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	Safety	IEC/EN 60950-1, IEC/EN 60950-22 24 V AC and 120 V AC: UL 60950-1, UL 60950-22
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Dimensions	258 x 584 x 463 mm (10 3/16 x 23 x 18 1/4 in)
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Rotation, Text and image overlay, Day/night shift level Wide Dynamic Range – Dynamic Contrast	Weight	17.5 kg (38.6 lb)
Network		Included accessories	Installation Guide
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Required hardware	AXIS Wall Bracket K or AXIS Column Bracket K
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Optional accessories	AXIS Washer Kit A AXIS T95A64 Corner Bracket AXIS T95A67 Pole Bracket AXIS T98A15-VE Media Converter Cabinet A
System integration		Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Event triggers	Analytics, Edge storage events	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>	
Event actions	File upload: FTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage, Pre- and post-alarm video buffering, Overlay text, Day/Night vision mode	More information is available at www.axis.com	
Data streaming	Event data		