

AXIS Q1942-E PT Mount Thermal Network Camera

Wide VGA thermal coverage with pan/tilt flexibility

The bullet-style, outdoor-ready AXIS Q1942-E PT Mount offers the possibility of mounting the camera on a pan/tilt motor to increase installation flexibility. The thermal resolution of 640x480 and a range of lenses make it easy to detect and verify people, objects and incidents from pitch dark areas to a sunlit parking lot. A noise filter gives improved thermal image contrast while keeping noise levels low, without adding blur and ghost effects. AXIS Q1942-E PT Mount withstands harsh weather conditions and has a built-in heater for the window. Additionally, it offers Power over Ethernet and has a microSD card slot.

- > [VGA thermal imaging](#)
- > [PT mount-ready](#)
- > [Powerful performance for video analytics](#)
- > [Electronic Image Stabilization](#)
- > [Axis Zipstream](#)



AXIS Q1942-E PT Mount Thermal Network Camera

Models	AXIS Q1942-E PT Mount 10 mm, 19 mm, 35 mm, 60 mm	Sustainability	PVC free
Camera		Memory	512 MB RAM, 256 MB Flash
Image sensor	Uncooled Micro bolometer 640x480, pixel size: 17 µm Spectral range: 8-14 µm	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 11.8 W 8-28 V DC: typical 6.6 W, max 13 W 20-24 V AC (50/60 Hz): typical 11 VA, max 19 VA Power supply not included.
Lens	10 mm: Horizontal field of view: 63°, F1.25 19 mm: Horizontal field of view: 32°, F1.23 35 mm: Horizontal field of view: 17°, F1.20 60 mm: Horizontal field of view: 10°, F1.25	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for power RS485/RS422 for pan/tilt control
Sensitivity	NETD < 50 mK	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Pan/Tilt	Preset positions, Guard tour, Driver selection, Control queue	Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10-100% RH (condensing)
Video		Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Approvals	EMC EN 55022 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment EN 50581, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3 IEC 60529 IP66
Resolutions	Sensor is 640x480. Image can be scaled up to 800x600 (SVGA).	Dimensions	309 x 105 mm (12 3/16 x 4 1/8 in)
Frame rate	Up to 8.3 fps and 30 fps	Weight	10/19 mm: 1800 g (4.0 lb) Mount 35 mm: 1900 g (4.2 lb) Mount 60 mm: 2000 g (4.4 lb)
Video streaming	At least three H.264 and Motion JPEG streams, simultaneous and individually configured in max. resolution in full frame rate Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Included accessories	Torx® T20 screw driver, Terminal block connector Installation Guide, Windows decoder 1-user license
Image settings	Compression, Brightness, Sharpness, Contrast, Exposure zone, Text and image overlay, Privacy mask, Mirroring of images, Electronic Image Stabilization, Multiple palettes Rotation: 0°, 180°	Optional accessories	Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS T8415 Wireless Installation Tool AXIS T8310 Control Board For more accessories, see www.axis.com
Network		Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
System integration		Export control	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profiles S and G, specifications at www.onvif.org	a.	<i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>
Analytics	Video motion detection, shock detection Support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications, see www.axis.com/acap	Environmental responsibility:	www.axis.com/environmental-responsibility
Event triggers	Analytics, Temperature, External input, Time scheduled, Edge storage events PTZ preset		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			
Casing	IP66- and NEMA 4X-rated Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B		