

AXIS T94Q01F Ceiling-and-Column Mount

For many installation scenarios

The powder-coated aluminum AXIS T94Q01F Ceiling-and-Column Mount can be used for both ceiling/soffit and column/parapet installations. This allows Axis' fixed camera housings to be mounted under hard surfaces such as ceilings, beams, soffits and canopies. It can also be mounted on pole or column tops, parapets and other horizontal building structures. Re-direction and maintenance of the camera is easy thanks to the swivel arm feature. The cable is routed through the pipe, and is never exposed to weather or potential vandalism. Cable conduits and Axis' conduit adapters (3/4" dimension) are used for cable protection when routed from the side.

- > For outdoors and indoors – ceilings, columns and parapets
- > Easy installation and camera maintenance
- > Sturdy and safe - keeps the camera steady year after year
- > Resistant to corrosion



AXIS T94Q01F Ceiling-and-Column Mount

General	
Supported products	AXIS T92E Series, AXIS T93F Series, AXIS T93E05, AXIS T93G05, AXIS Q16-E/P13-E/M11-E Network Cameras, AXIS Q1775-E Network Camera
Casing	NEMA 4X- and IK10-rated impact resistant aluminum mount Color: White NCS S 1002-B
Environment	Indoor Outdoor
Cable routing	Internal Back: Cable hole Side: Cable conduit holes M25 3/4"
Maximum load	5 kg (11 lb)
Angle	Arm: 360° Tilt: +25° to - 65° Pan: +100° to -100°
Approvals	IEC/EN/UL 60950-1
	IEC/EN/UL 60950-22 Vibration: Class 4M3 IEC 60068-2-6 and IEC 60068-2-27 EN 50581, REACH, CE
Dimensions	271 x 300.4 x 129.7 mm (11 x 12 x 5 in)
Weight	1.3 kg (3 lb)
Included accessories	Installation Guide
Optional accessories	AXIS ACI Conduit Adapter 3/4" NPS AXIS ACI Conduit Adapter 3/4" U-Shape 30 mm (1 in) AXIS Bird Control Spike For more accessories, see www.axis.com
Warranty	Axis 3-year warranty, see www.axis.com/warranty

Environmental responsibility:

www.axis.com/environmental-responsibility