

AXIS Q6135-LE PTZ Network Camera

High-speed PTZ with long-range optimizedIR

AXIS Q6135-LE offers HDTV 1080p with 32x optical zoom. It features OptimizedIR up to 250 m (820 ft) or more depending on the scene and Lightfinder 2.0 for clear, sharp images even in challenging light. Sharpdome technology allows you to see 20° above the horizon with the same sharp image quality as below. It includes orientation aid and autotracking 2 with click and track functionality. Privacy masking with mosaic lets you pixelate whole areas of the scene. It includes enhanced security features such as signed firmware, secure boot and TPM module. Plus, Axis Zipstream with support for H.264 and H.265.

- > [HDTV 1080p with 32x optical zoom](#)
- > [OptimizedIR \(250 m/820 ft range\)](#)
- > [Lightfinder 2.0](#)
- > [Autotracking 2 and orientation aid](#)
- > [TPM, FIPS 140-2 level 2 certified](#)



AXIS Q6135-LE PTZ Network Camera

Models	AXIS Q6135-LE 50 Hz AXIS Q6135-LE 60 Hz	Video: live stream open,day/night mode
Camera		Event actions
Image sensor	1/2.8" Progressive scan CMOS	Record video: SD card and network share Pre- and post-alarm video or image buffering for recording or upload Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Notification: email, HTTP, HTTPS, TCP, and SNMP trap PTZ: PTZ preset, guard tour Overlay text, day/night mode WDR mode IR illumination
Lens	Varifocal, 4.3-137.6 mm, F1.4 - 4.0 Horizontal field of view: 58.3°-2.4° Vertical field of view: 34.9°-1.3° Autofocus, auto-iris	Data streaming
Day and night	Automatically removable infrared-cut filter	Event data
Minimum illumination	Color: 0.06 lux at 30 IRE F1.4 B/W: 0.008 lux at 30 IRE F1.4, 0 lux with IR illumination on Color: 0.09 lux at 50 IRE F1.4 B/W: 0.01 lux at 50 IRE F1.4, 0 lux with IR illumination on	Built-in installation aids
Shutter speed	1/66500 s to 2s	Pixel counter, leveling guide
Pan/Tilt/Zoom	Pan: 360° endless, 0.05°-700°/s Tilt: +20 to -90°, 0.05°-500°/s Zoom: 32x optical, 12x digital, total 384x zoom Nadir flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, speed dry	Analytics
Video		Compute capabilities
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Machine learning processing unit (MLPU)
Resolution	1920x1080p (HDTV 1080p) to 320x180	AXIS Object Analytics
Frame rate	Up to 50/60 fps (50/60 Hz) in 1080p	Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	Applications
Image settings	Compression, saturation, brightness, sharpness, contrast, local contrast, white balance, exposure control, exposure zones, Forensic WDR: Up to 120 dB depending on scene, defogging, day/night shift level, tone mapping, fine tuning of low-light behavior, rotation: 0°, 180°, text and image overlay, image freeze on PTZ, electronic image stabilization (EIS), scene profiles, 32 individual polygon privacy masks	Included AXIS Object Analytics AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard AXIS Video Motion Detection, Autotracking 2, Active Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Audio		General
Audio input/output	Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology	Casing
Network		IK08, IK10 housing and mounting ^b , IP66- and NEMA 4X-rated Repaintable metal casing (aluminum), hard coated Polycarbonate (PC) clear dome with Sharpdome technology
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module	Sustainability
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTCIP, LLDP, MQTT v3.1.1, Syslog	PVC free
System integration		Memory
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-Click Cloud Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	1024 MB RAM, 512 MB Flash
Event conditions	Analytics Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready, PTZ autotracking Scheduled and recurring: scheduled event	Power
		Axis High PoE midspan 1-port: 100-240 V AC, max 74 W Camera consumption: typical 13.5 W (no IR), max 51 W Axis PoE+ midspan 1-port: 100-240 V AC, max 37 W IEEE 802.3at Type 2 Class 4 Camera consumption: typical 13.5 W, max 25 W
		Connectors
		RJ45 10BASE-T/100BASE-TX PoE RJ45 Push-pull Connector (IP66) Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
		IR illumination
		Optimized IR with power-efficient, long life 850 nm IR LEDs With 30 W midspan: Range of reach 190 m (623 ft) or more depending on the scene With 60 W midspan: Range of reach 250 m (820 ft) or more depending on the scene
		Storage
		Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
		Operating conditions
		With 30 W midspan: -30 °C to 50 °C (-22 °F to 122 °F) With 60 W midspan: -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10-100% RH (condensing)
		Storage conditions
		-40 °C to 70 °C (-40 °F to 158 °F) Humidity 5-95% RH (non-condensing)
		Approvals
		EMC EN 55032 Class A, EN 55035, EN 55024, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZSCISPR32 Class A KC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 risk group 2, IS13252

	Environment IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250, Type 4X, NEMA TS 2 (2.2.7–2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, ISO4892-2 Network NIST SP500-267 For midspan approvals, see: axis.com/products/axis-t8154-60-w-sfp-midspan	Video management software AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/vms
		Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty 5-year warranty, see axis.com/warranty
Dimensions	Height: 241 mm (9.5 in) ø 165 mm (6.4 in)	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i> b. <i>Mounting not included</i>
Weight	3 kg (6.6 lb)	Environmental responsibility: axis.com/environmental-responsibility
Included accessories	IP66-rated RJ45 connector kit, AXIS High PoE 60 W SFP Midspan, installation guide, Windows decoder 1-user licence	
Optional accessories	AXIS T91/T94 Mounting Accessories, Axis High PoE midspans For more accessories, see axis.com	