

## AXIS T94S01L Recessed Mount

### Swift and effortless ceiling installation

AXIS T94S01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations of indoor Axis fixed dome cameras. It features a patent-pending single-screw ceiling attachment design, which makes the installation quick and easy without having to remove the ceiling tile. Axis fixed dome camera attached to the recessed mount is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring.

- > [Cost-effective mount for Axis fixed dome cameras](#)
- > [Recessed ceiling installation made quick and easy](#)
- > [Enables sleek and discreet video surveillance](#)



## AXIS T94S01L Recessed Mount

General	
<b>Supported products</b>	AXIS P32-V/-LV Mk II Network Camera Series
<b>Casing</b>	Material: plastic Color: white NCS S 1002-B
<b>Sustainability</b>	PVC free
<b>Mounting</b>	Recessed in drop ceilings
<b>Environment</b>	Indoor
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	<b>Safety</b> IEC/EN/UL 60950-1 <b>Environment</b> IEC 60068-2-2, IEC 60068-2-6 (vibration), IEC 60068-2-27 (shock), IEC/EN 62262 IK08, REACH, RoHS, WEEE
<b>Dimensions</b>	<b>Outer dimensions</b> 252 x 179 x 146 mm (9.9 x 7.0 x 5.7 in)

Dimensions when recess-mounted with a camera  
Ø 179 mm (7.0 in), height 65 mm (2.6 in)

<b>Weight</b>	300 g (0.7 lb)
<b>Maximum load</b>	600 g (1.3 lb)
<b>Cable routing</b>	Top: cable hole
<b>Included accessories</b>	Installation Guide
<b>Optional accessories</b>	AXIS Safety Wire 3 m For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)