

AXIS T94M02L Recessed Mount

Discreet installation in drop and overhang ceiling

AXIS T94M02L Recessed Mount is designed for discreet installation in drop and overhang ceilings, and is compatible with AXIS P32-VE/-LVE, AXIS P33-VE/-LVE and AXIS Q35-VE/-LVE network camera models. The recessed mount is applicable for indoor environments as well as outdoor use in soffits. It is also suitable for installation in air-handling (plenum) spaces as the enclosure is made of metal alloy with a 3/4" (M25) conduit hole for protected cable routing.

- > [Mounting in drop ceiling and soffit](#)
- > [Indoor and outdoor use](#)
- > [Quick and easy installation](#)



AXIS T94M02L Recessed Mount

General		EN 50581
Supported products	AXIS P32-VE/-LVE Series AXIS P33-VE/-LVE Series AXIS Q35-VE/-LVE Series	Dimensions Height: 142 mm (5 19/32 in) Cover ring ø 240 mm (9 7/16 in) Ceiling tile hole ø 201 mm (7 29/32 in)
Mounting	Recessed in ceiling tiles	Weight 1.1 kg (2.68 lb)
Casing	Enclosure: Chromated aluminum alloy in natural color Cover ring: High-impact engineering polymer in white NCS S 1002-B	Included accessories Installation Guide, drill template, Gasket C M20, kit for changing between compatible cameras
Sustainability	PVC free	Optional accessories AXIS Safety wire 3m
Environment	Indoor and outdoor	Warranty Axis 3-year warranty, see www.axis.com/warranty
Cable routing	Back: Cable conduit holes 1/2" and 3/4"	
Approvals	IEC/EN 60950-1 IEC/EN 60950-22	

Environmental responsibility:
www.axis.com/environmental-responsibility