

AXIS TQ1809-LE Housing T92G

Robust and weather resistant with OptimizedIR

AXIS TQ1809-LE Housing T92G has a robust metal casing with IP66/IP67, NEMA 4X, and IK10 ratings for protection against dust, UV radiation, water and impact. It is spaciouly designed to house cameras with large CS-mount lenses and connecting accessories. With efficient cooling fins and heaters, the housing maintains optimal conditions for sensitive components, and enables cameras to operate in both extremely hot and cold environments. Suitable for fixed box cameras in both indoor and outdoor installations, AXIS TQ1809-LE offers built-in IR illumination for outstanding surveillance in the dark, and PoE connectivity for easy one-cable installation.

- > **Built-in IR illumination**
- > **Start-up in -40 °C to 60 °C (-40 °F to 140 °F)**
- > **Active cooling and heating**
- > **IP66, IP67 and IK10 rating**
- > **PoE connectivity**



AXIS TQ1809-LE Housing T92G

General	
Supported products	AXIS Q1615 Mk III Network Camera AXIS Q1645 Network Camera AXIS Q1647 Network Camera AXIS Q1715 Block Camera (HDMI and SDI outputs disabled) AXIS P1375 Network Camera AXIS P1377 Network Camera AXIS P1378 Network Camera
Casing	IP66-, IP67-, NEMA 4X- and IK10-rated Aluminum Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Power	Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4, max 25.5 W
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 30 m (98 ft) or more depending on the scene
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Start-up: -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A,
	ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, EN 55015, EN 61547 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, IEC/EN 62262 IK10, NEMA 250 Type 4X Other IEC 62471
Weight	5400 g (11.9 lb)
Included accessories	Installation guide, drill hole template, connector kit, Torx® T20 screw driver, sunshield, connector guard, AXIS T94Q01A Wall Mount
Optional accessories	T91 Mounting Accessories, T94 Mounting Accessories, YP3040 PT Motor, Bird Control Spikes, AXIS Door Switch A For more accessories, see axis.com
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility