

AXIS W703 Docking Station 8-bay

AXIS W703 Docking Station 8-bay enables easy handling of the body worn cameras with fast charging, quick, secure and easy data offloading.

- > **Grab and go, ready when you are**
- > **Dock and go, for automatic reliable offloading and fast charging**
- > **Reliable docking connectors**
- > **Splash proof**



AXIS W703 Docking Station 8-bay

Network		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10-85% RH (non-condensing)
Network protocols	IPv4, IPv6 USGv6, HTTPS, Bonjour, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP	Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A
Throughput	100 Mbit/s (per camera)	Safety	IEC/EN/UL 62368-1
General		Environment	IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-78
Capacity	8 bays	Network	Compatible with NIST SP500-267 throughput
Casing	Plastic casing Color: black NCS S 9000-N	Dimensions	Height: 52 mm (2.1 in) Width: 128 mm (5.1 in) Depth: 425 mm (16.8 in)
Mounting	Screws (included)	Weight	800 g (1.76 lb)
Sustainability	PVC free	Warranty	3-year warranty, see axis.com/warranty
Power	12 V DC, max 120 W		
Connectors	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T DC input Pogo pin pads		
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10-85% RH (non-condensing)		