

# AXIS A8207-VE Mk II Network Video Door Station

Multifunctional door station for better security solutions

AXIS A8207-VE Mk II Network Video Door Station combines a fully featured 6 MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID multi-frequency reader with support for most standard credential types including HID<sup>®</sup> iClass<sup>®</sup>, allowing you to integrate with other access control systems. By providing both surveillance and access for visitors and employees, AXIS A8207-VE Mk II increases the efficiency while keeping down the number of devices at the door. Interaction is intuitive and accessible, with an induction loop for hearing aids. Analytics, such as motion or sound detection, are supported.

- > **6MP wide-angle camera**
- > **Multiple hardware interfaces: audio input/output, relays, HDMI output, RS485**
- > **Easy integration with SIP, VAPIX, and ONVIF**
- > **Signed firmware with Secure Boot**
- > **Support for HID<sup>®</sup> iClass<sup>®</sup>**



# SIP

ONVIF<sup>®</sup> | GS

**HDTV**  
NETWORK VIDEO

# AXIS A8207-VE Mk II Network Video Door Station

<b>Camera</b>		<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Guardian with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at <a href="http://onvif.org">onvif.org</a>
<b>Image sensor</b>	1/2.9" progressive scan RGB CMOS	<b>VoIP</b>	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX Tested with various SIP software such as Cisco, Bria and Grandstream Tested with various PBX softwares such as Cisco, Avaya and Asterisk Phone book, parallel call forking, sequential call forking, call extension dialing
<b>Lens</b>	1.56 mm, F2.8 Horizontal field of view: 180° Vertical field of view: 120° Fixed focus, IR corrected, fixed iris	<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, active tampering alarm, audio detection <b>Supported</b> AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Minimum illumination</b>	LED lit: 0.0 lux LED unlit (with WDR): 0.7 lux LED unlit (without WDR): 0.55 lux	<b>Event triggers</b>	Analytics, external input, edge storage events, virtual inputs through API Call: DTMF, state, state changes Detectors: audio detection, live stream accessed, shock detection, tampering, PIR, motion alarm Hardware: Casing open, temperature, relays and outputs, network Input Signal: digital input port, manual trigger, virtual inputs Storage: disruption, recording System: system ready Time: recurrence, use schedule PTZ: moving, preset reached
<b>Shutter time</b>	1/143000 s to 2 s with 50 Hz 1/143000 s to 2 s with 60 Hz	<b>Event actions</b>	Axis door control HDMI Make call: SIP, API Terminate call: SIP, API Record video and audio: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS and TCP External output activation, play audio clip, overlay text, PTZ controls, status LED, WDR mode
<b>Video</b>		<b>Data streaming</b>	Event data
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles Motion JPEG	<b>General</b>	
<b>Resolution</b>	3072x2048 to 160x90	<b>Casing</b>	IP66 and NEMA 4X-rated, IK08 impact- and scratch-resistant glass Aluminum casing, polycarbonate (PC) hard-coated dome Color: metallic dark grey
<b>Frame rate</b>	Up to 30/25 fps (60/50 Hz) in all resolutions	<b>Sustainability</b>	PVC free
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	<b>PIR sensor</b>	Passive infrared (PIR) motion sensor.
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, forensic WDR: Up to 120 dB depending on scene, white balance, exposure mode, exposure zones, compression, text and image overlay, privacy masks	<b>Memory</b>	2048 MB RAM, 512 MB Flash
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Power</b>	<b>Power in:</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, or Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4, or 8-28 V DC min. 25 W <b>Power consumption:</b> typical 8 W, max 22 W <b>Power out:</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3: 24 V/0.05 A or 12 V/0.1 A. Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4, or 8-28 V DC: 24 V/0.3 A or 12 V/0.7 A <b>Relay rating:</b> 30 V, 1 A
<b>Audio</b>		<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX, PoE I/O: 6-pin terminal block for 4 alarm inputs/outputs DC input, 2 relays, line out, line in, microHDMI, RS485/Wiegand
<b>Audio streaming</b>	Two-way, full duplex Echo cancellation and noise reduction	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Audio compression</b>	384bit LPCM, AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16 kHz Configurable bit rate		
<b>Audio input/output</b>	Line input, line output, dual built-in microphone (can be disabled) T-coil Built-in speaker 73 dB (at 50 cm / 19.7 in)		
<b>Amplifier description</b>	Built-in 2 W Class D amplifier		
<b>RFID reader</b>			
<b>Entry authentication</b>	Card, tag, PIN, door code		
<b>Alarm status indication</b>	User feedback for access granted, access denied, keypad, armed, disarmed		
<b>Supported protocols</b>	RS485 (OSDP), Wiegand, VAPIX reader interface		
<b>Reader technology</b>	Generic 13.56 MHz (MIFARE Classic®, MIFARE Plus® (Level 1), MIFARE DESFire® EV1 and EV2, HID® iCLASS®, HID® iCLASS® Elite). Proximity 125 kHz (HID® Prox, EM-42xx, ISOProx II).		
<b>Accessibility</b>			
<b>Hearing loop</b>	T-coil 4 W Class D amplifier		
<b>User feedback</b>	Illuminated symbols, indicator stripe, illuminated buttons, audible feedback		
<b>Tampering</b>			
<b>Detection type</b>	Tamper switch, accelerometer (shock detection), video tampering		
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, signed firmware, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, secure boot		
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>b</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, SIP, SIPS, LLDP, STUN, TURN		
<b>System integration</b>			

<b>Operating conditions</b>	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 10-100% RH (condensing)	<b>Included accessories</b>	Installation guide, Torx® TR20 bit, terminal block connectors, connector guard
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)	<b>Optional accessories</b>	AXIS TA8201 Recessed Mount, AXIS A9801 Security Relay, AXIS T8133 Midspan, AXIS TA8601 Conduit Adapter 3/4" NPS, AXIS TA8801 Clear Dome Cover For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Approvals</b>	<b>EMC</b> EN 55032 Class A, EN 55024, EN 61000-6-2, FCC Part 15 Subpart B Class A and Subpart C and Subpart E <b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, UL 293, UL 294 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK08, NEMA 250 Type 4X <b>Other</b> EN 300330, EN 62311, RSS-Gen, RSS-210, EN 301 489-3, EN 303 348	<b>Video management software</b>	Video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Dimensions</b>	H x W x D: 248 x 106 x 51 mm (9 3/4 x 4 3/16 x 2 in)	<b>Languages</b>	English, German, French, Spanish, Italian
<b>Weight</b>	1.3 kg (2.9 lbs)	<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Mounting option</b>	Wall mount, wall mount with conduit pipe, or recessed with AXIS TA8201 Recessed Mount	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)