

AXIS Companion Dome mini LE

Outdoor full HD IR network camera

AXIS Companion Dome mini LE is an outdoor-ready day-and-night camera. It has built-in IR illumination for surveillance in total darkness and WDR technology that delivers sharp HD 1080p video even in scenes with complex light conditions. The compact design and weather-resistant enclosure enables discreet installations both indoors and out. Power over Ethernet (PoE) allows easy installation with a single cable to provide both network connectivity and electrical power. AXIS Companion Dome mini LE is supported only by the AXIS Companion video management software and mobile app, and requires an AXIS Companion Recorder for system completion.

- > **HD 1080p video quality**
- > **Surveillance in total darkness**
- > **Handles complex light conditions**
- > **Power over Ethernet (PoE)**
- > **Outdoor-ready**



AXIS Companion Dome mini LE

Camera		Typical 2.1 W, max 3.2 W
Image sensor	1/2.8" progressive scan RGB CMOS	Connectors
Lens	Horizontal field of view: 100° Vertical field of view: 53° Fixed iris and IR corrected	T/100BASE-TX PoE
Day and night	Automatically removable infrared-cut filter	IR illumination
Minimum illumination	0 lux with IR illumination on	Power-efficient, long-life 850 nm IR LEDs. Range of reach up to 15 m (49 ft) depending on scene
Camera angle adjustment	Pan: 350° Tilt: +/-70° Rotation: +/-95° Can be directed in any direction	Storage
Video		AXIS Companion Recorder is required
Video compression	H.265 (MPEG-H Part 2)	Operating conditions
Resolution	1920x1080 HDTV 1080p and 640x360	-20 °C to 50 °C (-4°F to 122°F) Humidity 10–85% RH
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Storage conditions
Video streaming	One high resolution and one low resolution, individually configurable streams Controllable frame rate	-40 °C to 65 °C (-40 °F to 149 °F)
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, rotation: 0°, 90°, 180°, 270°, including Corridor Format, privacy masks	Approvals
Wide dynamic range	WDR	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66
Network		Dimensions
Security	Password protection, HTTPS ^a encryption, digest authentication, user access log, signed firmware	Height: 70 mm (2 3/4 in) ø 120 mm (4 3/4 in)
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , Bonjour, UPnP [®] , DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP	Weight
System integration		205 g (0.45 lb)
Event triggers	Video motion detection	Included accessories
General		Installation guide Tool mounting RJ45
Casing	IP66-rated enclosure. Dome: clear PC. Bottom: PC+GF, black NCS S 9000-N. Cover: ASA, white NCS S 1002-B. For repainting instructions of casing and impact on warranty, contact your Axis partner.	Optional accessories
Sustainability	PVC free	AXIS T8415 Wireless installation tool AXIS T94B01P Conduit back box AXIS T91A27 Pole mount AXIS T94C01M J-box/gang box plate AXIS T94C01L Recessed mount AXIS T94C01U Universal mount AXIS Companion Weathershield A For more accessories, see axis.com
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1	Video management software
		AXIS Companion available on axis.com/vms
		Warranty
		Axis 3-year warranty, see axis.com/warranty
		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
		Environmental responsibility: axis.com/environmental-responsibility