

## AXIS F1035-E Sensor Unit

Fisheye lens for wide area surveillance indoors or outdoors

AXIS F1035-E is ideal for highly discreet, wide area coverage in indoor, outdoor and in-vehicle surveillance applications, such as in buses and trams. For use with an AXIS F Main Unit, AXIS F1035-E provides a 1080p resolution and a fisheye lens with a 194° horizontal field of view. The unit also supports Wide Dynamic Range (WDR) – Forensic Capture, ideal for scenes with very bright and dark areas. The rugged AXIS F1035-E withstands dust, rain, snow, vibration, shock and impact. It comes with a 3- or 12-m (10/39 ft.) pre-mounted cable for connection to a main unit. A vari-angle mounting bracket is included.

- > **Flexible, rugged design for indoor, outdoor and mobile use**
- > **Fisheye lens with 1080p resolution**
- > **Ultra-wide 194° horizontal field of view**
- > **WDR – Forensic Capture (with AXIS F41/F44 Main Unit)**



## AXIS F1035-E Sensor Unit

<b>Models</b>	AXIS F1035-E 3 m / 10 ft. cable: Fisheye, IP66/IP67-rated AXIS F1035-E 12 m / 39 ft. cable: Fisheye, IP66/IP67-rated	<b>General</b>	
<b>Camera</b>		<b>Casing</b>	IP66-, IP67-rated, Aluminum
<b>Image sensor</b>	1/2.8" (effective) progressive scan RGB CMOS	<b>Operating conditions</b>	-30 °C to 55 °C (-22 °F to 131 °F) Humidity 10-100% RH (condensing)
<b>Lens</b>	Fixed iris 1.3 mm, F2.8 With AXIS F34/F41/F44 in 1080p: Horizontal angle of view: 194° Vertical angle of view: 113° With AXIS F34/F44 in 720p: Horizontal angle of view: 112° Vertical angle of view: 66°	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Resolution</b>	Max. 1920x1200/1080	<b>Approvals</b>	ECE R10 rev.04, EN 50121-4, IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-78, IEC 60529 IP4X, IEC 62236-4, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581 IEC 60068-2-60, IEC 60529 IP66/IP67, IEC 60721-3-5 5M3 (vibration, shock), IEC/EN/UL 60950-22, NEMA 250 Type 4X
<b>Wide dynamic range</b>	WDR – Forensic Capture With AXIS F41: 1080p, 25/30 fps (50/60 Hz) With AXIS F44: 720p, 12.5/15 fps (50/60 Hz)	<b>Dimensions</b>	62 mm (2 7/16 in) ø 30 mm (1 3/16 in)
<b>Minimum illumination</b>	Color: 0.3 lux	<b>Weight</b>	3 m / 10 ft. cable: 96 g (0.21 lb) 12 m / 39 ft. cable: 346 g (0.76 lb)
<b>Shutter time</b>	With AXIS F34/F44: HDTV 720p 25/30 fps: 1/28000 s to 2 s 1080p 12.5/15 fps: 1/22500 s to 2 s With AXIS F41: HDTV 1080p 25/30/50/60 fps: 1/143000 s to 2 s WUXGA (1920x1200) 25/30 fps: 1/143000 s to 2 s	<b>Required hardware</b>	AXIS F34/F41/F44 Main Unit
<b>Frame rate</b>	Max. 50/60 fps (50/60 Hz)	<b>Included accessories</b>	Installation Guide AXIS F8201 Vari-angle Mounting Bracket
		<b>Optional accessories</b>	AXIS F8203 Fixed Mount Bracket AXIS F8204 Mounting Band AXIS F8212 Trim Ring AXIS F8235 Fisheye Accessory
		<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)