

## AXIS M3057-PLVE

6 MP outdoor-ready dome with 360° panoramic view and IR illumination

AXIS M3057-PLVE Network Camera delivers outstanding video in any light conditions, using Axis-developed Forensic WDR and Lightfinder technologies. With its integrated, automatically adaptable OptimizedIR illumination, this versatile camera even sees in the dark. The camera offers 360° overview as well as dewarped views. AXIS M3057-PLVE is vandal resistant (IK10) and discreetly designed. The optional black skin, which is also easily repaintable, can be used to further blend the camera into its environment. The camera has good capacity for analytics. It comes factory-focused and is designed for easy installation.

- > **6 MP sensor**
- > **OptimizedIR illumination**
- > **Lightfinder technology**
- > **Forensic WDR**
- > **Zipstream for reduced bandwidth and storage**



# AXIS M3057-PLVE

|  |   |                                   |   |
|--|---|-----------------------------------|---|
| <b>Camera</b>                            |   | <b>Event triggers</b>             | Analytics, supervised external input, virtual inputs through API, edge storage events   |
| <b>Image sensor</b>                      | 6 MP (3072x2048) 1/1.8" progressive scan RGB CMOS   | <b>Event actions</b>              | Record video: SD card and network share<br>Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email<br>Pre- and post-alarm video or image buffering for recording or upload<br>Notification: email, HTTP, HTTPS, TCP and SNMP trap<br>PTZ: PTZ preset, start/stop guard tour<br>Overlay text, external output activation  |
| <b>Lens</b>                              | Fixed iris, fixed focus, 1.6 mm, F2.0<br>Horizontal field of view: 185°<br>Vertical field of view: 185°   | <b>Data streaming</b>             | Event data  |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter   | <b>Built-in installation aids</b> | Pixel counter, digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views   |
| <b>Minimum illumination</b>              | Color: 0.16 lux at 50 IRE F2.0<br>B/W: 0.03 lux at 50 IRE F2.0<br>0 lux with IR illumination on   | <b>General</b>                    |   |
| <b>Shutter time</b>                      | 1/100 000 s to 2 s  | <b>Casing</b>                     | IP66- and NEMA 4X-rated, IK10 impact-resistant casing in polycarbonate and aluminium, with hard-coated dome and dehumidifying membrane<br>Encapsulated electronics and captive screws<br>Color: White NCS S 1002-B<br>For repainting, use the optional skin cover. Contact your Axis partner for instructions.  |
| <b>Camera angle adjustment</b>           | Rotation $n \pm 180^\circ$  | <b>Sustainability</b>             | PVC free  |
| <b>Video</b>                             |   | <b>Memory</b>                     | 2 GB RAM, 512 MB Flash  |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>Motion JPEG  | <b>Power</b>                      | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3<br>Typical 7.7 W, max 12.95 W   |
| <b>Resolution</b>                        | Overview: 2048x2048 to 160x160<br>Panorama: 2560x960 to 192x72<br>Double Panorama: 2560x1920 to 256x144<br>Quad view: 2560x1920 to 256x144<br>View area 1-4, 16:9: 2048x1152 to 256x144, 4:3: 1920x1440 to 320x240<br>Panorama corner left/right: 2368x1184 to 192x72<br>Double Panorama Corner: 2048x2048 to 320x240<br>Corridor: 2560x1920 to 256x144                     | <b>Connectors</b>                 | RJ45 10BASE-T/100BASE-TX PoE<br>Terminal block for 1 supervised alarm input and 1 digital output (12 V DC output, max. load 25 mA)<br>HDMI type D <sup>0</sup>  |
| <b>Frame rate</b>                        | 360° overview only, up to 2048x2048 without WDR: 50/60 fps @ 50/60 Hz<br>360° overview and dewarped views up to max resolution with WDR: up to 25/30 fps @ 50/60 Hz   | <b>IR illumination</b>            | Optimized IR with with power-efficient, long-life 850 nm IR LEDs with adaptable illumination intensity<br>Range of reach 20 m (66 ft) or more depending on scene  |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Axis Zipstream technology in H.264<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264  | <b>Storage</b>                    | Support for microSD/microSDHC card<br>Support for SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>   |
| <b>Multi-view streaming</b>              | 360° overview, dewarped panorama, double panorama, corridor and quad views. Up to 4 individually cropped out and dewarped view areas. All different views can be streamed simultaneously. When streaming 4 dewarped view areas and one 360° overview in max resolution: up to 14 fps per stream   | <b>Operating conditions</b>       | -40 °C to 50 °C (-40 °F to 122 °F)<br>Maximum temperature (intermittent): 55 °C (131 °F)<br>Start-up: -30 °C to 50 °C (-22 °F to 122 °F)<br>Humidity 10–100% RH (condensing)  |
| <b>HDMI output</b>                       | HDMI 1080p @ 50/60 fps (50/60 Hz)   | <b>Storage conditions</b>         | -40 °C to 65 °C (-40 °F to 149 °F)  |
| <b>Image settings</b>                    | Compression, color, brightness, sharpness, contrast, local contrast, white balance, exposure control (including automatic gain control) exposure zones, fine tuning of behavior at different light levels, forensic WDR: up to 120 dB depending on scene, dynamic text and image overlay, privacy masks, mirroring of images, rotation: 0°, 180°, including Corridor Format | <b>Approvals</b>                  | EMC<br>EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35<br>Safety<br>IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471<br>Environment<br>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X |
| <b>Pan/Tilt/Zoom</b>                     | Digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views, preset positions, guard tour  | <b>Dimensions</b>                 | Height: 66 mm (2 5/8 in)<br>ø 149 mm (5 7/8 in)   |
| <b>Network</b>                           |   | <b>Weight</b>                     | 770 g (1.7 lb)  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management   | <b>Included accessories</b>       | Installation guide, Windows <sup>®</sup> decoder 1-user license, drill hole template, cable gaskets, connector guard, I/O connector, Resistor <sup>®</sup> T20 L-key, mounting bracket, cable hole lid, view protector  |
| <b>Supported protocols</b>               | IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, HDMI 1.4b   | <b>Optional accessories</b>       | AXIS T94T02D Pendant Kit with weathershield, AXIS T94K01D Pendant Kit, AXIS T94S02L Recessed Mount Kit, AXIS M30 Skin Cover A Black, Axis Mounts & Cabinets<br>For more accessories, see <a href="http://www.axis.com">www.axis.com</a>   |
| <b>System integration</b>                |   | <b>Video management software</b>  | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/vms">www.axis.com/vms</a>  |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://onvif.org">onvif.org</a>               |                                   |   |
| <b>Analytics</b>                         | <b>Included</b><br>AXIS Video Motion Detection, active tampering alarm<br><b>Supported</b><br>AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>   |                                   |   |

|                  |   |  |
|------------------|---|--|
| <b>Languages</b> | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Polish, Portuguese, Traditional Chinese | b. <i>Make sure that the cable has a slim connector plug</i>   |
| <b>Warranty</b>  | Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>      | <b>Environmental responsibility:</b><br><a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a> |

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*