

AXIS P3245-V Network Camera

Streamlined HDTV 1080p fixed dome

AXIS P3245-V offers excellent image quality in HDTV 1080p under any light conditions. This streamlined, IK10-rated camera features Forensic WDR to provide clarity when there's both dark and light areas in the scene. And, Lightfinder 2.0 delivers video with more life-like colors and sharp video of moving objects. Including a varifocal lens with remote zoom and focus capabilities, it eliminates the need for hands-on fine tuning. This camera features enhanced security features to ensure the integrity and authenticity of the camera's firmware. Furthermore, it offers Axis Zipstream with support for H.264/H.265, which significantly reduces bandwidth and storage requirements.

- > [HDTV 1080p video quality](#)
- > [Remote zoom and focus](#)
- > [Lightfinder 2.0 and Forensic WDR](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [Signed firmware and secure boot](#)



AXIS P3245-V Network Camera

Camera	
Image sensor	1/2.8" progressive scan RGB CMOS
Lens	Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Remote zoom and focus, P-Iris control, IR corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE, F1.8 B/W: 0.02 lux at 50 IRE, F1.8
Shutter time	1/66500 s to 2 s
Camera angle adjustment	Pan ±180°, tilt ±75°, rotation ±175°
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 to 160x90
Frame rate	With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ, preset positions
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, SIP, LLDP
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Perimeter Defender, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, AXIS Occupancy Estimator, AXIS Queue Monitor, AXIS People Counter, AXIS Tailgating Detector, AXIS Direction Detection, AXIS Random Selector Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Event conditions	Analytics, edge storage events, virtual inputs through API
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email
	Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text, make call
Data streaming	Event data
Built-in installation aids	Pixel counter, remote focus, remote zoom
General	
Casing	IP52-rated, IK10 impact-resistant casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.
Mounting	Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
Sustainability	PVC free BVR/CFR free
Memory	1024 MB RAM, 512 MB Flash
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 3.5 W, max 5.7 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE
Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78 IEC/EN 60529 IP52, IEC/EN 62262 IK10 Network NIST SP500-267
Dimensions	Height: 103 mm (4.06 in) ø 149 mm (5.87 in)
Weight	650 g (1.4 lb)
Included accessories	Installation guide, Windows [®] decoder 1-user license, drill template, Resistor [®] T20 L-key, cable gaskets, connector guard
Optional accessories	AXIS TP3201 Recessed Mount, AXIS T94K01D Pendant Kit, AXIS ACI Conduit Adapters, Axis mounts, smoked dome, black casing For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility