

AXIS P3364-LVE Network Camera

Vandal-resistant with IR illumination, remote focus and zoom

AXIS P3364-LVE features Axis' OptimizedIR, an IR LED technology providing automatic illumination of a scene in complete darkness. The day and night camera offers superb video performance in HDTV 720p/1 MP resolution. It provides multiple, individually configurable H.264 and Motion JPEG video streams. Digital pan/tilt/zoom allows a view cropped from the full view to be streamed for viewing or recording. P-iris control provides optimal depth of field, resolution, image contrast and clarity. AXIS P3364-LVE supports Axis' Lightfinder technology, making it extremely sensitive to low light. With its weather-proof and vandal-resistant casing, it is perfectly adapted for harsh environments. Its operating temperature ranges from -40 °C to 55 °C (-40 °F to 131 °F).

- > [HDTV 720p/1 MP](#)
- > [Axis' OptimizedIR technology](#)
- > [Remote zoom and focus](#)
- > [IR illumination](#)
- > [Outdoor-ready and vandal-resistant design](#)



AXIS P3364-LVE Network Camera

Models	AXIS P3364-LVE 6 mm AXIS P3364-LVE 12 mm	Notification: email, HTTP, HTTPS and TCP Video recording to edge storage Pre- and post-alarm video buffering External output activation, Audio recording to edge storage, Play audio clip
Camera		
Image sensor	Progressive scan RGB CMOS 1/3"	
Lens	6 mm: 2.5–6 mm, F1.2 Horizontal angle of view: 105°–49° Vertical angle of view: 80°–37° 12 mm: 3.3–12 mm, F1.4 Horizontal angle of view: 82°–24° Vertical angle of view: 60°–18° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	6 mm: Color: 0.12 lux, F1.2, B/W: 0.03 lux, F1.2 12 mm: Color: 0.18 lux, F1.4, B/W: 0.04 lux, F1.4 B/W: 0 lux with IR illumination	
Shutter time	1/24500 s to 2 s	
Camera angle adjustment	Pan 360°, Tilt 170°, Rotation 340°	
Video		
Video compression	H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC), Motion JPEG	
Resolutions	1280x960 ^a (approx. 1.3 MP) to 160x90	
Frame rate	25/30 fps with power line frequency 50/60 Hz	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	
Pan/Tilt/Zoom	Digital PTZ	
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Mirroring of images, Privacy mask, Wide Dynamic Range – Dynamic Contrast Rotation 0°, 90°, 180°, 270°, including Corridor Format	
Audio		
Audio streaming	Two-way audio	
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Configurable bit rate	
Audio input/output	External microphone input or line input, Line output	
Network		
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X ^b network access control, Digest authentication, User access log	
Supported protocols	IPv4/v6, HTTP, HTTPS ^b , SSL/TLS ^b , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	
Analytics	Video motion detection, Active tampering alarm, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	
Event triggers	Analytics, Edge storage events External input	
Event actions	File upload: FTP, HTTP, HTTPS, network share and email	
Data streaming	Event data	
Built-in installation aids	Remote zoom, Remote focus, Pixel counter OptimizedIR with adjustable IR illumination angle and intensity	
General		
Casing	Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics IP66- and NEMA 4X-rated, IK10 impact-resistant casing with aluminum base and dehumidifying membrane Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner.	
Memory	256 MB RAM, 128 MB Flash	
Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.1 W	
Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out	
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs with adjustable angle of illumination and intensity. Range of reach up to 30 m (100 ft) depending on scene.	
Edge storage	Support for SD/SDHC/SDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com	
Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 10–100% RH (condensing)	
Approvals	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78 EN 50121-4, IEC 62236-4, IEC/EN/UL 60950-22, IEC 62262 IK10, IEC/EN 60529 IP66, NEMA 250 Type 4X EN 62471	
Dimensions	Ø178 x 119 mm (Ø7 x 4 11/16 in)	
Weight	1.4 kg (3.1 lb) without weather shield	
Included accessories	Installation Guide, Windows decoder 1-user license, Resistorx T20 screw driver, Drill hole template Connector kit, Mounting bracket, 5 m (16 ft) network cable with pre-mounted gasket	
Optional accessories	AXIS P33 Series Pendant Kit AXIS T8120 Midspan 15 W 1-port AXIS T8415 Wireless Installation Tool AXIS T94H01P Conduit Back Box	
Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	

- a. 1400x1050 (1.4MP) scaled resolution available via VAPIX[®]
b. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).

More information is available at www.axis.com