

## AXIS P3367-VE Network Camera

5-megapixel, light-sensitive with remote focus and zoom

AXIS P3367-VE is a fixed dome network camera that offers superb video performance in HDTV 1080p/5 MP resolution. It complies with the SMPTE 274M standard and can cover a large area with exceptional detail and light sensitivity. Wide dynamic range and day/night functionality provides high image quality even in low-light conditions. With multi-view streaming, the full view and up to 8 individually cropped out view areas can be streamed simultaneously. AXIS P3367-VE has support for digital pan/tilt/zoom, two-way audio, audio detection and input/output ports for external devices. With its weather-proof and vandal-resistant casing, it is perfectly adapted for harsh environments.

- > **HDTV 1080p/5 MP**
- > **P-Iris control**
- > **Remote zoom and focus**
- > **I/O ports and two-way audio**
- > **Outdoor-ready and IK10 vandal-resistance**



# AXIS P3367-VE Network Camera

|  |   |  |
|--|---|--|
| <b>Camera</b>                            |   | Detection, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>  |
| <b>Image sensor</b>                      | Progressive scan RGB CMOS 1/3.2"  | <b>Event triggers</b> Analytics, Edge storage events, External input   |
| <b>Lens</b>                              | 3–9 mm, F1.2<br>Horizontal angle of view: 84°–30°<br>Vertical angle of view: 63°–22°<br>Varifocal, Remote focus and zoom, P-Iris control, IR corrected  | <b>Event actions</b> File upload: FTP, FTPS, HTTP, HTTPS, network share and email<br>Notification: email, HTTP, HTTPS and TCP<br>Video recording to edge storage<br>Pre- and post-alarm video buffering<br>External output activation, Audio recording to edge storage, Play audio clip<br>Preset positions, Guard tour  |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter   | <b>Data streaming</b> Event data   |
| <b>Minimum illumination</b>              | Color: 0.2 lux, F1.2, B/W: 0.04 lux, F1.2   | <b>Built-in installation aids</b> Remote zoom, Remote focus, Pixel counter   |
| <b>Shutter time</b>                      | 1/28000 s to 2 s  | <b>General</b>   |
| <b>Camera angle adjustment</b>           | Pan 360°, Tilt 160°, Rotation 340°  | <b>Casing</b> Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics<br>IP66- and NEMA 4X-rated, IK10 impact-resistant casing with aluminum base and dehumidifying membrane<br>Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner.   |
| <b>Video</b>                             |   | <b>Memory</b> 512 MB RAM, 128 MB Flash   |
| <b>Video compression</b>                 | H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC)<br>Motion JPEG   | <b>Power</b> Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3<br>Max. 12.1 W  |
| <b>Resolutions</b>                       | 2592x1944 (5 MP) to 160x90  | <b>Connectors</b> RJ45 10BASE-T/100BASE-TX PoE<br>Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out   |
| <b>Frame rate</b>                        | 2 MP 4:3 (1600x1200) and HDTV 1080p (1920x1080) capture modes: 30 fps in all resolutions,<br>3 MP capture mode: 20 fps in all resolutions,<br>5 MP capture mode: 12 fps in all resolutions  | <b>Edge storage</b> Support for SD/SDHC/SDXC card<br>Support for recording to dedicated network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>   |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264  | <b>Operating conditions</b> -40 °C to 55 °C (-40 °F to 131 °F)<br>Humidity 10–100% RH (condensing)   |
| <b>Multi-view streaming</b>              | Up to 8 individually cropped out view areas<br>When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 12 fps per stream (5 MP capture mode) or 20 fps per stream (3 MP capture mode)   | <b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)   |
| <b>Pan/Tilt/Zoom</b>                     | Digital PTZ<br>Preset positions, Guard tour   | <b>Approvals</b> EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78<br>EN 50121-4, IEC 62236-4, IEC/EN/UL 60950-22, IEC 62262 IK10, IEC/EN 60529 IP66, NEMA 250 Type 4X |
| <b>Image settings</b>                    | Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Mirroring of images, Privacy mask<br>Rotation 0°, 90°, 180°, 270°, including Corridor Format<br>Wide Dynamic Range - Dynamic Contrast | <b>Weight</b> 1.7 kg (3.7 lb), with weather shield   |
| <b>Audio</b>                             |   | <b>Dimensions</b> Ø178 x 117 (Ø7 x 4 5/8 in)   |
| <b>Audio streaming</b>                   | Two-way audio   | <b>Included accessories</b> Installation Guide, Windows decoder 1-user license, Resistorx T20 screw driver, Drill hole template<br>Connector kit, Mounting bracket, Smoked dome, Weather shield, 5 m (16 ft) network cable with pre-mounted gasket   |
| <b>Audio compression</b>                 | AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz<br>Configurable bit rate  | <b>Video management software</b> AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>   |
| <b>Audio input/output</b>                | External microphone input or line input, Line output  | <b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese  |
| <b>Network</b>                           |   | <b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>   |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log   | a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit ( <a href="http://www.openssl.org/">http://www.openssl.org/</a> ), and cryptographic software written by Eric Young ( <a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a> ).  |
| <b>Supported protocols</b>               | IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, SFTP, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH  | <b>More information is available at <a href="http://www.axis.com">www.axis.com</a></b>   |
| <b>System integration</b>                |   |  |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform, specifications at <a href="http://www.axis.com">www.axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>           |  |
| <b>Analytics</b>                         | Video motion detection, Active tampering alarm, Audio detection<br>Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line   |  |