

AXIS S1116 MT

Out-of-the box ready workstation for high-definition surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [3-year hardware warranty with on-site replacement service](#)



AXIS S1116 MT

Licenses	16 AXIS Camera Station core licenses included, can be upgraded up to 32 licenses (sold separately)		1x Universal audio jack 1x Audio line out 1x Serial port
Processor	Intel® Core i5-8400		
Memory	8 GB		
Storage	8 TB (1x8 TB) Enterprise Class HDD, 7200 rpm Additional storage 8 TB (1 free bay)		
Operating system	Microsoft® Windows® 10 Enterprise Operating system recovery: yes Operating system drive: 128 GB SSD		
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view Playback: 4 x 1080p camera split views or 1 x 4K camera view Supports two monitors.		
Recording	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.		
Graphic card	Intel® HD Graphics 630		
Power	360 W (100 - 240 V AC, 50/60 Hz, 5.0 - 2.5 A)		
Connectors	5x USB 3.1 1x USB 3.1 Type-C 4x USB 2.0 2x DisplayPort™ 1.2 1x Ethernet (RJ45)		
		Operating conditions	0 °C to 45 °C (32 °F to 113 °F)
		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals	IEC/EN/UL 60950-1 FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, EAC, BSMI, NOM
		Dimensions	274 x 154 x 350 mm (13.8 x 6.1 x 10.8 in)
		Weight	7.4 kg (16 lb)
		Included accessories	Power cord, keyboard, mouse
		Optional accessories	Axis joysticks and control boards For more accessories, see axis.com
		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
		Environmental responsibility:	www.axis.com/environmental-responsibility