

# AXIS T8154 60 W SFP Midspan

For network or fiber installations

AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers High PoE 60 W. It works with all Axis network products supporting Power over Ethernet.

- > **SFP slot for fiber**
- > **Integrated midspan**
- > **High PoE 60 W**
- > **Support for all Axis network products**



**Data**

A black horizontal line with solid black circles at each end, representing a data connection.

**PoE**

A yellow horizontal line with solid yellow circles at each end, representing a PoE connection.

## AXIS T8154 60 W SFP Midspan

Midspans		General	
<b>Function</b>	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support	<b>Display and indicators</b>	Port interfaces are located on the front panel PoE LED Power LED
<b>Data rate</b>	10/100/1000 Mbps	<b>Mounting</b>	Wall, shelf or DIN rail <sup>a</sup>
<b>Installation and management</b>	Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display	<b>Operating conditions</b>	<b>Up to 30 W:</b> -10 °C to 55 °C (14 °F to 131 °F) <b>Up to 60 W:</b> -10 °C to 45 °C (14 °F to 113 °F) Humidity max 90% RH (non-condensing)
<b>Data &amp; power</b>		<b>Storage conditions</b>	-20 °C to 70 °C (-4 °F to 158 °F) Humidity max 95% RH (non-condensing)
<b>Power</b>	High Power over Ethernet, max 60 W	<b>Approvals</b>	<b>Safety:</b> IEC/EN/UL 60950-1, KC, CCC, CB, S-Mark, GS Mark per EN 60950-1 <b>EMC:</b> EN 55022 Class A, EN 55032 Class A, EN 61000 3-2, EN 61000 3-3, EN 55024, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A, KCC KN32 Class A, KN35, EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4 <b>Environment:</b> RoHS, REACH, WEEE
<b>Input power</b>	AC input voltage: 100 to 240 V AC AC frequency: 50-60 Hz	<b>Dimensions</b>	50 x 80 x 184 mm (2.0 x 3.1 x 7.2 in)
<b>Max. output power</b>	56 V DC (max 60 W)	<b>Weight</b>	517 g (1.1 lb)
<b>Connectors</b>	Shielded RJ45, EIA 568A and 568B SFP slot Power connector C14	<b>Optional accessories</b>	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13-Open 0.5 m AXIS T8611 SFP Module LC.LX AXIS T8612 SFP Module LC.SX AXIS T8613 SFP Module 1000BASE-T For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Wiring</b>	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 1/2 (-), 3/6 (+), 4/5 (+) and 7/8 (-)	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

a. Sold as optional accessory

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)