

AXIS T8606 Media Converter Switch 24 V DC

AXIS T8606 Media Converter Switch 24 V DC allows connection to the network using standard Ethernet or fiber optic cables that help lower the cost of installing the cameras over long distances. Perfect for city surveillance, airports and other long distance installations, AXIS T8606 is a DIN-mounted device that can convert an Ethernet signal to be used over optical fiber cable. Surveillance integrators in the field can also connect installation monitors and laptops (via the RJ45 connectors) to AXIS T8606 for camera maintenance and control. The media converter switch can be connected in a daisy chain network.

- > **24 V DC IN**
- > **Convert Ethernet to optical fiber**
- > **Support for 10/100 Mbps**
- > **Two SFP slots and two RJ45 ports**
- > **Compatible with Axis network products**



| General | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported products | All Axis network video products |
| Casing | Metal Color: White NCS S 1002-B |
| Power | 24 V DC, max 3.5 W (power supply not included) |
| Connectors | 2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP) CAT5 or higher.) 2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP for copper modules 1x power |
| Display and indicators | Power LED indicator Network LED indicator (4x) |
| Compliance | RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756 |
| Mounting | DIN Rail mount |
| Environment | Indoor/Cabinet |
| Operating conditions | -40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing) |
| Storage conditions | -40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing) |

| | |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals | EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32, KCC KN32 Class A, KN35 Safety IEC/EN 60950-1 |
| Dimensions | 150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in) |
| Weight | 284 g (0.63 lb) |
| Included accessories | Bracket Mount DIN Clip, Installation Guide |
| Warranty | Axis 3-year warranty, see www.axis.com/warranty |

Environmental responsibility:

www.axis.com/environmental-responsibility