

AXIS T92E05 Protective Housing

For protection against weather and vandalism

AXIS T92E05 protects Axis fixed network camera in environments where temperature management is not a demand, such as subways or shopping malls. No power connection is required. AXIS T92E05 is IP66- and NEMA 4X-rated against the ingress of dust, rain, high-pressure water jets and damage from external ice formation. It is also IK10-rated for protection against impact and vandal acts. The network cable is protected inside the wall mount to enhance vandal protection. It comes with a wall mount with an internal cable channel and ball joint.

- > [IP66- and NEMA 4X-rated](#)
- > [IK10-rated](#)
- > [One-cable installation](#)



AXIS T92E05 Protective Housing

Supported cameras	<p>AXIS M1124/M1125 Indoor models of AXIS P13 Series AXIS Q1604/Q1614/Q1615 AXIS Q1775</p>	<p>AXIS Q1775: PoE IEEE 802.3af/at: 0 °C to 50 °C (23 °F to 122 °F) Humidity 15-100% RH (condensing)</p>
Casing	<p>Aluminium casing, polycarbonate sunshield and cable cover IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure Color: White NCS 1002-B</p>	<p>Approvals IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10</p>
Power	Not required	<p>Weight 2.4 kg (5.1 lb)</p>
Environment	Indoor/Outdoor	<p>Included accessories AXIS T94Q01A Wall Mount AXIS T92E Camera Holder Plate C Cable Gland M20x1.5, RJ45 Front glass kit Sunshield Kit Installation Guide, Screw driver torx 20</p>
Operating conditions	<p>AXIS M1124/M1125: PoE IEEE 802.3af/at: -20 °C to 50 °C (-4 °F to 122 °F) Humidity 15-100% RH (condensing) Indoor models of AXIS P13 Series: PoE IEEE 802.3af/at: 0 °C to 50 °C (32 °F to 122 °F) Humidity 15-100% RH (condensing) AXIS Q1604/Q1614: PoE IEEE 802.3af/at: 0 °C to 50 °C (32 °F to 122 °F) Humidity 15-100% RH (condensing) AXIS Q1615: PoE IEEE 802.3af/at: 0 °C to 55 °C (32 °F to 131 °F) Humidity 15-100% RH (condensing)</p>	<p>Optional accessories AXIS T94R01P Conduit Back Box AXIS Bird Control Spike AXIS T8120 Midspan 15 W 1-port AXIS T8133 Midspan 30 W 1-port YP3040 Pan-Tilt Motor</p>
		<p>Warranty Axis 3-year warranty, www.axis.com/warranty</p>

Environmental responsibility:
www.axis.com/environmental-responsibility