

DHL55

55" Full-HD LCD Monitor



Features :

- Industrial level DID LCD panel, suitable for extensive 7x24 continuous works
- High fidelity digital processing, brilliant and vivid video
- 8ms fast response time, no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Brightness smart detection, power-saving
- Using Tamper-proof metal housing, no radiation
- Professional thermal design to extend equipment lifespan



Technical Specification

Model	
Model	DHL55
System	
Diagonal	54.6"(16:9)
Resolution	1920x1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	400 cd/ m ²
Contrast	1200:1
Angle of view	178°/178°(vertical/horizontal)
Response time	8ms

Signals

Input	standard	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1, USB
	optional	Audio×1, RJ45×1, HDCVI×1, SDI×1, DP×1
Output	Standard	CVBS(BNC)×2, RS232×1
	optional	DP×1

General

Consumption (Standard)	130W
Consumption (Standby)	≤1W

Power Supply	AC100~240V (+/-10%), 50/60 Hz
Weight	35kg
Dimensions(no base)	1263.10x743.90x50.30mm
Work Environment	Temperature:0 C~50 C
	Humidity:20%~90%

Accessory

Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

Dimensions(mm)

