



POI-3010 Version: 1

Gigabit PoE Injector, 802.3at/af PoE, 30W

The LevelOne POI-3010 is a single port, high power PoE PSE solution for remote PoE PD devices. Generating up to 30W, POI-3010 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras and videophones. It complies with IEEE 802.3at PoE standard and is backward to IEEE802.3af. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points. For all the function featured in POI-3010, people can get the benefit of flexible network installation at lower cost, less downtime. It also provides a high-bandwidth pipe to the network.

Key Features

- IEEE 802.3af/at PoE PSE with 30W power budget
- Auto-detection and protection of non-standard PoE devices
- Unique interlocking feature for easy installation
- 10/100/1000Mbps wire speed transmission and reception

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10Base-T, Ethernet
IEEE 802.3u 100Base-TX, Fast Ethernet
IEEE802.3ab 1000Base-T, Gigabit Ethernet
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.3at Power over Ethernet Plus (PoE+)

Port:

1 x 10/100/1000Base-T RJ-45 Input Port
1 x 10/100/1000Base-T RJ-45 PoE Output Port

Indicator:

Power, PoE

Pin Assignment and Polarity:

1/2 (+), 3/6 (-)

Power Input:

100-240V AC, 50/60Hz, 0.8A

Power Output:

PoE DC 52V / 0.6A (30W)



Power Consumption:
30W (Max.)

Features

PoE:
IEEE 802.3af/at compliant

Environment

Operating Temperature (°C):
0°C ~ 45°C

Operating Humidity (Non-condensing):
5% to 95%

Storage Temperature (°C):
0°C ~ 70°C

Storage Humidity (Non-condensing):
5% to 95%

Installation:
Wall mount

Physical Specifications

Dimensions (W x D x H mm):
87.9 x 51.3 x 166 mm

Weight (g):
350g

Reliability

MTBF:
87.0966(K.hrs)

Approval and Compliance

EMI/EMS:
FCC Part 15, CE, RoHS

Safety:
EN 60950-1

Order Information

POI-3010

Package Contents

POI-3010
Quick Installation Guide
Power Cord

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.