

# ProductOverview

24.01.2022 English EUR



BeyondHumanVision

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.  
HS = Harmonized System Code DG = Discount Group  
MOBOTIX • 24.01.2022 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 24.01.2022

**MOBOTIX**

# Professional Video Systems Outdoor





BeyondHumanVision

MOBOTIX

## M73A

## MOBOTIX 7 Solution Platform

Weatherproof (IP66) Fixed Network Camera (Body) in two color variants, modular design with separately orderable optical 4K UHD image sensor modules (optimized for day, night or day & night use) and separately orderable function modules for easy insertion in the front panel (3 module openings, can be assigned as required), module connection via MOBOTIX sensor cables pre-positioned in the camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>Mx-M73A-LSA</b>  <b>M73 Body with LSA Connector Box (white)</b>  M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone &amp; Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 3 years (optionally extendable up to 8 years)</p>	<p>4047438036825  85258091  2.500 g</p>	<p>29,6 cm  26,8 cm  18,0 cm  14,3 l</p>
	<p><b>Mx-M73A-LSA-wg</b>  <b>M73 Body with LSA Connector Box (white-gray)</b>  M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone &amp; Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • • Housing: Aluminium, PBT-30GF • Color: white-gray • Warranty: 3 years (optionally extendable up to 8 years)</p>	<p>4047438036832  85258091  2.500 g</p>	<p>29,6 cm  26,8 cm  18,0 cm  14,3 l</p>
	<p><b>Mx-M73A-RJ45</b>  <b>M73 Body with RJ45 Connector Box (white)</b>  M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone &amp; Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 3 years (optionally extendable up to 8 years)</p>	<p>4047438034982  85258091  2.500 g</p>	<p>29,6 cm  26,8 cm  18,0 cm  14,3 l</p>
	<p><b>Mx-M73A-RJ45-wg</b>  <b>M73 Body with RJ45 Connector Box (white-gray)</b>  M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone &amp; Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • • Housing: Aluminium, PBT-30GF • Color: white-gray • Warranty: 3 years (optionally extendable up to 8 years)</p>	<p>4047438034999  85258091  2.500 g</p>	<p>29,6 cm  26,8 cm  18,0 cm  14,3 l</p>

## D71 Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-D71A-4DN050</b>	4047438039741	19,6 cm
	<b>D71 Complete Camera 4MP Ultra LowLight DN050 (Day)</b> D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-4DN080</b>	4047438039758	19,6 cm
	<b>D71 Complete Camera 4MP Ultra LowLight DN080 (Day)</b> D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-4DN100</b>	4047438039765	19,6 cm
	<b>D71 Complete Camera 4MP Ultra LowLight DN100 (Day)</b> D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-4DN150</b>	4047438039772	19,6 cm
	<b>D71 Complete Camera 4MP Ultra LowLight DN150 (Day)</b> D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-4DN280</b>	4047438039789	19,6 cm
	<b>D71 Complete Camera 4MP Ultra LowLight DN280 (Day)</b> D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-8DN050</b>	4047438039697	19,6 cm
	<b>D71 Complete Camera 4K DN050 (Day/Night)</b> D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l
	<b>Mx-D71A-8DN080</b>	4047438039703	19,6 cm
	<b>D71 Complete Camera 4K DN080 (Day/Night)</b> D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	85258091	18,0 cm
		1.180 g	14,8 cm
			5,2 l



**Mx-D71A-8DN100****D71 Complete Camera 4K DN100 (Day(Night))**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039710	19,6 cm
85258091	18,0 cm
1.180 G	14,8 cm
	5,2 l

**Mx-D71A-8DN150****D71 Complete Camera 4K DN150 (Day(Night))**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included


4047438039727	19,6 cm
85258091	18,0 cm
1.180 G	14,8 cm
	5,2 l

**Mx-D71A-8DN280****D71 Complete Camera 4K DN280 (Day(Night))**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 with standard dome • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included


4047438039734	19,6 cm
85258091	18,0 cm
1.180 G	14,8 cm
	5,2 l

## Q71A Hemispheric Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-Q71A-12DN016</b>	4047438039796	19,6 cm
	<b>Q71 Complete Camera 12MP, DN016 (Day/Night)</b>	85258091	18,0 cm
	Q71 camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 12MP image sensor • 4K effective resolution: 2880x2880 (hemispheric original image) • Max. Frame rate (4K): 20 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR and white light LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • IP66 - IK10 with standard lens cover • Operating temperature range: -40 to +65 °C • Built-in speaker and microphone - Line In & Out - Input & Output • USB-C • 8GB memory card included	1.050 g	14,8 cm
			5,2 l

## M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M16B</b> <b>M16B Body, For M16 Sensor Modules (Day/Night)</b> M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	4047438030915 85258091 1.764 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N036</b> <b>M16B Complete Cam 6MP, 2x B036 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030922 85258091 1.981 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N041</b> <b>M16B Complete Cam 6MP, 2x B041 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030939 85258091 1.974 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N061</b> <b>M16B Complete Cam 6MP, 2x B061 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030946 85258091 1.980 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N079</b> <b>M16B Complete Cam 6MP, 2x B079 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030953 85258091 1.971 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

**Mx-M16B-6D6N119****M16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030960	29,6 cm
85258091	19,6 cm
1.970	18,0 cm
	10,4 l







**Mx-M16B-6D6N237****M16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030977	29,6 cm
85258091	19,6 cm
1.981	18,0 cm
	10,4 l

## D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-D16B</b>	4047438030588	39,5 cm
	<b>D16B Body, For D16B/D15 Sensor Modules (Day/Night)</b> IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 31° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	85258091 1.277 g	29,6 cm 9,0 cm 10,5 l
	<b>Mx-D16B-F-6D6N036</b>	4047438030595	39,5 cm
	<b>D16B Complete Cam 6MP, 2x B036 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	85258091 1.646 g	29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N041</b>	4047438030601	39,5 cm
	<b>D16B Complete Cam 6MP, 2x B041 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	85258091 1.627 g	29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N061</b>	4047438030618	39,5 cm
	<b>D16B Complete Cam 6MP, 2x B061 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	85258091 1.642 g	29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N079</b>	4047438030625	39,5 cm
	<b>D16B Complete Cam 6MP, 2x B079 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	85258091 1.645 g	29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N119</b>	4047438030632	39,5 cm
	<b>D16B Complete Cam 6MP, 2x B119 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	85258091 1.630 g	29,6 cm 18,0 cm 21,0 l



**Mx-D16B-P-6D6D041****D16B Complete Cam 2x 6MP, Panorama 180° (Day)**

IP camera with PAN lens bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030656	39,5 cm
85258091	29,6 cm
1.650 9	18,0 cm
	21,0 l








**Mx-D16B-P-6N6N041****D16B Complete Cam 2x 6MP, Panorama 180° (Night)**

IP camera with PAN sensor bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030663	39,5 cm
85258091	29,6 cm
1.642 9	18,0 cm
	21,0 l

## V16B Vandalism Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-V16B-6D041</b>	4047438031462	26,0 cm
	<b>V16B Complete Cam 6MP, 1x B041 (Day)</b> V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D079</b>	4047438031479	26,0 cm
	<b>V16B Complete Cam 6MP, 1x B079 (Day)</b> V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6D041</b>	4047438031486	26,0 cm
	<b>V16B Complete Cam 6MP, 2x B041 (Day)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6D079</b>	4047438031493	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B079 (Day)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6N041</b>	4047438031509	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B041 (Day &amp; Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6N079</b>	4047438031516	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B079 (Day &amp; Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6N6N041</b>	4047438031523	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B041 (Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm

**Mx-V16B-6N6N079****V16B Complete Cam 2x 6MP, 2x B079 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing


4047438031530 26,0 cm

85258091 26,0 cm

4.700 g 26,0 cm

17,6 l

## S74A

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S74A</b>	4047438035552	29,6 cm
	<b>S74 Body for 4 Sensor- and Functional Modules</b>	85258091	19,6 cm
	S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 or 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white	1.400 g	9,0 cm
	• Warranty: 3 years (optionally extendable up to 8 years)		5,2 l

## S16B DualFlex Camera „Mx6B“



Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S16B</b> <b>S16B Body, For S16B/S15 Sensor Modules</b> S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box	4047438031400 85258091 660 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-S16B-S1</b> <b>S16B Complete Cam, Set 1, 6MP, 1x B016 (Day)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)	4047438031417 85258091 720 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>Mx-S16B-S2</b> <b>S16B Complete Cam, Set 2, 6MP, 2x B016 (Day)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	4047438031424 85258091 1.700 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>Mx-S16B-S3</b> <b>S16B Complete Cam, Set 3, 6MP, 2x B016 (Day &amp; Night)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	4047438031431 85258091 1.700 g	29,6 cm 19,6 cm 9,0 cm 5,2 l



## S26B Flex Camera „Mx6B“







Second Mx6 generation – with MxBus functionality and enhanced performance.







	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S26B-6D016</b>	4047438031448	19,6 cm
	<b>S26B Complete Cam 6MP, B016 (Day)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091 685 g	15,0 cm 9,0 cm 2,6 l
	<b>Mx-S26B-6N016</b>	4047438031455	19,6 cm
	<b>S26B Complete Cam 6MP, B016 (Night)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091 685 g	15,0 cm 9,0 cm 2,6 l

## M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.





	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M26B-6D</b> <b>M26B Body 6MP (Day)</b> IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031042 85258091 1.337 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D016</b> <b>M26B Complete Cam 6MP, B016 (Day)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031059 85258091 1.342 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D036</b> <b>M26B Complete Cam 6MP, B036 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031066 85258091 1.365 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D041</b> <b>M26B Complete Cam 6MP, B041 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031073 85258091 1.354 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D061</b> <b>M26B Complete Cam 6MP, B061 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031080 85258091 1.361 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D079</b> <b>M26B Complete Cam 6MP, B079 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031097 85258091 1.359 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

	<p><b>Mx-M26B-6D119</b>  <b>M26B Complete Cam 6MP, B119 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031103 29,6 cm            85258091 19,6 cm            1.359 9 18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6D237</b>  <b>M26B Complete Cam 6MP, B237 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031110 29,6 cm            85258091 19,6 cm            1.359 9 18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6D500</b>  <b>M26B Complete Cam 6MP, B500 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031127 29,6 cm            85258091 19,6 cm            2.000 9 18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N</b>  <b>M26B Body 6MP (Night)</b>            IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031134 29,6 cm            85258091 19,6 cm            1.344 9 18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N016</b>  <b>M26B Complete Cam 6MP, B016 (Night)</b>            Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031141 29,6 cm            85258091 19,6 cm            1.342 9 18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N036</b>  <b>M26B Complete Cam 6MP, B036 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031158 29,6 cm            85258091 19,6 cm            1.365 9 18,0 cm            10,4 l</p>








	<p><b>Mx-M26B-6N041</b>  <b>M26B Complete Cam 6MP, B041 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031165            85258091            1.354 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N061</b>  <b>M26B Complete Cam 6MP, B061 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031172            85258091            1.361 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N079</b>  <b>M26B Complete Cam 6MP, B079 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031189            85258091            1.359 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N119</b>  <b>M26B Complete Cam 6MP, B119 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031196            85258091            1.359 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N237</b>  <b>M26B Complete Cam 6MP, B237 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031202            85258091            1.359 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N500</b>  <b>M26B Complete Cam 6MP, B500 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031219            85258091            1.366 9</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>

## D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.



	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-D26B-6D</b> <b>D26B Body 6MP (Day)</b> D26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030670 85258091 799 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D036</b> <b>D26B Complete Cam 6MP, B036 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030687 85258091 814 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D041</b> <b>D26B Complete Cam 6MP, B041 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030694 85258091 762 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D061</b> <b>D26B Complete Cam 6MP, B061 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030700 85258091 814 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D079</b> <b>D26B Complete Cam 6MP, B079 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessor)	4047438030717 85258091 1.580 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D119</b> <b>D26B Complete Cam 6MP, B119 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030724 85258091 1.580 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-D26B-6D237</b> <b>D26B Complete Cam 6MP, B237 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030731 85258091 815 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



	<p><b>Mx-D26B-6N</b>  <b>D26B Body 6MP (Night)</b></p> <p>D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030748  85258091  799 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N036</b>  <b>D26B Complete Cam 6MP, B036 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030755  85258091  814 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N041</b>  <b>D26B Complete Cam 6MP, B041 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030762  85258091  1.580 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N061</b>  <b>D26B Complete Cam 6MP, B061 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030779  85258091  1.580 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N079</b>  <b>D26B Complete Cam 6MP, B079 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030786  85258091  1.580 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N119</b>  <b>D26B Complete Cam 6MP, B119 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030793  85258091  1.580 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N237</b>  <b>D26B Complete Cam 6MP, B237 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030809  85258091  1.580 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>

## Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-Q26B-6D016</b>	4047438031387	29,6 cm
	<b>Q26B Complete Cam 6MP, B016 (Day)</b>	85258091	19,6 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	853 g	9,0 cm 5,2 l
	<b>Mx-Q26B-6N016</b>	4047438031394	29,6 cm
	<b>Q26B Complete Cam 6MP, B016 (Night)</b>	85258091	19,6 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	855 g	9,0 cm 5,2 l







# Professional Video Systems Indoor





BeyondHumanVision

MOBOTIX

## c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-c26B-6D</b>	4047438030489	19,6 cm
	<b>c26B Body 6MP (Day)</b> c26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		431 g	9,0 cm
			2,6 l
	<b>Mx-c26B-6D016</b>	4047438030496	19,6 cm
	<b>c26B Complete Cam 6MP, B016, Day</b> Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		433 g	9,0 cm
			2,6 l
	<b>Mx-c26B-6D036</b>	4047438030502	19,6 cm
	<b>c26B Complete Cam 6MP, B036, Day</b> IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		444 g	9,0 cm
			2,6 l
	<b>Mx-c26B-6N</b>	4047438030519	19,6 cm
	<b>c26B Body 6MP (Night)</b> c26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		431 g	9,0 cm
			2,6 l
	<b>Mx-c26B-6N016</b>	4047438030526	19,6 cm
	<b>c26B Complete Cam 6MP, B016, Night</b> Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		433 g	9,0 cm
			2,6 l
	<b>Mx-c26B-6N036</b>	4047438030533	19,6 cm
	<b>c26B Complete Cam 6MP, B036, Night</b> IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	85258091	15,0 cm
		444 g	9,0 cm
			2,6 l

	<p><b>Mx-c26B-AU-6D016</b>  <b>c26B Complete Cam 6MP, B016, Day, Audio Package</b>  Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438030540 19,6 cm  85258091 15,0 cm  442 9 9,0 cm  2,6 l</p>
	<p><b>Mx-c26B-AU-6D036</b>  <b>c26B Complete Cam 6MP, B036, Day, Audio Package</b>  IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438030557 19,6 cm  85258091 15,0 cm  446 9 9,0 cm  2,6 l</p>
	<p><b>Mx-c26B-AU-6N016</b>  <b>c26B Complete Cam 6MP, B016, Night, Audio Package</b>  Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438030564 19,6 cm  85258091 15,0 cm  452 9 9,0 cm  2,6 l</p>
	<p><b>Mx-c26B-AU-6N036</b>  <b>c26B Complete Cam 6MP, B036, Night, Audio Package</b>  IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438030571 19,6 cm  85258091 15,0 cm  446 9 9,0 cm  2,6 l</p>



## i26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-i26B-6D</b> <b>i26B Body 6MP (Day)</b> i26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030816 85258091 420 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6D016</b> <b>i26B Complete Cam 6MP, B016, Day</b> Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030823 85258091 423 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6D036</b> <b>i26B Complete Cam 6MP, B036, Day</b> IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030830 85258091 440 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N</b> <b>i26B Body 6MP (Night)</b> i26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030847 85258091 420 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N016</b> <b>i26B Complete Cam 6MP, B016, Night</b> Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030854 85258091 423 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N036</b> <b>i26B Complete Cam 6MP, B036, Night</b> IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030861 85258091 440 g	19,6 cm 15,0 cm 9,0 cm 2,6 l

**Mx-i26B-AU-6D016****i26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030878 19,6 cm  
85258091 15,0 cm  
429 9 9,0 cm  
2,6 l

**Mx-i26B-AU-6D036****i26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030885 19,6 cm  
85258091 15,0 cm  
437 9 9,0 cm  
2,6 l

**Mx-i26B-AU-6N016****i26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030892 19,6 cm  
85258091 15,0 cm  
429 9 9,0 cm  
2,6 l







**Mx-i26B-AU-6N036****i26B Complete Cam 6MP, B036, Night, Audio Package**















IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030908 19,6 cm  
85258091 15,0 cm  
437 9 9,0 cm  
2,6 l

## p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-p26B-6D</b>	4047438031226	19,6 cm
	<b>p26B Body 6MP, Day</b>	85258091	18,0 cm
	<p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	582 g	14,8 cm 5,2 l
	<b>Mx-p26B-6D016</b>	4047438031233	19,6 cm
	<b>p26B Complete Cam 6MP, B016, Day</b>	85258091	18,0 cm
	<p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	574 g	14,8 cm 5,2 l
	<b>Mx-p26B-6D036</b>	4047438031240	19,6 cm
	<b>p26B Complete Cam 6MP, B036, Day</b>	85258091	18,0 cm
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	596 g	14,8 cm 5,2 l
	<b>Mx-p26B-6D061</b>	4047438031257	19,6 cm
	<b>p26B Complete Cam 6MP, B061, Day</b>	85258091	18,0 cm
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	480 g	14,8 cm 5,2 l
	<b>Mx-p26B-6D079</b>	4047438031264	19,6 cm
	<b>p26B Complete Cam 6MP, B079, Day</b>	85258091	18,0 cm
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	596 g	14,8 cm 5,2 l
	<b>Mx-p26B-6D119</b>	4047438031271	19,6 cm
	<b>p26B Complete Cam 6MP, B119, Day</b>	85258091	18,0 cm
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	480 g	14,8 cm 5,2 l

 	<p><b>Mx-p26B-6D237</b>  <b>p26B Complete Cam 6MP, B237, Day</b></p> <p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031288 19,6 cm  85258091 18,0 cm  480 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-6N</b>  <b>p26B Body 6MP, Night</b></p> <p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031295 19,6 cm  85258091 18,0 cm  582 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-6N016</b>  <b>p26B Complete Cam 6MP, B016, Night</b></p> <p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031301 19,6 cm  85258091 18,0 cm  574 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-6N036</b>  <b>p26B Complete Cam 6MP, B036, Night</b></p> <p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031318 19,6 cm  85258091 18,0 cm  480 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-AU-6D</b>  <b>p26B Body 6MP, Day, Audio Package</b></p> <p>p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031325 19,6 cm  85258091 18,0 cm  591 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-AU-6D016</b>  <b>p26B Complete Cam 6MP, B016, Day, Audio Package</b></p> <p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031332 19,6 cm  85258091 18,0 cm  480 <b>G</b> 14,8 cm  5,2 l</p>
 	<p><b>Mx-p26B-AU-6D036</b>  <b>p26B Complete Cam 6MP, B036, Day, Audio Package</b></p> <p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031349 19,6 cm  85258091 18,0 cm  480 <b>G</b> 14,8 cm  5,2 l</p>

**Mx-p26B-AU-6N****p26B Body 6MP, Night, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031356	19,6 cm
85258091	18,0 cm
480 <b>g</b>	14,8 cm
	5,2 l

**Mx-p26B-AU-6N016****p26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031363	19,6 cm
85258091	18,0 cm
480 <b>g</b>	14,8 cm
	5,2 l






**Mx-p26B-AU-6N036****p26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031370	19,6 cm
85258091	18,0 cm
480 <b>g</b>	14,8 cm
	5,2 l

## v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-v26B-6D</b>	4047438031547	19,6 cm
	<b>v26B Body 6MP, Day, White</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
<p>v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white</p>			
	<b>Mx-v26B-6D-b</b>	4047438031554	19,6 cm
	<b>v26B Body 6MP, Day, Black</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
<p>v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: black</p>			
	<b>Mx-v26B-6D036</b>	4047438031561	19,6 cm
	<b>v26B Complete Cam 6MP, B036, Day, White</b>	85258091	18,0 cm
		737 g	14,8 cm
			5,2 l
<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white</p>			
	<b>Mx-v26B-6N</b>	4047438031578	19,6 cm
	<b>v26B Body 6MP, Night, White</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
<p>v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white</p>			
	<b>Mx-v26B-6N-b</b>	4047438031585	19,6 cm
	<b>v26B Body 6MP, Night, Black</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
<p>v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: black</p>			



# Professional Video Systems Thermal

BeyondHumanVision

MOBOTIX

## M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M16TB-EST079</b>	4047438037433	29,6 cm
	<b>M16B Thermographic Camera TR (EST), 50 mK, R079 (45°)</b> IP thermographic camera with EST079 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	85258091 2.480 g	19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16TB-EST119</b>	4047438037440	29,6 cm
	<b>M16B Thermographic Camera TR (EST), 50 mK, R119 (25°)</b> IP thermographic camera with EST119 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	85258091 2.480 g	19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16TB-EST237</b>	4047438037457	29,6 cm
	<b>M16B Thermographic Camera TR (EST), 50 mK, R237 (17°)</b> IP thermographic camera with EST237 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	85258091 2.480 g	19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16TB-R075</b>	4047438036788	29,6 cm
	<b>M16B Thermographic Camera TR, 50 mK, R075 (45°)</b> IP thermographic camera TR with Germanium Lens: B075 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251920 2.480 g	19,6 cm 18,0 cm 10,4 l

	<b>Mx-M16TB-R079</b>	4047438030984	29,6 cm
	<b>M16B Thermographic Camera TR, 50 mK, R079 (45°)</b>	90251920	19,6 cm
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm 10,4 l
	<b>Mx-M16TB-R090</b>	4047438036795	29,6 cm
	<b>M16B Thermographic Camera TR, 50 mK, R090 (35°)</b>	90251920	19,6 cm
	IP thermographic camera TR with Germanium Lens: B090 equivalent, horizontal/vertical image angle 35°/27° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm 10,4 l
	<b>Mx-M16TB-R119</b>	4047438030991	29,6 cm
	<b>M16B Thermographic Camera TR, 50 mK, R119 (25°)</b>	90251920	19,6 cm
	IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.936 g	18,0 cm 10,4 l
	<b>Mx-M16TB-R237</b>	4047438031004	29,6 cm
	<b>M16B Thermographic Camera TR, 50 mK, R237 (17°)</b>	90251920	19,6 cm
	IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.942 g	18,0 cm 10,4 l
	<b>Mx-M16TB-T079</b>	4047438031011	29,6 cm
	<b>M16B Thermographic Camera 50 mK, T079 (45°)</b>	90251920	19,6 cm
	IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.460 g	18,0 cm 10,4 l

**Mx-M16TB-T119****M16B Thermographic Camera 50 mK, T119 (25°)**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)








4047438031028	29,6 cm
90251920	19,6 cm
2.460 g	18,0 cm
	10,4 l




**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031035	29,6 cm
90251920	19,6 cm
1.946 g	18,0 cm
	10,4 l

## Sensor Module Thermal for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-M73TA-336R100</b> <b>Thermal module 336-R100 with front plate for M73</b> CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438035644 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-336R150</b> <b>Thermal module 336-R150 with front plate for M73</b> CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate	4047438035651 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-336R280</b> <b>Thermal module 336-R280 with front plate for M73</b> CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate	4047438035668 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-336T100</b> <b>Thermal module 336-T100 with front plate for M73</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438035613 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-336T150</b> <b>Thermal module 336-T150 with front plate for M73</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate	4047438035620 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-336T280</b> <b>Thermal module 336-T280 with front plate for M73</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate	4047438035637 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M73TA-640R050</b> <b>Thermal module 640-R050 with front plate for M73</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate	4047438035705 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

	<p><b>Mx-O-M73TA-640R080</b></p> <p><b>Thermal module 640-R080 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate</p>	<p>4047438035712</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640R100</b></p> <p><b>Thermal module 640-R100 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate</p>	<p>4047438035729</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640R150</b></p> <p><b>Thermal module 640-R150 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • incl. M73 replacement front plate</p>	<p>4047438035866</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640T050</b></p> <p><b>Thermal module 640-T050 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate</p>	<p>4047438035675</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640T080</b></p> <p><b>Thermal module 640-T080 with front plate für M73</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate</p>	<p>4047438035682</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640T100</b></p> <p><b>Thermal module 640-T100 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate</p>	<p>4047438035699</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TA-640T150</b></p> <p><b>Thermal module 640-T150 with front plate for M73</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • incl. M73 replacement front plate</p>	<p>4047438035859</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-336R100</b></p> <p><b>Thermal module 336-R100 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate</p>	<p>4047438040198</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>



	<p><b>Mx-O-M73TB-336R150</b></p> <p><b>Thermal module 336-R150 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate</p>	<p>4047438040204</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-336R280</b></p> <p><b>Thermal module 336-R280 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate</p>	<p>4047438040211</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-336T100</b></p> <p><b>Thermal module 336-T100 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate</p>	<p>4047438040129</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-336T150</b></p> <p><b>Thermal module 336-T150 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate</p>	<p>4047438040136</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-336T280</b></p> <p><b>Thermal module 336-T280 with front plate for M73 (B)</b></p> <p>CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate</p>	<p>4047438040143</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640R050</b></p> <p><b>Thermal module 640-R050 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate</p>	<p>4047438040228</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640R080</b></p> <p><b>Thermal module 640-R080 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate</p>	<p>4047438040235</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640R100</b></p> <p><b>Thermal module 640-R100 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate</p>	<p>4047438040242</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>

	<p><b>Mx-O-M73TB-640R150</b></p> <p><b>Thermal module 640-R150 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • incl. M73 replacement front plate</p>	<p>4047438040259</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640T050</b></p> <p><b>Thermal module 640-T050 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate</p>	<p>4047438040150</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640T080</b></p> <p><b>Thermal module 640-T080 with front plate für M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate</p>	<p>4047438040167</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640T100</b></p> <p><b>Thermal module 640-T100 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate</p>	<p>4047438040174</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M73TB-640T150</b></p> <p><b>Thermal module 640-T150 with front plate for M73 (B)</b></p> <p>VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • incl. M73 replacement front plate</p>	<p>4047438040181</p> <p>90275000</p> <p>450 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p><b>Mx-O-M7SA-320T040</b></p> <p><b>Thermal Module ECO 320 - T040</b></p> <p>MOBOTIX 7 Thermal Module 320-T040 for M73/S74, 320x240, 105° viewing angle • NETD: 65mK (typ); &lt;100mK (max)</p>	<p>4047438040648</p> <p>90275000</p> <p>106 g</p>	<p>9,8 cm</p> <p>7,5 cm</p> <p>9,0 cm</p> <p>0,7 l</p>
	<p><b>Mx-O-M7SA-320T080</b></p> <p><b>Thermal Module ECO 320 - T080</b></p> <p>MOBOTIX 7 Thermal Module 320-T080 for M73/S74, 320x240, 56° viewing angle • NETD: 65mK (typ); &lt;100mK (max)</p>	<p>4047438040655</p> <p>90275000</p> <p>106 g</p>	<p>9,8 cm</p> <p>7,5 cm</p> <p>9,0 cm</p> <p>0,7 l</p>
	<p><b>Mx-O-M7SA-336RP100</b></p> <p><b>S7x PTMount Thermal 336-R100</b></p> <p>CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable</p>	<p>4047438036948</p> <p>90021900</p> <p>890 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>

	<p><b>Mx-O-M7SA-336RP150</b>  <b>S7x PTMount Thermal 336-R150</b>            CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable</p>	<p>4047438036955            90021900            890 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>Mx-O-M7SA-336RP280</b>  <b>S7x PTMount Thermal 336-R280</b>            CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable</p>	<p>4047438036962            90021900            890 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>Mx-O-M7SA-336RS100</b>  <b>S7x Thermal Module 336-R100</b>            CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35°</p>	<p>4047438035767            90275000            380 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-O-M7SA-336RS150</b>  <b>S7x Thermal module 336-R150</b>            CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19°</p>	<p>4047438035774            90275000            380 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-O-M7SA-336RS280</b>  <b>S7x Thermal Module 336-R280</b>            CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13°</p>	<p>4047438035781            90275000            380 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-O-M7SA-336TP100</b>  <b>S7x PTMount Thermal 336-T100</b>            CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable</p>	<p>4047438036917            90021900            890 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>Mx-O-M7SA-336TP150</b>  <b>S7x PTMount Thermal 336-T150</b>            CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable</p>	<p>4047438036924            90021900            890 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>Mx-O-M7SA-336TP280</b>  <b>S7x PTMount Thermal 336-T280</b>            CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable</p>	<p>4047438036931            90021900            890 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>

	<b>Mx-O-M7SA-336TS100</b> <b>S7x Thermal Module 336-T100</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35°	4047438035736 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SA-336TS150</b> <b>S7x Thermal module 336-T150</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19°	4047438035743 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SA-336TS280</b> <b>S7x Thermal Module 336-T280</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13°	4047438035750 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SA-640RP050</b> <b>S7x PTMount Thermal 640-R050</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable	4047438037013 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SA-640RP080</b> <b>S7x PTMount Thermal 640-R080</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable	4047438037020 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SA-640RP100</b> <b>S7x PTMount Thermal 640-R100</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable	4047438037037 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SA-640RP150</b> <b>S7x PTMount Thermal 640-R150</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable	4047438037044 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SA-640RS050</b> <b>S7x Thermal Module 640-R050</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69°	4047438035828 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l

	<p><b>Mx-O-M7SA-640RS080</b>  <b>S7x Thermal Module 640-R080</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56°</p>	<p>4047438035835  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SA-640RS100</b>  <b>S7x Thermal Module 640-R100</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37°</p>	<p>4047438035842  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SA-640RS150</b>  <b>S7x Thermal module 640-R150</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26°</p>	<p>4047438035880  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SA-640TP050</b>  <b>S7x PTMount Thermal 640-T050</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° Equipped with a 2 meter connection cable</p>	<p>4047438036979  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SA-640TP080</b>  <b>S7x PTMount Thermal 640-T080</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° Equipped with a 2 meter connection cable</p>	<p>4047438036986  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SA-640TP100</b>  <b>S7x PTMount Thermal 640-T100</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° Equipped with a 2 meter connection cable</p>	<p>4047438036993  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SA-640TP150</b>  <b>S7x PTMount Thermal 640-T150</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° Equipped with a 2 meter connection cable</p>	<p>4047438037006  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SA-640TS050</b>  <b>S7x Thermal Module 640-T050</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69°</p>	<p>4047438035798  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>

	<p><b>Mx-O-M7SA-640TS080</b>  <b>S7x Thermal Module 640-T080</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°</p>	<p>4047438035804  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SA-640TS100</b>  <b>S7x Thermal module 640-T100</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°</p>	<p>4047438035811  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SA-640TS150</b>  <b>S7x Thermal module 640-T150</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26°</p>	<p>4047438035873  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-336RP100</b>  <b>S7x PTMount Thermal 336-R100 (B model)</b>  CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° Equipped with a 2 meter connection cable</p>	<p>4047438040051  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-336RP150</b>  <b>S7x PTMount Thermal 336-R150 (B model)</b>  CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° Equipped with a 2 meter connection cable</p>	<p>4047438040068  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-336RP280</b>  <b>S7x PTMount Thermal 336-R280 (B model)</b>  CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° Equipped with a 2 meter connection cable</p>	<p>4047438040075  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-336RS100</b>  <b>S7x Thermal Module 336-R100 (B model)</b>  CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35°</p>	<p>4047438039918  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-336RS150</b>  <b>S7x Thermal module 336-R150 (B model)</b>  CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19°</p>	<p>4047438039925  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>

	<b>Mx-O-M7SB-336RS280</b> <b>S7x Thermal Module 336-R280 (B model)</b> CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13°	4047438039932 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SB-336TP100</b> <b>S7x PTMount Thermal 336-T100 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable	4047438039987 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SB-336TP150</b> <b>S7x PTMount Thermal 336-T150 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable	4047438039994 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SB-336TP280</b> <b>S7x PTMount Thermal 336-T280 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable	4047438040006 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-M7SB-336TS100</b> <b>S7x Thermal Module 336-T100 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35°	4047438039840 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SB-336TS150</b> <b>S7x Thermal module 336-T150 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19°	4047438039857 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SB-336TS280</b> <b>S7x Thermal Module 336-T280 (B model)</b> CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13°	4047438039864 90275000 380 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-O-M7SB-640RP050</b> <b>S7x PTMount Thermal 640-R050 (B model)</b> VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable	4047438040082 90021900 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l






	<p><b>Mx-O-M7SB-640RP080</b>  <b>S7x PTMount Thermal 640-R080 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable</p>	<p>4047438040099  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640RP100</b>  <b>S7x PTMount Thermal 640-R100 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable</p>	<p>4047438040105  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640RP150</b>  <b>S7x PTMount Thermal 640-R150 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable</p>	<p>4047438040112  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640RS050</b>  <b>S7x Thermal Module 640-R050 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69°</p>	<p>4047438039949  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640RS080</b>  <b>S7x Thermal Module 640-R080 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56°</p>	<p>4047438039956  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640RS100</b>  <b>S7x Thermal Module 640-R100 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37°</p>	<p>4047438039963  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640RS150</b>  <b>S7x Thermal module 640-R150 (B model)</b>  VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26°</p>	<p>4047438039970  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640TP050</b>  <b>S7x PTMount Thermal 640-T050 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable</p>	<p>4047438040013  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>

	<p><b>Mx-O-M7SB-640TP080</b>  <b>S7x PTMount Thermal 640-T080 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable</p>	<p>4047438040020  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640TP100</b>  <b>S7x PTMount Thermal 640-T100 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable</p>	<p>4047438040037  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640TP150</b>  <b>S7x PTMount Thermal 640-T150 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable</p>	<p>4047438040044  90021900  890 g</p>	<p>19,6 cm  18,0 cm  14,8 cm  5,2 l</p>
	<p><b>Mx-O-M7SB-640TS050</b>  <b>S7x Thermal Module 640-T050 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69°</p>	<p>4047438039871  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640TS080</b>  <b>S7x Thermal Module 640-T080 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°</p>	<p>4047438039888  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640TS100</b>  <b>S7x Thermal module 640-T100 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37°</p>	<p>4047438039895  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>
	<p><b>Mx-O-M7SB-640TS150</b>  <b>S7x Thermal module 640-T150 (B model)</b>  VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26°</p>	<p>4047438039901  90275000  380 g</p>	<p>14,8 cm  9,8 cm  9,0 cm  1,3 l</p>

## Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-TS-R079</b>	4047438030090	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TS-R119</b>	4047438030106	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TS-R237</b>	4047438030113	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TP-R079</b>	4047438030120	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R119</b>	4047438030137	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R237</b>	4047438030144	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R079-b</b>	4047438030151	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l

	<p><b>Mx-O-SMA-TP-R119-b</b>  <b>PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black</b>            PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030168 19,6 cm            90275000 18,0 cm            890 g 14,8 cm            5,2 l</p>
	<p><b>Mx-O-SMA-TP-R237-b</b>  <b>PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black</b>            PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030175 19,6 cm            90275000 18,0 cm            890 g 14,8 cm            5,2 l</p>
	<p><b>Mx-O-SMA-TS-T079</b>  <b>Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)</b>            Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029049 17,5 cm            90275000 14,0 cm            650 g 13,5 cm            3,3 l</p>
	<p><b>Mx-O-SMA-TS-T119</b>  <b>Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)</b>            Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029056 17,5 cm            90275000 14,0 cm            650 g 13,5 cm            3,3 l</p>
	<p><b>Mx-O-SMA-TS-T237</b>  <b>Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)</b>            Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029063 17,5 cm            90275000 14,0 cm            650 g 13,5 cm            3,3 l</p>
	<p><b>Mx-O-SMA-TP-T079</b>  <b>PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White</b>            PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029070 19,6 cm            90275000 18,0 cm            890 g 14,8 cm            5,2 l</p>
	<p><b>Mx-O-SMA-TP-T119</b>  <b>PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White</b>            PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029087 19,6 cm            90275000 18,0 cm            890 g 14,8 cm            5,2 l</p>
	<p><b>Mx-O-SMA-TP-T237</b>  <b>PTMount Thermal For S16/S15, 50 mK, B237 (17°), White</b>            PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029094 19,6 cm            90275000 18,0 cm            890 g 14,8 cm            5,2 l</p>

	<p><b>Mx-O-SMA-TP-T079-b</b>  <b>PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black</b></p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030021 19,6 cm  90275000 18,0 cm  890 g 14,8 cm  5,2 l</p>
	<p><b>Mx-O-SMA-TP-T119-b</b>  <b>PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black</b></p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030038 19,6 cm  90275000 18,0 cm  890 g 14,8 cm  5,2 l</p>
	<p><b>Mx-O-SMA-TP-T237-b</b>  <b>PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black</b></p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, &lt;79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black</p>	<p>4047438030045 19,6 cm  90275000 18,0 cm  890 g 14,8 cm  5,2 l</p>

# MOBOTIX MOVE Cameras

BeyondHumanVision

MOBOTIX

## MOBOTIX MOVE Speed Dome Cameras



### MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-SD1A-230-LL</b>	4047438040495	42,5 cm
	<b>MOBOTIX MOVE SpeedDome SD-230-LL Low Light</b> MOBOTIX MOVE SpeedDome Network Camera SD-230-LL • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 2MP SONY Low-Light Sensor (1945 x 1097), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° - 2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • Anti-Vibration function • autom. Object Tracking • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE802.3at, max. 23.11 W, AC24V max. 24.20 W / 39.60 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • Warranty: 2 years	85258091 5.700 g	26,2 cm 35,0 cm 39,0 l
	<b>Mx-SD1A-330</b>	4047438031646	42,5 cm
	<b>MOBOTIX MOVE SpeedDome SD-330</b> MOBOTIX MOVE SpeedDome Network Camera SD-330 • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° - 2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3at or DC 12V (2.12 A) or AC 24V; max 25.4 W • Warranty: 2 years	85258091 5.700 g	26,2 cm 35,0 cm 39,0 l
	<b>Mx-SD1A-340-IR</b>	4047438031653	40,2 cm
	<b>MOBOTIX MOVE SpeedDome SD-340-IR</b> MOBOTIX MOVE SpeedDome Network Camera SD-340-IR • Weatherproof, motorized ONVIF S / G dome PTZ camera with built-in IR LEDs (up to 200m) for day and night use • Up to 40x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 170 mm, viewing angle HxV: 62 ° - 2 ° x 49 ° - 1 °) with "One Push" autofocus and P-iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -40 to 55°C, Humidity 10 to 90% • Video codecs: H.265, H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30B / s (H.265, H.264 , with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: UPoE (Universal PoE) or DC 12V (3.25 A) or AC 24V; max 39 W • Warranty: 2 years	85258091 5.600 g	25,0 cm 37,0 cm 37,2 l



## MOBOTIX MOVE Vandal Dome Cameras

### MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-VD1A-8-IR-VA</b> <b>MOBOTIX MOVE VandalDome VD-8-IR-VA (DNN Analytics)</b> MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040341 85258091 1.081 g	17,3 cm 17,3 cm 16,6 cm 5,0 l
	<b>Mx-VD2A-5-IR-VA</b> <b>MOBOTIX MOVE VandalDome VD2-5-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Dome Network Camera VD2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040457 85258091 1.210 g	17,5 cm 17,5 cm 17,0 cm 5,2 l
	<b>Mx-VD1A-5-IR-VA</b> <b>MOBOTIX MOVE VandalDome VD-5-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Dome Network Camera VD-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Warranty: 2 years	4047438037792 85258091 1.210 g	17,5 cm 17,5 cm 17,0 cm 5,2 l
	<b>Mx-VD3A-2-IR-VA</b> <b>MOBOTIX MOVE VandalDome VD3-2-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Dome Network Camera VD3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040433 85258091 1.210 g	17,5 cm 17,5 cm 17,0 cm 5,2 l

**Mx-VD2A-2-IR-VA****MOBOTIX MOVE VandalDome VD-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD-2-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99 °-31 °, V: 53 °-18 °) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Warranty: 2 years

4047438037778 17,5 cm  
85258091 17,5 cm  
1.210 9 17,0 cm  
5,2 l

**Mx-VD1A-4-IR****MOBOTIX MOVE VandalDome VD-4-IR**

MOBOTIX MOVE VandalDome Network Camera VD-4-IR • Weatherproof ONVIF S/G dome camera with integrated IR LEDs (up to 30 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103 °-35 ° x 53 °-23 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years

4047438031639 17,5 cm  
85258091 17,5 cm  
1.050 9 17,0 cm  
5,2 l

**Mx-VD1A-4-IR-D****MOBOTIX MOVE VandalDome VD-4-IR-D**

MOBOTIX MOVE VandalDome Network Camera VD-4-IR-D • Weatherproof ONVIF S/G dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 °-15 °, V: 20 °-9 °) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, H.265); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years

4047438034371 17,5 cm  
85258091 17,5 cm  
1.010 9 17,0 cm  
5,2 l

**Mx-VD2A-2-IR****MOBOTIX MOVE VandalDome VD2-2-IR**


MOBOTIX MOVE VandalDome Network Camera VD2-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S/G/T vandal dome camera with built-in IR LEDs (up to 40 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91 °-34 °) • IP66 • IK10 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 320 dB) • Max. Frame rate: 2MP @ 60B / s (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 2 years

4047438038959 17,5 cm  
85258091 17,5 cm  
1.010 9 17,0 cm  
5,2 l

## MOBOTIX MOVE Bullet Cameras


### MOBOTIX MOVE Bullet Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-VB1A-8-IR-VA</b> <b>MOBOTIX MOVE VandalBullet VB-8-IR-VA (DNN Analytics)</b> MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040358 85258091 1.793 g	28,5 cm 19,6 cm 17,4 cm 9,7 l
	<b>Mx-VB2A-5-IR-VA</b> <b>MOBOTIX MOVE VandalBullet VB2-5-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Bullet Network Camera VB2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040464 85258091 1.710 g	29,6 cm 20,0 cm 17,5 cm 10,4 l
	<b>Mx-VB1A-5-IR-VA</b> <b>MOBOTIX MOVE VandalBullet VB-5-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Bullet Network Camera VB-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Warranty: 2 years	4047438037808 85258091 1.460 g	29,6 cm 20,0 cm 17,5 cm 10,4 l
	<b>Mx-VB3A-2-IR-VA</b> <b>MOBOTIX MOVE VandalBullet VB3-2-IR-VA (Video Analytics)</b> MOBOTIX MOVE Vandal Bullet Network Camera VB3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 2 years	4047438040440 85258091 1.460 g	29,6 cm 20,0 cm 17,5 cm 10,4 l

	<b>Mx-VB2A-2-IR-VA</b>	4047438037785	29,6 cm
	<b>MOBOTIX MOVE VandalBullet VB-2-IR-VA (Video Analytics)</b>	85258091	20,0 cm
	MOBOTIX MOVE Vandal Bullet Network Camera VB-2-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Warranty: 2 years	1.460 G	17,5 cm 10,4 l
	<b>Mx-VB1A-4-IR</b>	4047438034395	29,6 cm
	<b>MOBOTIX MOVE VandalBullet VB1A-4-IR</b>	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera VB1A-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 2.7 to 12 mm, viewing angle H: 99° - 31°, V: 53° - 18°) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.460 G	17,5 cm 10,4 l
	<b>Mx-VB1A-4-IR-D</b>	4047438034401	29,6 cm
	<b>MOBOTIX MOVE VandalBullet VB1A-4-IR-D</b>	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera VB1A-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35°-15°, V: 20°-9°) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.460 G	17,5 cm 10,4 l
	<b>Mx-BC1A-4-IR</b>	4047438031622	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-4-IR</b>	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103° -35° x 53° -23°) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.237 G	17,5 cm 10,4 l
	<b>Mx-BC1A-4-IR-D</b>	4047438034388	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-4-IR-D</b>	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35° - 15°, V: 20° - 9°) with Auto Iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.030 G	17,5 cm 10,4 l
	<b>Mx-BC1A-2-IR</b>	4047438034418	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-2-IR</b>	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S bullet camera with built-in IR LEDs (up to 15 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91° -34°) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 2MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 2 years	580 G	17,5 cm 10,4 l

## MOBOTIX MOVE Hemispheric Vandal Dome

### MOBOTIX MOVE Hemispheric Vandal Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-VH1A-12-IR-VA</b>	4047438038317	17,3 cm
	<b>MOBOTIX MOVE 12MP Vandal Hemispheric</b>	85258091	17,3 cm
	MOBOTIX MOVE Vandal Hemispheric Network Camera Mx-VH1A-12-IR-VA • Image sensor: 12MP (4000 x 3000), 1/1.7" Progressive CMOS • Indoor • ONVIF S/G/T/M • Hemispheric camera with built-in IR LED illumination (up to 10 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • focal length 1.65 mm • IK10 • Ambient temperature -10 to 55°C (14° to 131°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Max. Frame rate: 12MP@20 fps (Backend dewarping) 4MP@30 fps (Edge dewarping) • Power supply: PoE IEEE 802.3af • Warranty: 3 years • MTBF: 95,000h	640 g	10,7 cm
			3,2 l

# Optics

## Sensor Modules 4K for MOBOTIX 7







	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-M7SA-12DN016</b> <b>12MP Hemispheric Day &amp; Night Sensor Module</b> 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, white	4047438040631 90021900 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8L040</b> <b>120° 4K LPF Sensor Module WIDE</b> M73/S74 sensor module with premium wide-angle lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438040310 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8DN040</b> <b>120° 4K IR Cut Day &amp; Night Sensor Module WIDE</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438034968 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8DN050</b> <b>95° 4K IR Cut Day &amp; Night Sensor Module WIDE</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438034814 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8DN080</b> <b>60° 4K IR Cut Day &amp; Night Sensor Module WIDE</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438035941 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8DN100</b> <b>45° 4K IR Cut Day &amp; Night Sensor Module STANDARD</b> M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438034821 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-8DN150</b> <b>30° 4K IR Cut Day &amp; Night Sensor Module TELE</b> M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438035958 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l










	<p><b>Mx-O-M7SA-8DN280</b>  <b>15° 4K IR Cut Day &amp; Night Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034838  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D040</b>  <b>120° 4K Day Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034944  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D050</b>  <b>95° 4K Day Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034845  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D080</b>  <b>60° 4K Day Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438035989  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D100</b>  <b>45° 4K Day Sensor Module STANDARD</b>  M73/S74 sensor module with premium standard-angle lens for day, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034852  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D150</b>  <b>30° 4K Day Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438035996  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8D280</b>  <b>15° 4K Day Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens for day, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034869  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8N040</b>  <b>120° 4K Night Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034951  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

	<p><b>Mx-O-M7SA-8N050</b>  <b>95° 4K Night Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034876  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8N080</b>  <b>60° 4K Night Sensor Module WIDE</b>  M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438035965  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8N100</b>  <b>45° 4K Night Sensor Module STANDARD</b>  M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034883  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8N150</b>  <b>30° 4K Night Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438035972  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8N280</b>  <b>15° 4K Night Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438034890  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8L150</b>  <b>30° 4K LPF Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438037730  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-M7SA-8L280</b>  <b>15° 4K LPF Sensor Module TELE</b>  M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white</p>	<p>4047438037723  90021900  140 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

## Sensor Modules 4MP Low Light for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-M7SA-4DN040</b> <b>120° 4MP IR Cut Day &amp; Night Ultra LowLight Sensor Module</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4MP (2688x1512), IP66, white	4047438037167 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-4DN050</b> <b>95° 4MP IR Cut Day &amp; Night Ultra LowLight Sensor Module</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP (2688x1512), IP66, white	4047438037174 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-4DN080</b> <b>60° 4MP IR Cut Day &amp; Night Ultra LowLight Sensor Module</b> M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP (2688x1512), IP66, white	4047438037181 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-4DN100</b> <b>45° 4MP IR Cut Day &amp; Night Ultra LowLight Sensor Module</b> M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP (2688x1512), IP66, white	4047438037198 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-4DN150</b> <b>30° 4MP IR Cut Day &amp; Night Ultra LowLight Sensor Module</b> M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP (2688x1512), IP66, white	4047438037204 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-M7SA-4DN280</b> <b>15° 4MP IR Cut Day &amp; Night Low Light Sensor Module WIDE</b> M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP (2688x1512), IP66, white	4047438037211 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

## Sensor Modules 6MP For S16A/S16B And

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-S-6D016</b>	4047438029100	9,8 cm
	<b>Sensor Module 6MP, B016 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D036</b>	4047438029117	9,8 cm
	<b>Sensor Module 6MP, B036 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D041</b>	4047438029124	9,8 cm
	<b>Sensor Module 6MP, B041 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D061</b>	4047438029131	9,8 cm
	<b>Sensor Module 6MP, B061 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D079</b>	4047438029148	9,8 cm
	<b>Sensor Module 6MP, B079 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D119</b>	4047438029155	9,8 cm
	<b>Sensor Module 6MP, B119 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D237</b>	4047438029162	9,8 cm
	<b>Sensor Module 6MP, B237 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l

	<p><b>Mx-O-SMA-S-6D500</b>  <b>Sensor Module 6MP, B500 (Day), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029179            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6DCSV</b>  <b>Sensor Module 6MP, CSVario 4,5-10 mm (Day), White</b>            Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030052            90021900            190 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6DCS</b>  <b>Sensor Module 6MP, CS-Mount (Day), White</b>            Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030076            90021900            146 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N016</b>  <b>Sensor Module 6MP, B016 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029186            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N036</b>  <b>Sensor Module 6MP, B036 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029193            90021900            170 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N041</b>  <b>Sensor Module 6MP, B041 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029209            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N061</b>  <b>Sensor Module 6MP, B061 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029216            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N079</b>  <b>Sensor Module 6MP, B079 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029223            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

	<p><b>Mx-O-SMA-S-6N119</b>  <b>Sensor Module 6MP, B119 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029230            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N237</b>  <b>Sensor Module 6MP, B237 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029247            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N500</b>  <b>Sensor Module 6MP, B500 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029254            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6NCSV</b>  <b>Sensor Module 6MP, CSVario 4,5-10 mm (Night), White</b>            Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS (focal length 4.5 -10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030069            90021900            190 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6NCS</b>  <b>Sensor Module 6MP, CS-Mount (Night), White</b>            Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030083            90021900            146 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L016</b>  <b>Sensor Module 6MP, B016 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029261            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L036</b>  <b>Sensor Module 6MP, B036 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029278            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L041</b>  <b>Sensor Module 6MP, B041 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029285            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>



	<p><b>Mx-O-SMA-S-6L061</b>  <b>Sensor Module 6MP, B061 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029292  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L079</b>  <b>Sensor Module 6MP, B079 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029308  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L119</b>  <b>Sensor Module 6MP, B119 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029315  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L237</b>  <b>Sensor Module 6MP, B237 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029322  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L500</b>  <b>Sensor Module 6MP, B500 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029339  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D016-b</b>  <b>Sensor Module 6MP, B016 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029346  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D036-b</b>  <b>Sensor Module 6MP, B036 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029353  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D041-b</b>  <b>Sensor Module 6MP, B041 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029360  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>



 	<p><b>Mx-O-SMA-S-6D061-b</b>  <b>Sensor Module 6MP, B061 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029377            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6D079-b</b>  <b>Sensor Module 6MP, B079 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029384            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6D119-b</b>  <b>Sensor Module 6MP, B119 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029391            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6D237-b</b>  <b>Sensor Module 6MP, B237 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029407            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6D500-b</b>  <b>Sensor Module 6MP, B500 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029414            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N016-b</b>  <b>Sensor Module 6MP, B016 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029421            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N036-b</b>  <b>Sensor Module 6MP, B036 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029438            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N041-b</b>  <b>Sensor Module 6MP, B041 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029445            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

 	<p><b>Mx-O-SMA-S-6N061-b</b>  <b>Sensor Module 6MP, B061 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029452            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N079-b</b>  <b>Sensor Module 6MP, B079 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029469            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N119-b</b>  <b>Sensor Module 6MP, B119 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029476            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N237-b</b>  <b>Sensor Module 6MP, B237 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029483            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N500-b</b>  <b>Sensor Module 6MP, B500 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029490            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L016-b</b>  <b>Sensor Module 6MP, B016 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029506            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L036-b</b>  <b>Sensor Module 6MP, B036 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029513            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L041-b</b>  <b>Sensor Module 6MP, B041 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029520            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

 	<p><b>Mx-O-SMA-S-6L061-b</b>  <b>Sensor Module 6MP, B061 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029537  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L079-b</b>  <b>Sensor Module 6MP, B079 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029544  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L119-b</b>  <b>Sensor Module 6MP, B119 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029551  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L237-b</b>  <b>Sensor Module 6MP, B237 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029568  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L500-b</b>  <b>Sensor Module 6MP, B500 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029575  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

## BlockFlexMounts 6MP For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-B-6D016</b>	4047438029797	9,8 cm
	<b>BlockFlexMount 6MP, Incl. Hemispheric B016 (Day)</b> Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D036</b>	4047438029803	9,8 cm
	<b>BlockFlexMount 6MP, Incl. B036 (Day)</b> Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D041</b>	4047438029810	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B041 (Day)</b> Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D061</b>	4047438029827	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B061 (Day)</b> Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 136 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D079</b>	4047438029834	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B079 (Day)</b> Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D119</b>	4047438029841	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B119 (Day)</b> Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 130 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D237</b>	4047438029858	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B237 (Day)</b> Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l

	<p><b>Mx-O-SMA-B-6D500</b>  <b>BlockFlexMount 6MP, incl. B500 (Day)</b>            Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029865            90021900            150 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6DCS</b>  <b>BlockFlexMount 6MP, For CS Mount Lens (Day)</b>            Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029766            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N016</b>  <b>BlockFlexMount 6MP, Incl. Hemispheric B016 (Night)</b>            Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029872            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N036</b>  <b>BlockFlexMount 6MP, Incl. B036 (Night)</b>            Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029889            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N041</b>  <b>BlockFlexMount 6MP, Incl. B041 (Night)</b>            Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029896            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N061</b>  <b>BlockFlexMount 6MP, Incl. B061 (Night)</b>            Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029902            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N079</b>  <b>BlockFlexMount 6MP, Incl. B079 (Night)</b>            Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029919            90021900            134 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N119</b>  <b>BlockFlexMount 6MP, Incl. B119 (Night)</b>            Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029926            90021900            130 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>



	<p><b>Mx-O-SMA-B-6N237</b>  <b>BlockFlexMount 6MP, Incl. B237 (Night)</b></p> <p>Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029933  90021900  134 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6N500</b>  <b>BlockFlexMount 6MP, Incl. B500 (Night)</b></p> <p>Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029940  90021900  155 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6NCS</b>  <b>BlockFlexMount 6MP, For CS Mount Lens (Night)</b></p> <p>Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029773  90021900  102 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6L036</b>  <b>BlockFlexMount 6MP, Incl. B036 (Night LPF)</b></p> <p>Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029957  90021900  136 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6L041</b>  <b>BlockFlexMount 6MP, Incl. B041 (Night LPF)</b></p> <p>Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029964  90021900  132 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6L061</b>  <b>BlockFlexMount 6MP, Incl. B061 (Night LPF)</b></p> <p>Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029971  90021900  134 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6L079</b>  <b>BlockFlexMount 6MP, Incl. B079 (Night LPF)</b></p> <p>Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029988  90021900  134 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-B-6L119</b>  <b>BlockFlexMount 6MP, Incl. B119 (Night LPF)</b></p> <p>Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029995  90021900  130 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>

**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,0 cm
90021900	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030014	10,0 cm
90021900	7,5 cm
150 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**

















Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)







4047438029780	10,0 cm
90021900	7,5 cm
104 9	9,0 cm
	0,7 l



## Sensor Modules 6MP For D16A/D16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
 	<b>Mx-O-SDA-F-6D6N</b> <b>Sensor Bridge FIX For D16/D15, 2x 6MP (Day &amp; Night)</b> Day & Night sensor bridge for D16/D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	4047438030182 90021900 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-SDA-P-6D6D</b> <b>Sensor Bridge PAN/180° For D16/D15, 2x 6MP (Day)</b> Panorama/180° sensor bridge for D16/D15 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030199 90021900 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 	<b>Mx-O-SDA-P-6N6N</b> <b>Sensor Bridge PAN-N/180° for D16/D15, 2x 6MP (Night)</b> Panorama/180° sensor bridge for D16/D15 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030205 90021900 344 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-SDA-S-6D036</b> <b>Sensor Module D16/D15 6MP, Incl. B036 (Day)</b> Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029582 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	<b>Mx-O-SDA-S-6D041</b> <b>Sensor Module D16/D15 6MP, Incl. B041 (Day)</b> Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029599 90021900 66 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>Mx-O-SDA-S-6D061</b> <b>Sensor Module D16/D15 6MP, Incl. B061 (Day)</b> Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029605 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	<b>Mx-O-SDA-S-6D079</b> <b>Sensor Module D16/D15 6MP, Incl. B079 (Day)</b> Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029612 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

 	<p><b>Mx-O-SDA-S-6D119</b>  <b>Sensor Module D16/D15 6MP, Incl. B119 (Day)</b>            Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029629            90021900            64 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N036</b>  <b>Sensor Module D16/D15 6MP, Incl. B036 (Night)</b>            Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029643            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N041</b>  <b>Sensor Module D16/D15 6MP, Incl. B041 (Night)</b>            Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029650            90021900            66 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N061</b>  <b>Sensor Module D16/D15 6MP, Incl. B061 (Night)</b>            Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029667            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N079</b>  <b>Sensor Module D16/D15 6MP, Incl. B079 (Night)</b>            Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029674            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N119</b>  <b>Sensor Module D16/D15 6MP, Incl. B119 (Night)</b>            Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029681            90021900            64 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L036</b>  <b>Sensor Module D16/D15 6MP, Incl. B036 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029704            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L041</b>  <b>Sensor Module D16/D15 6MP, Incl. B041 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029711            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>



 	<p><b>Mx-O-SDA-S-6L061</b></p> <p><b>Sensor Module D16/D15 6MP, Incl. B061 (Night LPF)</b></p> <p>Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029728</p> <p>90021900</p> <p>64 g</p>	<p>7,5 cm</p> <p>4,9 cm</p> <p>9,0 cm</p> <p>0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L079</b></p> <p><b>Sensor Module D16/D15 6MP, Incl. B079 (Night LPF)</b></p> <p>Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029735</p> <p>90021900</p> <p>64 g</p>	<p>7,5 cm</p> <p>4,9 cm</p> <p>9,0 cm</p> <p>0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L119</b></p> <p><b>Sensor Module D16/D15 6MP, Incl. B119 (Night LPF)</b></p> <p>Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029742</p> <p>90021900</p> <p>64 g</p>	<p>7,5 cm</p> <p>4,9 cm</p> <p>9,0 cm</p> <p>0,3 l</p>

# Camera Accessories

## Camera Mounts (M7)

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M-CM-M73</b> <b>Ceiling Mount for M73 models</b> Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039819 90079100 631 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-M-IC-DQ</b> <b>In-Ceiling Set for MOBOTIX 7 Single Lens Models</b> In-Ceiling Set for MOBOTIX 7 Single Lens Models	4047438040761 90079100 g	cm cm cm l
	<b>Mx-M-OW-DQ</b> <b>On-Wall Set for MOBOTIX 7 Single Lens Models</b> On-Wall Set for MOBOTIX 7 Single Lens Models	4047438040662 90079100 g	cm cm cm l
	<b>Mx-M-OW-M73</b> <b>On-Wall Mount for M73 models</b> Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039802 90079100 502 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-M-PM-M73</b> <b>Pole mount for M73 models</b> Suitable for: M73 Cameras • 2 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	4047438035064 90079100 1.247 g	20,0 cm 18,2 cm 9,0 cm 3,3 l
	<b>Mx-M-WM-DQ</b> <b>Wall Mount for MOBOTIX 7 Single Lens Models</b> Wall Mount for MOBOTIX 7 Single Lens Models	4047438040778 90079100 835 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

## Mounts For S74

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M-DLMA</b> <b>DualMount S7x, white</b> For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white	4047438036887 90079100 450 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-M-PTMA</b> <b>PTMount S7x, white</b> Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideway tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x and S16B • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white • Angled sensor cables are recommended (e.g. Mx-A-S7A-CBL01-AN)	4047438036894 90079100 620 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-M-PTMA-b</b> <b>PTMount S7x, black</b> Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideway tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	4047438036900 90079100 620 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-M-SLMA</b> <b>SingleMount S7x, white</b> For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x and S16B (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white	4047438036870 90079100 240 g	14,8 cm 9,8 cm 9,0 cm 1,3 l

## S7x Sensor Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>Mx-A-S7A-AUCBL05-AN</b>  <b>S74 audio cable 5m</b>            Audio cable to connect a MOBOTIX 7 audio module Mx-F-AUDA to the IO board Mx-F-S7A-INT01 the S74, length 5m</p>	<p>4047438040501            85444210            155 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL01</b>  <b>Sensor Cable 1m for S7x straight-straight</b>            Sensor cable straight-straight, length 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body</p>	<p>4047438035583            85444210            70 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL01-AN</b>  <b>Sensor cable 1m for S7x straight-angled</b>            Sensor cable straight-angled, length 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts</p>	<p>4047438035897            85444210            70 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL02</b>  <b>Sensor Cable 2m for S7x straight-straight</b>            Sensor cable straight-straight, length 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body</p>	<p>4047438035590            85444210            90 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL02-AN</b>  <b>Sensor cable 2m for S7x straight-angled</b>            Sensor cable straight-angled, length 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts</p>	<p>4047438035903            85444210            90 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL03</b>  <b>Sensor Cable 3m for S7x straight-straight</b>            Sensor cable straight-straight, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body</p>	<p>4047438035606            85444210            110 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>
	<p><b>Mx-A-S7A-CBL03-AN</b>  <b>Sensor cable 3m for S7x straight-angled</b>            Sensor cable straight-angled, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts</p>	<p>4047438035910            85444210            110 g</p>	<p>14,0 cm            3,5 cm            15,0 cm            0,7 l</p>



	<p><b>Mx-A-S7A-LCE-OF30</b>  <b>30m optical fibre cable for Long Cable Extender (A)</b>            MOBOTIX 30m optical fibre cable for Long Cable Extender Variante A</p>	<p>4047438040334            85444210            1.228 9</p>	<p>31,5 cm            31,5 cm            13,5 cm            13,4 l</p>
	<p><b>Mx-CBL-MUC-AB-1</b>  <b>S74 Cable MiniUSB-C to USB-A 1m</b>            MiniUSB-C straight &gt; USB-A straight • Length 1 m /3,3 ft • For S74 • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438037129            85444210            102 9</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-CBL-MUC-AB-5</b>  <b>S74 Cable MiniUSB-C to USB-A 5m</b>            MiniUSB-C straight &gt; USB-A straight • Length 5 m /16,4 ft • For S74 • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438037136            85444210            220 9</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-CBL-MUC-AN-AB-1</b>  <b>S7x Cable MiniUSB-C to USB-A angled-straight 1m</b>            MiniUSB-C angled &gt; USB-A straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438040556            85444210            102 9</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-CBL-MUC-AN-AB-5</b>  <b>S7x Cable MiniUSB-C to USB-A angled-straight 5m</b>            MiniUSB-C angled &gt; USB-A straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438040563            85444210            220 9</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-CBL-MUC-AN-MU-1</b>  <b>S7x Cable MiniUSB-C to MiniUSB angled-straight 1m</b>            MiniUSB-C angled &gt; MiniUSB straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438040532            85444210            102 9</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-CBL-MUC-AN-MU-5</b>  <b>S7x Cable MiniUSB-C to MiniUSB angled-straight 5m</b>            MiniUSB-C angled &gt; MiniUSB straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)</p>	<p>4047438040549            85444210            220 9</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>Mx-CBL-MUC-MU-1</b>  <b>S74 Cable MiniUSB-C to MiniUSB 1m</b>            MiniUSB-C straight &gt; MiniUSB straight • Length 1 m /3,3 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438037143            85444210            102 9</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>

**Mx-CBL-MUC-MU-5****S74 Cable MiniUSB-C to MiniUSB 5m**

MiniUSB-C straight > MiniUSB straight • Length 5 m/16,4 ft • For S74 • To connect  
RS232-IO-Box (MX-OPT-RS1-EXT)

4047438037150 14,8 cm

85444210 9,8 cm

220 g 9,0 cm

1,3 l

## HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-B036</b> <b>Ultra Wide Lens B036, Focal Length: 3.6 mm</b> Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	4047438026536 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B041</b> <b>Super Wide Lens B041, Focal Length: 4.1 mm</b> Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	4047438026543 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B061</b> <b>Wide Lens B061, Focal Length: 6.1 mm</b> Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)	4047438026550 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B079</b> <b>Standard Lens B079, Focal Length: 7.9 mm</b> Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	4047438026567 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B119</b> <b>Tele Lens B119, Focal Length: 11.9 mm</b> Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)	4047438026574 90021900 30 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B237</b> <b>lens for D1x/M2x/D2x (HS code 90021900)</b> Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)	4047438026581 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B500</b> <b>Super Tele Lens B500, Focal Length: 50 mm</b> Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 • Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)	4047438026598 90021900 52 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29° -65°

4047438026604	9,0 cm
90021900	7,5 cm
66 g	5,0 cm
	0,3 l

**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 g	5,0 cm
	0,3 l

## Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-M24M-OPT-LCSK</b> <b>Replacement Lens Cover M2x, Standard</b> Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	4047438012980 90079100 32 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-M24M-OPT-LCSG</b> <b>Replacement Lens Cover M2x, With Glass Pane</b> Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438012997 90079100 38 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-M24M-OPT-LCGL</b> <b>Replacement Lens Cover M2x, Extended</b> Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438013000 90079100 44 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-OPT-DK-L11</b> <b>Replacement Cover Hemispheric</b> Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	4047438016469 90079100 24 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-D15-OPT-DCT</b> <b>Replacement Cover D1x/v2x, Standard</b> Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	4047438018227 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>MX-D15-OPT-DCS</b> <b>Replacement Cover D1x/v2x, Tinted</b> Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments	4047438018210 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>MX-D15-DCT-XL</b> <b>Replacement Cover D1x FIX/PAN, XL</b> Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)	4047438027519 90079100 281 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

	<p><b>MX-D15-DCS-XL</b>  <b>Replacement Cover D1x PAN/FIX, XL Tinted</b>            Suitable for: D1x PAN/180° and FIX/Day&amp;Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)</p>	<p>4047438027526            90079100            60 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-D24M-OPT-DCT</b>  <b>Replacement Cover D2x, Standard</b>            Suitable for: D2x • With sealing ring</p>	<p>4047438011419            90079100            150 g</p>	<p>19,6 cm            15,0 cm            9,0 cm            2,6 l</p>
	<p><b>MX-D24M-OPT-DCS</b>  <b>Replacement Cover D2x, Tinted</b>            Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments</p>	<p>4047438011402            90079100            150 g</p>	<p>19,6 cm            15,0 cm            9,0 cm            2,6 l</p>
	<p><b>MX-D15-Vandal-ESMA</b>  <b>Vandalism Set For D1x, Matt</b>            Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018173            90079100            1.012 g</p>	<p>39,5 cm            29,6 cm            9,0 cm            10,5 l</p>
	<p><b>MX-D15-DCT-V</b>  <b>Replacement Cover D1x/v2x, Vandalism</b>            Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&amp;Night models (XL cover needed)</p>	<p>4047438027533            90079100            278 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-D24M-Vandal-ESMA</b>  <b>Vandalism Set For D2x, Matt</b>            Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011143            90079100            672 g</p>	<p>30,5 cm            24,0 cm            12,0 cm            8,8 l</p>
	<p><b>MX-D25-DCT-V</b>  <b>Replacement D2x, Vandalism</b>            Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring</p>	<p>4047438027700            90079100            60 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-Q24M-Vandal-ESMA</b>  <b>Vandalism Set For Q2x, Matt</b>            Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. safety screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available</p>	<p>4047438011273            90079100            590 g</p>	<p>29,6 cm            19,6 cm            9,0 cm            5,2 l</p>

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027601	29,6 cm
90079100	19,6 cm
502 g	9,0 cm
	5,2 l

**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**


Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027625	29,6 cm
90079100	19,6 cm
680 g	9,0 cm
	5,2 l



## Mounts For S16A/S16B









	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-FLEX-OPT-DM-PW</b>	4047438017626	19,6 cm
	<b>DualMount S1x, White</b>	90079100	15,0 cm
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	414 g	9,0 cm
			2,6 l
	<b>MX-FLEX-OPT-SM-PW</b>	4047438016407	19,6 cm
	<b>SurroundMount S1x, White</b>	90079100	15,0 cm
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all 6MP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	392 g	9,0 cm
			2,6 l
	<b>MX-FLEX-OPT-DM-BL</b>	4047438021869	19,6 cm
	<b>DualMount S1x, Black</b>	90079100	15,0 cm
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	414 g	9,0 cm
			2,6 l
	<b>MX-FLEX-OPT-SM-BL</b>	4047438021845	19,6 cm
	<b>SurroundMount S1x, Black</b>	90079100	15,0 cm
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	392 g	9,0 cm
			2,6 l
	<b>MX-HALO-EXT-PW</b>	4047438017664	13,5 cm
	<b>HaloMount S1x, White</b>	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l
	<b>MX-HALO-EXT-BL</b>	4047438017671	13,5 cm
	<b>HaloMount S1x, Black</b>	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	175 g	4,5 cm
			0,7 l
	<b>MX-HALO-EXT-CM</b>	4047438017633	13,5 cm
	<b>HaloMount S1x, Matt Chrome</b>	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l

	<p><b>MX-HALO-EXT-CO</b>  <b>HaloMount S1x, Chrome</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)</p>	<p>4047438017640  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-EXT-NG</b>  <b>HaloMount S1x, Brushed Nickel</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)</p>	<p>4047438017657  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-SP-EXT-PW</b>  <b>SpeakerMount S1x, White</b></p> <p>Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • Impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included</p>	<p>4047438017688  85182200  273 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-SP-EXT-CM</b>  <b>SpeakerMount S1x, Matt Chrome</b></p> <p>Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • Impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included</p>	<p>4047438017695  85182200  273 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-S14-OPT-MK-CW</b>  <b>Extension Set Sensor Module, 40 mm And 15°</b></p> <p>Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut</p>	<p>4047438016384  90079100  96 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-S14-OPT-MK-EX</b>  <b>Extension Sensor Module, 40 mm</b></p> <p>1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions</p>	<p>4047438016391  90079100  62 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-FLEX-OPT-AM-BL</b>  <b>AudioMount S26/S1xM, Self-Adhesive</b></p> <p>Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)</p>	<p>4047438019873  85299065  386 g</p>	<p>24,0 cm  13,6 cm  5,3 cm  1,7 l</p>

## Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M-OWA-AU</b>	4047438030328	19,6 cm
	<b>On-Wall Mounting Set With Audio For v26, White</b>	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	510 g	14,8 cm
			5,2 l
	<b>Mx-M-OWA-AU-b</b>	4047438030335	19,6 cm
	<b>On-Wall Mounting Set With Audio For v26, Black</b>	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	510 g	14,8 cm
			5,2 l
	<b>MX-MT-OW2-AUD</b>	4047438027632	19,6 cm
	<b>On-Wall Mounting Set With Audio For v25, White</b>	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	500 g	14,8 cm
			5,2 l
	<b>MX-MT-OW2-AUD-b</b>	4047438027670	19,6 cm
	<b>On-Wall Mounting Set With Audio For v25, Black</b>	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	500 g	14,8 cm
			5,2 l
	<b>MX-MT-TUBE</b>	4047438027557	29,6 cm
	<b>MxTubeMount Ceiling Suspension System</b>	90079100	19,6 cm
	For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color: white	870 g	9,0 cm
			5,2 l
	<b>MX-MT-TUBE100</b>	4047438027687	106,0 cm
	<b>MxTube, 1 m</b>	90079100	4,0 cm
	Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	700 g	4,0 cm
			1,7 l
	<b>MX-MT-TUBE200</b>	4047438027564	212,5 cm
	<b>MxTube, 2 m</b>	90079100	4,0 cm
	Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	1.390 g	4,0 cm
			3,4 l

	<p><b>MX-OPT-UP1</b> <b>Cavity Wall Installation Set i2x</b></p> <p>Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations</p>	<p>4047438022118 90079100 158 g</p>	<p>14,8 cm 9,8 cm 9,0 cm 1,3 l</p>
	<p><b>MX-OPT-AP2</b> <b>On-Wall Mounting Set For i2x</b></p> <p>Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white</p>	<p>4047438025898 90079100 136 g</p>	<p>14,8 cm 9,8 cm 9,0 cm 1,3 l</p>
	<p><b>MX-MT-OW-1</b> <b>On-Wall Mounting Set For c2x/p2x</b></p> <p>Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White</p>	<p>4047438027083 90079100 514 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>MX-MT-CM-1</b> <b>Corner Mounting Set For c2x</b></p> <p>Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White</p>	<p>4047438027076 90079100 448 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-OPT-AP</b> <b>On-Wall Mounting Set For Q2x/D2x/ExtIO</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438011358 90079100 612 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-OPT-AP-10DEG</b> <b>On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438010283 90079100 552 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-D15-OPT-WHMH-Set</b> <b>Wall &amp; Pole/Corner Mount Set For D1x</b></p> <p>Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438018159 90079100 6.280 g</p>	<p>41,0 cm 31,0 cm 39,0 cm 49,6 l</p>
	<p><b>MX-OPT-WHMH-Set</b> <b>Wall &amp; Pole/Corner Mount Set For Q2x/D2x/ExtIO</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438011396 90079100 3.380 g</p>	<p>41,0 cm 31,0 cm 20,0 cm 25,4 l</p>

	<p><b>MX-WH-Dome</b>  <b>Wall Mount For D1x</b>            Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts</p>	<p>4047438002233            90079100            2.020 g</p>	<p>39,5 cm            29,6 cm            18,0 cm            21,0 l</p>
	<p><b>MX-OPT-WH</b>  <b>Wall Mount For Q2x/D2x/ExtIO</b>            Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts</p>	<p>4047438011372            90079100            886 g</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>MX-MH-Dome-ESWS</b>  <b>Pole/Corner Mount For MX-WH-Dome</b>            Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002240            90079100            3.000 g</p>	<p>34,0 cm            18,5 cm            11,5 cm            7,2 l</p>
	<p><b>MX-MH-SecureFlex-ESWS</b>  <b>Pole Mount For M1x/M2x</b>            Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002226            90079100            1.230 g</p>	<p>20,0 cm            15,2 cm            8,0 cm            2,4 l</p>
	<p><b>MX-OPT-MH</b>  <b>Pole/Corner Mount For MX-OPT-WH</b>            Suitable for: D7x, Q7x, Q2x, D2x, ExtIO • Mount for fastening the wall mount Mx-M-WM-DQ and MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) for the Q2x/D2x und ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm • Wall mounts (Mx-M-WM-DQ or MX-OPT-WH) are not included in the scope of delivery and must be ordered separately</p>	<p>4047438011389            90079100            2.050 g</p>	<p>21,0 cm            20,0 cm            17,0 cm            7,1 l</p>
	<p><b>MX-OPT-IC-ESMA</b>  <b>In-Ceiling Set For Q2x/D2x/ExtIO, Matt</b>            Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011433            90079100            724 g</p>	<p>29,6 cm            19,6 cm            9,0 cm            5,2 l</p>
	<p><b>MX-OPT-IC-ESPO</b>  <b>In-Ceiling Set For Q2x/D2x/ExtIO, Polished</b>            Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011426            90079100            724 g</p>	<p>29,6 cm            19,6 cm            9,0 cm            5,2 l</p>
	<p><b>MX-OPT-IC</b>  <b>In-Ceiling Set For Q2x/D2x/ExtIO, White</b>            Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011365            90079100            412 g</p>	<p>29,6 cm            19,6 cm            9,0 cm            5,2 l</p>



**MX-DH-M24-SecureFlex**  
**Ceiling Mount For M16/M26**

Suitable for: M16, M26, M15, M25, M24 • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)

4047438015653	15,0 cm
90079100	9,5 cm
160 g	9,0 cm
	1,3 l



**MX-OPT-TW-Demo-1**  
**Demo Table/Wall Mount For Q2x/D2x**




Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	14,8 cm
90079100	9,8 cm
170 g	9,0 cm
	1,3 l

## MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-FLEX-OPT-CBL-015</b> <b>Sensor Module Cable For M15/M16, 0.15 m</b> Length: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	4047438019941 85444210 16 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-05</b> <b>Sensor Cable For S1x, 0.5 m</b> Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018890 85444210 66 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-1</b> <b>Sensor Cable For S1x, 1 m</b> Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018883 85444210 80 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-2</b> <b>Sensor Cable For S1x, 2 m</b> Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018876 85444210 116 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-3</b> <b>Sensor Cable For S1x (6MP/Thermal), 3 m</b> Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules	4047438024303 85444210 144 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-AB-05</b> <b>USB Device Cable For M/Q/T2x, 0.5 m</b> MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device	4047438016728 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-AB-2</b> <b>USB Device Cable For M/Q/T2x, 2 m</b> MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB-Gerät	4047438016711 85444210 102 g	10,0 cm 7,5 cm 9,0 cm 0,7 l



	<p><b>MX-CBL-MU-EN-AB-5</b>  <b>USB Device Cable For M/Q/T2x, 5 m</b>  MiniUSB angled &gt; USB-A straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device</p>	<p>4047438016704  85444210  194 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-EN-PG-05</b>  <b>ExtIO Cable For M/Q/T2x, 0,5 m</b>  MiniUSB angled &gt; MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO</p>	<p>4047438020947  85444210  52 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-EN-PG-2</b>  <b>ExtIO Cable For M/Q/T2x, 2 m</b>  MiniUSB angled &gt; MiniUSB+ angled • Length 2 m/6,6 m • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO</p>	<p>4047438020930  85444210  102 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-EN-PG-5</b>  <b>ExtIO Cable for M/Q/T2x, 5 m</b>  MiniUSB angled &gt; MiniUSB+ angled • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO</p>	<p>4047438020923  85444210  194 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-AB-05</b>  <b>USB Device Cable For D25/D26, 0,5 m</b>  MiniUSB+ angled &gt; USB-A straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect ext. USB device</p>	<p>4047438020916  85444210  52 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-AB-2</b>  <b>USB Device Cable For D25/D26, 2 m</b>  MiniUSB+ angled &gt; USB-A straight • Length 2 m/6,6 ft • For D25/D26 • to connect ext. USB device</p>	<p>4047438020909  85444210  102 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-AB-5</b>  <b>USB Device Cable For D25/D26, 5 m</b>  MiniUSB+ angled &gt; USB-A straight • Length 5 m/16,4 ft • For D25/D26 • To connect ext. USB device</p>	<p>4047438020893  85444210  194 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-EN-PG-05</b>  <b>ExtIO Cable For D25/D26, 0,5 m</b>  MiniUSB+ angled &gt; MiniUSB+ angled • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-ExtIO</p>	<p>4047438020886  85444210  52 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

**MX-CBL-MU-EN-PG-EN-PG-2****ExtIO Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D25/D26 • To connect MX-ExtIO

4047438020879 9,8 cm  
85444210 7,5 cm  
102 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-PG-EN-PG-5****ExtIO Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D25/D26 • To connect MX-ExtIO

4047438020862 9,8 cm  
85444210 7,5 cm  
194 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-PG-STR-05****232-IO-Box Cable For D25/D26, 0.5 m**

MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020855 9,8 cm  
85444210 7,5 cm  
52 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-PG-STR-2****232-IO-Box Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020848 9,8 cm  
85444210 7,5 cm  
102 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-PG-STR-5****232-IO-Box Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020831 9,8 cm  
85444210 7,5 cm  
194 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-STR-05****232-IO-Box Cable For M/Q/T2x, 0.5 m**

MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016667 10,0 cm  
85444210 7,5 cm  
48 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-STR-2****232-IO-Box Cable For M/Q/T2x, 2 m**

MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016650 10,0 cm  
85444210 7,5 cm  
94 g 9,0 cm  
0,7 l

**MX-CBL-MU-EN-STR-5****232-IO-Box Cable For M/Q/T2x, 5 m**

MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016643 10,0 cm  
85444210 7,5 cm  
188 g 9,0 cm  
0,7 l

	<p><b>MX-CBL-MU-STR-05</b>  <b>232-IO-Box Cable For D/S/V1x, 0.5 m</b>  MiniUSB straight &gt; MiniUSB straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016605  85444210  50 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-2</b>  <b>232-IO-Box Cable For D/S/V1x, 2 m</b>  MiniUSB straight &gt; MiniUSB straight • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016599  85444210  94 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-5</b>  <b>232-IO-Box Cable For D/S/V1x, 5 m</b>  MiniUSB straight &gt; MiniUSB straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016445  85444210  184 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-05</b>  <b>USB Device Cable For D/S/V1x, 0.5 m</b>  MiniUSB straight &gt; USB-A straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016698  85444210  56 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-2</b>  <b>USB Device Cable For D/S/V1x, 2 m</b>  MiniUSB straight &gt; USB-A straight • Length 2 m/6,6 ft • D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016681  85444210  102 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-5</b>  <b>USB Device Cable For D/S/V1x, 5 m</b>  MiniUSB straight &gt; USB-A straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016674  85444210  196 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-EN-PG-05</b>  <b>ExtIO Cable For D/S/V1x, 0.5 m</b>  MiniUSB straight &gt; MiniUSB+ angled • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO</p>	<p>4047438020978  85444210  52 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-STR-EN-PG-2</b>  <b>ExtIO Cable For D/S/V1x, 2 m</b>  MiniUSB straight &gt; MiniUSB+ angled • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO</p>	<p>4047438020961  85444210  102 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

**MX-CBL-MU-STR-EN-PG-5****ExtIO Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020954	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-OPT-CBL-LAN-1****Ethernet Patch Cable, 1 m**

Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300	23,5 cm
85444210	15,0 cm
36 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-10****Ethernet Patch Cable, 10 m**

Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331	27,0 cm
85444210	17,0 cm
462 g	4,0 cm
	1,8 l

**MX-OPT-CBL-LAN-2****Ethernet Patch Cable, 2 m**

Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317	23,5 cm
85444210	15,0 cm
62 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-5****Ethernet Patch Cable, 5 m**

Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324	23,5 cm
85444210	15,0 cm
237 g	4,0 cm
	1,4 l

**MX-FLEX-IO-CBL-015****IO Connection Cable For M15/M16, 0.15 m**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)

4047438019958	13,5 cm
85444210	8,0 cm
10 g	2,0 cm
	0,2 l

**MX-CBL-NPA-BAT-2****NPA Battery Cable, 2 m**

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft








4047438013949	10,0 cm
85444210	7,5 cm
68 g	9,0 cm
	0,7 l

## Other Camera Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-M7SA-Blind</b> <b>Blind Module M73</b> For M73 • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438035415 90079100 50 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-OPT-Ring-L10-L12-BL</b> <b>Sealing Ring For Hemispheric Sensor Modules, Black</b> Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	4047438021241 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	<b>MX-OPT-Ring-L10-L12-PW</b> <b>Sealing Ring For Hemispheric Sensor Modules, White</b> Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	4047438021234 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	<b>MX-OPT-SEC-SCREWS-SET</b> <b>Security Screw Set With Allen Bit For M1x/M2x</b> Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438021265 90079100 120 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	<b>MX-SM-Blind-PW</b> <b>Blind Module M1x</b> For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438019965 90079100 46 g	9,0 cm 7,5 cm 5,0 cm 0,3 l






## MOBOTIX MOVE Accessories

### MOBOTIX MOVE Accessories


	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-SD-DCS</b> <b>Tinted Dome For MOBOTIX MOVE SD-330</b> Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	4047438031776 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	<b>Mx-A-SD-DCT</b> <b>Dome (Standard) For MOBOTIX MOVE SD-330</b> Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	4047438031783 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	<b>Mx-A-VD-DCS</b> <b>Tinted Dome For MOBOTIX MOVE VandalDome</b> Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras	4047438031714 90079100 210 g	16,1 cm 16,1 cm 11,5 cm 3,0 l
	<b>Mx-A-VD-DCT</b> <b>Dome (Standard) For MOBOTIX MOVE VandalDome</b> VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras	4047438031721 90079100 250 g	16,1 cm 16,1 cm 11,5 cm 3,0 l
	<b>Mx-M-BC-P</b> <b>Pole Mount For MOBOTIX MOVE 4MP BulletCamera</b> BC Pole Mount suitable for MOBOTIX MOVE BulletCameras BC-4-IR, BC-4-IR-D, VB-4-IR and VB-4-IR-D	4047438031677 90079100 1.000 g	17,3 cm 17,3 cm 16,7 cm 5,0 l
	<b>Mx-M-BC-W</b> <b>Wall Mount For MOBOTIX MOVE 4MP BulletCamera</b> BC Wall Mount suitable for MOBOTIX MOVE BulletCamera BC-4-IR, BC-4-IR-D, VB-4-IR and VB-4-IR-D	4047438031660 90079100 840 g	17,3 cm 17,3 cm 10,7 cm 3,2 l
	<b>Mx-M-NVR16-RM</b> <b>19" Rack Mounting Brackets for MOVE NVR 16CH</b> 2x metal mounting brackets for installing MOBOTIX MOVE NVR 16CH in a 19" rack	4047438037075 85299097 447 g	14,5 cm 11,0 cm 6,0 cm 1,0 l

	<p><b>Mx-M-NVR8-RM</b>  <b>19" Rack Mounting Brackets for MOVE NVR 8CH</b>            2x metal mounting brackets for installing MOBOTIX MOVE NVR 8CH in an 19" rack</p>	<p>4047438037068            85299097            544 g</p>	<p>14,5 cm            11,0 cm            6,0 cm            1,0 l</p>
	<p><b>Mx-M-SD-C</b>  <b>Corner Mount For MOBOTIX MOVE SD-330/SD-340-IR</b>            SD Corner Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)</p>	<p>4047438031769            90079100            2.170 g</p>	<p>21,0 cm            12,5 cm            25,0 cm            6,6 l</p>
	<p><b>Mx-M-SD-GN</b>  <b>MOBOTIX MOVE SD Parapet Mount</b>            MOBOTIX MOVE SD Parapet Mount(Gooseneck) with integrated junction Box for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR</p>	<p>4047438038997            90079100            14.800 g</p>	<p>90,0 cm            57,0 cm            20,0 cm            102,6 l</p>
	<p><b>Mx-M-SD-P</b>  <b>Pole Mount For MOBOTIX MOVE SD-330/SD-340-IR</b>            SD Pole Mount suitable for MOBOTIX MOVE SpeedDome SD-330 und SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)</p>	<p>4047438031752            90079100            1.580 g</p>	<p>31,0 cm            15,5 cm            26,0 cm            12,5 l</p>
	<p><b>Mx-M-SD-PM</b>  <b>MOBOTIX MOVE SD Pendant Mount Kit</b>            MOBOTIX MOVE SD Pendant Mount Kit 25 cm incl. Base-Mount, 25 cm pendant pipe, installation material and safety wires 50cm &amp; 1m. Max. extendable pendant mount length 1m by usage of additional pendant mount extension Mx-M-SD-PMEXT</p>	<p>4047438039000            90079100            2.295 g</p>	<p>64,0 cm            22,0 cm            22,0 cm            31,0 l</p>
	<p><b>Mx-M-SD-PMEXT</b>  <b>MOBOTIX MOVE SD PM Extension</b>            MOBOTIX MOVE SD Pendant Mount 25cm extension for Mx-M-SD-PM</p>	<p>4047438039017            90079100            800 g</p>	<p>14,4 cm            14,5 cm            28,0 cm            5,8 l</p>
	<p><b>Mx-M-SD-W</b>  <b>Wall Mount For MOBOTIX MOVE SD-330/SD-340-IR</b>            SD Wall Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)</p>	<p>4047438031745            90079100            840 g</p>	<p>21,6 cm            12,7 cm            14,8 cm            4,1 l</p>
	<p><b>Mx-M-SD-WM</b>  <b>Wall Mount For MOBOTIX MOVE SpeedDome</b>            MOBOTIX MOVE SD Wall Mount supporting optional Junction Box Mx-M-SD-WMJB, suitable for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR</p>	<p>4047438038973            90079100            1.300 g</p>	<p>33,0 cm            15,0 cm            23,0 cm            11,4 l</p>



	<p><b>Mx-M-SD-WMJB</b>  <b>MOBOTIX MOVE SD Junction Box</b>  MOBOTIX MOVE SD Wall Mount Junction Box for use with Wall Mount Mx-M-SD-WM</p>	<p>4047438038980  90079100  4.800 g</p>	<p>29,0 cm  32,0 cm  19,0 cm  17,6 l</p>
	<p><b>Mx-M-VD-C</b>  <b>Corner Mount For MOBOTIX MOVE VandalDome</b>  VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031738  90079100  2.170 g</p>	<p>21,0 cm  12,5 cm  25,0 cm  6,6 l</p>
	<p><b>Mx-M-VD-IC</b>  <b>In-Ceiling Set For MOBOTIX MOVE VandalDome</b>  VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031684  90079100  800 g</p>	<p>23,4 cm  23,4 cm  12,8 cm  7,0 l</p>
	<p><b>Mx-M-VD-P</b>  <b>Pole Mount For MOBOTIX MOVE VandalDome</b>  VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031707  90079100  1.580 g</p>	<p>31,0 cm  15,5 cm  26,0 cm  12,5 l</p>
	<p><b>Mx-M-VD-W</b>  <b>Wall Mount For MOBOTIX MOVE VandalDome</b>  VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031691  90079100  1.400 g</p>	<p>31,0 cm  22,0 cm  18,0 cm  12,3 l</p>


## MOVE Other Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>Mx-A-ETP1A-2601-SET</b></p> <p><b>Media converter set Ethernet(PoE+) – Twisted-Pair</b></p> <p>Mx-ETP1A-2601-SET Complete set consisting of two two-wire transmitting and receiving units for realising an Ethernet transmission path via Twisted Pair cable. • Transmission of Ethernet and PoE+ power supply via two-wire line according to IEEE1901. • Simple connection of 10/100 Mbps Ethernet end devices • Max. 95 Mbps transmission bandwidth, range up to 600m for data / 300m for PoE depending on the quality of the Twisted-Pair link • 128 bit AES network data encryption • Power supply 2-wire transmitter (Tx) and receiver (Rx) as well as end device via PoE+ network switch or external power supply 56VDC / 1.2A (not included!) • Connected end devices are supplied via PoE switch IEEE802.3af(PoE), IEEE802.3at (PoE+), UPoE up to 60W (requires ext. power supply unit). • Status LEDs (data, power supply, data link, PoE) • Integrated Overvoltage protection (IEC 61000-4-5 4kV(1.2 / 50us), 2kA(8 / 20us)) • Power Supply: TX: T-Linx or DC12V-57V, RX: PoE Switch or DC48V-57V • Operational temperature: -20 to 60 ;C • Dimensions: 80.4(L) x 61.6(W) x 24(H)mm • Weight: RX/TX: 102g • Warranty: 2 years</p>	<p>4047438041317</p> <p>85299065</p> <p>368 g</p>	<p>20,7 cm</p> <p>12,5 cm</p> <p>7,0 cm</p> <p>1,8 l</p>

# System Components

## Functional Modules for MOBOTIX 7 Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-F-AUDA</b> <b>M73/S74 Audio Module equipped with microphone /</b> Weatherproof audio module (IP66, -30 to 65 °C, IP07) with integrated microphone and speaker for connection to the MOBOTIX M73 camera, no camera removal required • In connection with the audio cable Mx-A-S7A-AUCBL05-AN and the IO plug-in board Mx-F-S7A-INT01, the audio module can also be operated at the S74 (compatible with S74 module mounts)	4047438034937 85299065 150 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-F-IRA-S</b> <b>M73/S74 IR Light Module for Standard Lens (45° - 60°)</b> Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 45°-60° illumination angle (horizontal) • 860 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses: up to 70 m	4047438034913 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-F-IRA-T</b> <b>M73/S74 IR Light Module for Tele Lens (15° - 30°)</b> Infrared illuminator module for MOBOTIX M73/S74 cameras night sensor modules with 15°-30° illumination angle (horizontal) • 860 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses up to 100 m	4047438034920 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-F-IRA-W</b> <b>M73/S74 IR Light Module for Wide Lens (95°)</b> Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 95° illumination angle (horizontal) • 860 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with W-IR illuminator: up to 40 m	4047438034906 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-F-MSA</b> <b>MOBOTIX 7 MultiSense Outdoor</b> Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (max ±0.4°C / 0.72°F) and microphone • Camera connection and supply via MOBOTIX 7 sensor cable (up to 3m): power consumption approx. 100 mW • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Protection class IP66 • IK05 • Housing color: white	4047438035545 85299065 100 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>Mx-F-S7A-INT01</b> <b>S74 IO Slide in Board</b> S74 IO slide in board with 1x input / output, 1x line in / out and 1x mic in / speaker out functionality • Connection option for audio module Mx-F-AUDA with audio cable Mx-A-S7A-AUCBL05-AN	4047438035576 85299065 110 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>Mx-F-S7A-LCE</b> <b>MOBOTIX 7 Long Cable Extender Kit (Type A)</b> MOBOTIX 7 long cable extender kit - up to 30m extension between S74A and MOBOTIX 7 sensor module via LWL and power cable	4047438037877 85299065 448 g	19,6 cm 14,8 cm 9,0 cm 2,6 l

**Mx-F-S7A-LSA****S74 network slide in board with LSA terminal**

S74 network slide in board with LSA terminal

4047438037051	14,8 cm
85299065	9,8 cm
110 g	9,0 cm
	1,3 l

**Mx-F-S7A-RJ45****S74 Network slide in board with RJ45 socket**

S74 Network slide in board with RJ45 socket








4047438035569	14,8 cm
85299065	9,8 cm
110 g	9,0 cm
	1,3 l


**Mx-F-S7A-RJ45-VDC****S74 RJ45 Network slide in board with 12/24 VDC Power**

S74 Network slide in board with RJ45 socket and 12/24V DC Power Supply

4047438039680	14,8 cm
85299065	9,8 cm
110 g	9,0 cm
	1,3 l


## Interface Boxes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-GPSA</b>	4047438035507	10,5 cm
	<b>MX-GPS-Box</b> Weatherproof GPS time base for MOBOTIX systems • GPS and Glonass support • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	85299065 120 g	6,8 cm 10,5 cm 0,7 l
	<b>MX-OPT-BPA1-EXT</b>	4047438025881	10,5 cm
	<b>MX-BPA-BOX</b> Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP66/IK08, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065 120 g	6,8 cm 10,5 cm 0,7 l
	<b>MX-OPT-NPA1-EXT</b>	4047438015424	10,0 cm
	<b>MX-NPA-Box</b> Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	85043180 140 g	7,5 cm 9,0 cm 0,7 l
	<b>MX-Overvoltage-Protection-Box-LSA</b>	4047438018470	10,0 cm
	<b>Network Connector with Surge Protection, LSA Version</b> Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065 146 g	7,5 cm 9,0 cm 0,7 l
	<b>MX-Overvoltage-Protection-Box-RJ45</b>	4047438018463	10,0 cm
	<b>Network Connector with Surge Protection, RJ45 Version</b> Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065 150 g	7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-Input1-EXT</b>	4047438021227	10,0 cm
	<b>MX-Input-Box</b> Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connecting up to 6 external sensors • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065 148 g	7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-Output1-EXT</b>	4047438021944	10,5 cm
	<b>MX-Output-Box</b> Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP66/IK07, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065 120 g	6,8 cm 10,5 cm 0,7 l

**MX-OPT-RS1-EXT****MX-232-IO-Box**

Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

4047438015417	10,5 cm
85299065	6,8 cm
120 9	10,5 cm
	0,7 l

**MX-PROX-BOX****MX-Proximity-Box**

Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Detection range: up to 8m/26 ft. (person), up to 20m/66 ft. (vehicle) • Camera connection and supply via MxBus • Protection class IP66/IK07, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).

4047438025935	10,5 cm
85299065	6,8 cm
165 9	10,5 cm
	0,7 l

**MX-OPT-DIGI-INT****MxDigitizer For S1x**









Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white


4047438028790	10,5 cm
85299065	6,8 cm
120 9	10,5 cm
	0,7 l



## Functional Enhancement & IR Illuminators

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-TCLIENTA</b>	4047438028899	9,8 cm
	<b>MxThinClient</b>	84714900	7,5 cm
	PoE-supplied IP video device to transfer live pictures of cameras and door stations to a monitor/TV set • Password protected web interface • Automatic change of video source via sequencer (time-controlled) or via MxMessageSystem (event-controlled) • Input (connection to PoE switch): 1x Ethernet 100Base-T (RJ45) • Output (connection to monitor/TV set): 1x HDMI Type D (MicroHDMI) • Connection cables (Ethernet, HDMI) are not included • Indoor-use only: Protection class IP20, ambient temperature 0 to 40 °C (32 to 104°F) • With the supplied adhesive strips, the device can easily be attached to the backside of the monitor/TV	200 g	9,0 cm
			0,7 l
	<b>MX-ExtIO</b>	4047438009850	29,6 cm
	<b>ExtIO Extension Module For All MOBOTIX Cameras</b>	85299065	19,6 cm
	ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60° C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via USB	744 g	9,0 cm
			5,2 l
	<b>MX-MULTISENSE1-EXT</b>	4047438028905	9,8 cm
	<b>MxMultiSense Outdoor (HS code 85299065)</b>	85299065	7,5 cm
	Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (±0.3°C / 0.18°F) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white	110 g	9,0 cm
			0,7 l
	<b>MX-OPT-IO3-INT</b>	4047438025928	10,7 cm
	<b>Extension Module For c25, i25, p25 And v25</b>	85299065	5,2 cm
	Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	<b>Mx-A-IOA-IC</b>	4047438029032	10,7 cm
	<b>Extension Module For All Indoor Cameras x26A/x26B</b>	85299065	5,2 cm
	Expansion module for Indoor Cameras c26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	<b>Mx-A-SPA</b>	4047438030229	30,5 cm
	<b>MxSplitProtect Installation Box, IP66</b>	85299065	24,0 cm
	Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white	1.184 g	16,0 cm
			11,7 l

	<p><b>Mx-A-SPA-HR</b> <b>MxSplitProtectHR Hat Rail Module</b></p> <p>Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray</p>	<p>4047438030236 85299065 130 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p><b>Mx-A-SPCA-M</b> <b>MxSplitProtect Cover, M-Cameras</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white</p>	<p>4047438028820 85299065 514 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-SPCA-H</b> <b>MxSplitProtect Cover, Horizontal</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (orD2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white</p>	<p>4047438028837 85299065 570 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-SPCA-V</b> <b>MxSplitProtect Cover, Vertical</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white</p>	<p>4047438028844 85299065 482 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-IRA-120</b> <b>MxIRLight Infrared Illuminator (860 nm), 120°x120°</b></p> <p>Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030342 85394900 1.098 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-90</b> <b>MxIRLight Infrared Illuminator (860 nm), 90°x90°</b></p> <p>Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030359 85394900 1.112 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-60</b> <b>MxIRLight Infrared Illuminator (860 nm), 60°x60°</b></p> <p>Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030366 85394900 1.116 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-45</b> <b>MxIRLight Infrared Illuminator (860 nm), 45°x45°</b></p> <p>Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030373 85394900 1.124 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>

**Mx-A-IRA-30****MxIRLight Infrared Illuminator (860 nm), 30°x30°**

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030380	20,5 cm
85394900	17,5 cm
1.096 9	12,5 cm
	4,5 l

**Mx-A-IRA-15****MxIRLight Infrared Illuminator (860 nm), 15°x15°**

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397	20,5 cm
85394900	17,5 cm
1.090 9	12,5 cm
	4,5 l

**Mx-M-IRA-ML****MxIRLight Mounting Brackets For M1x**

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403	19,6 cm
85399090	5,5 cm
216 9	3,5 cm
	0,4 l

**Mx-M-IRA-M****MxIRLight Mounting Brackets For M2x**

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410	14,0 cm
85399090	5,5 cm
150 9	3,5 cm
	0,3 l

## PoE Power Supply

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-NPA-UPoE1A-60W</b> <b>UPoE Power Injector 60W</b> UPoE (PoE++) 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • 14° to 113°F @60W • 14° to 131°F @30W • IEEE 802.3at compliant with 2-event classification • IEEE 802.3af backward compatible • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation	4047438039024 85043180 450 g	20,5 cm 11,5 cm 6,5 cm 1,5 l
	<b>MX-SWITCH1</b> <b>MxSwitch For DIN Rail Mounting</b> PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable	4047438028882 85176200 310 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-EU-Set</b> <b>PoE Power Adapter Set, EU</b> PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 and M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012249 85043180 268 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-INT-Set</b> <b>PoE Power Adapter Set, INT</b> PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012256 85043180 314 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-RJ</b> <b>PoE Power Adapter</b> PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed	4047438013932 85043180 60 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-SNT-INT-PoE</b> <b>Universal Power Supply With 4 Power Plugs</b> For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F	4047438013925 85043180 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

## MOBOTIX Storage & Recording Solutions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S-NVR1A-64-POE24</b>	4047438040365	58,0 cm
	<b>MOBOTIX MOVE NVR Network Video Recorder 64 Channels</b> MOBOTIX MOVE NVR Network Video Recorder for recording and Display up to 64 IP Cameras (Resolution up to 12MP) • 24 integrated PoE+ Ports for centralized powering of connected IP-Cameras • 8x 3.5" SATA3 locklable HDD cartridge-slots (Delivery without hard disks (not available via MOBOTIX) • Harddrives "Hot-Swappable" • RAID 0/1/5/10 Support for Data recovering in case of HDD Failure • Optional Failover-Server functionality withing MOVE NVR System • IP-Data-Throughput (Live & Recording): avrg.: 480 Mbps, peak 2upt to 540 Mbps • Video-Codexs : H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support • 19"-Rack mount kit included. • Environmental Temperature 0 to 40°C • Power Supply: AC AC 100-240V, ATX 520W (53V/360W for PoE; 12V/160W for HDD/System) • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • Warranty: 2 Years (excl. HDD's)	85255000 12.510 g	58,0 cm 25,0 cm 84,1 l
	<b>Mx-S-NAS2A-8</b>	4047438034036	27,0 cm
	<b>MOBOTIX NAS 2-Bay/8 Channels (NAS-251G)</b> MOBOTIX Network Attached Storage device with 2 bays and 8 ONVIF S channels • Max. Storage capacity net (with redundancy): 12 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 2.320 g	20,2 cm 23,5 cm 12,8 l
	<b>Mx-S-NAS4A-16</b>	4047438034043	30,5 cm
	<b>MOBOTIX NAS 4-Bay/16 Channels (NAS-451G)</b> MOBOTIX Network Attached Storage device with 4 bays and 16 ONVIF S channels • Max. Storage capacity net (with redundancy): 36 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 3.420 g	25,0 cm 31,6 cm 24,1 l
	<b>Mx-S-NAS8A-32</b>	4047438034050	72,0 cm
	<b>MOBOTIX NAS 8-Bay/32 Channels (NAS-873UG)</b> MOBOTIX Network Attached Storage device with 8 bays and 32 ONVIF S channels • Max. Storage capacity net (with redundancy): 84 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 15.330 g	56,4 cm 26,0 cm 105,6 l
	<b>Mx-S-NVR1A-8-POE</b>	4047438036849	42,6 cm
	<b>MOBOTIX MOVE NVR Network Video Recorder 8 Channels</b> MOBOTIX MOVE NVR Network Video Recorder with 8 integrated PoE IP-Camera Channels (12 IP-Cameras total support) • Max. Storage capacity net (internal & external): 20 TB (2x 3.5" SATA3) • Delivery without hard disks (not available via MOBOTIX) • IP-Data-Throughput (Live & Recording): 80 up to peak 120Mbps • Recording & Playback: H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support	85255000 4.200 g	37,9 cm 11,0 cm 17,8 l
	<b>Mx-S-NVR1A-16-POE</b>	4047438036856	49,5 cm
	<b>MOBOTIX MOVE NVR Network Video Recorder 16 Channels</b> MOBOTIX MOVE NVR Network Video Recorder with 16 integrated PoE IP-Camera Channels (24 IP-Cameras total support) • Max. Storage capacity net: 28 TB (2x 3.5" SATA3) • Delivery without hard disks (not available via MOBOTIX) • IP-Data-Throughput (Live & Recording): 160 up to peak 240Mbps • Recording • Support of ONVIF S conformant 3rd Party cameras: H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support	85255000 8.500 g	34,5 cm 18,1 cm 30,9 l

# MOBOTIX Cloud

BeyondHumanVision

MOBOTIX

## MOBOTIX Cloud Bridge



### Article No. / Name / Description

### EAN / HS / weight dimen.

#### Mx-S-BRIDGEA-DT-15

4047438035453 25,6 cm

#### MOBOTIX CLOUD Bridge for up to 15 IP Cameras

85299065 20,5 cm








High-security connection box for the MOBOTIX CLOUD VMS • Locally connected to the Internet and up to 15 ONVIF IP cameras • Cybersecure connection to regionally available MOBOTIX CLOUD data centers • Secure end-to-end encryption of all data stored and transferred in the system • No data loss in case of up to 2-day Internet outage: Integrated hard disk as a memory buffer in case of interrupted connection to the cloud • No data loss due to Internet bandwidth fluctuations: Automatic data buffering in the BRIDGE • Ultra flexible cloud data storage with individually selectable retention period (max. 5 years) • Compact and fanless device design for highest reliability • Dimensions (LxWxH): 127 x 127 x 45 mm (5" x 5" x 1.75") • Connections: AC power supply (adapter included), 2x ETH (1x for PoE switch for local cameras, 1x for internet router), monitor and keyboard (optional)









1.420 g 9,5 cm









5,0 l



















## MOBOTIX Cloud Subscriptions









	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-CL-Sub-M10-1</b> <b>MOBOTIX CLOUD Camera license, only live stream, NO</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438040327	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D7-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/7 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036375	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D14-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/14 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036382	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D30-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/30 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036399	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D60-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/60 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036405	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D90-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/90 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036412	cm cm g cm l
	<b>Mx-CL-Sub-SD1-D180-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/180 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036429	cm cm g cm l









	<b>Mx-CL-Sub-SD1-D365-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/365 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036436	cm		
	<b>Mx-CL-Sub-SD1-D730-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/730 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036443	cm	g	cm
	<b>Mx-CL-Sub-SD1-D1095-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/1095 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036450	cm	g	cm
	<b>Mx-CL-Sub-SD1-D1825-1</b> <b>MOBOTIX CLOUD Camera Subscription, VGA/1825 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036467	cm	g	cm
	<b>Mx-CL-Sub-HD1-D7-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/7 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036023	cm	g	cm
	<b>Mx-CL-Sub-HD1-D14-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/14 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036030	cm	g	cm
	<b>Mx-CL-Sub-HD1-D30-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/30 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036047	cm	g	cm
	<b>Mx-CL-Sub-HD1-D60-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/60 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036054	cm	g	cm

	<b>Mx-CL-Sub-HD1-D90-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/90 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036061	cm	g	cm	l
	<b>Mx-CL-Sub-HD1-D180-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/180 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036078	cm	g	cm	l
	<b>Mx-CL-Sub-HD1-D365-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/365 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036085	cm	g	cm	l
	<b>Mx-CL-Sub-HD1-D730-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/730 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036092	cm	g	cm	l
	<b>Mx-CL-Sub-HD1-D1095-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/1095 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036108	cm	g	cm	l
	<b>Mx-CL-Sub-HD1-D1825-1</b> <b>MOBOTIX CLOUD Camera Subscription, 720p/1825 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036115	cm	g	cm	l
	<b>Mx-CL-Sub-HD2-D7-1</b> <b>MOBOTIX CLOUD Camera Subscription, 1080p/7 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036122	cm	g	cm	l
	<b>Mx-CL-Sub-HD2-D14-1</b> <b>MOBOTIX CLOUD Camera Subscription, 1080p/14 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036139	cm	g	cm	l









	<p><b>Mx-CL-Sub-HD2-D30-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/30 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036146	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D60-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/60 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036153	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D90-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/90 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036160	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D180-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/180 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036177	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D365-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/365 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036184	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D730-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/730 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036191	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D1095-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/1095 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036207	cm cm cm l
	<p><b>Mx-CL-Sub-HD2-D1825-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 1080p/1825 Days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036214	cm cm cm l









	<b>Mx-CL-Sub-HD3-D7-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/7 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036221	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D14-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/14 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036238	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D30-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/30 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036245	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D60-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/60 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036252	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D90-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/90 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036269	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D180-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/180 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036276	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D365-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/365 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036283	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D730-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/730 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX CLOUD access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036290	cm	g	cm	l

	<b>Mx-CL-Sub-HD3-D1095-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/1095 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036306	cm	g	cm	l
	<b>Mx-CL-Sub-HD3-D1825-1</b> <b>MOBOTIX CLOUD Camera Subscription, 3MP/1825 Days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036313	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D7-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/7 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036481	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D14-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/14 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036498	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D30-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/30 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036504	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D60-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/60 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036511	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D90-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/90 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036528	cm	g	cm	l
	<b>Mx-CL-Sub-HD4-D180-1</b> <b>MOBOTIX CLOUD Camera Subscription, 4MP/180 days</b> Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438036535	cm	g	cm	l

	<p><b>Mx-CL-Sub-HD4-D365-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 4MP/365 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036542	cm cm cm l
	<p><b>Mx-CL-Sub-HD4-D730-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 4MP/730 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036559	cm cm cm l
	<p><b>Mx-CL-Sub-HD4-D1095-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 4MP/1095 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036566	cm cm cm l
	<p><b>Mx-CL-Sub-HD4-D1825-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 4MP/1825 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036573	cm cm cm l
	<p><b>Mx-CL-Sub-HD5-D7-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/7 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036580	cm cm cm l
	<p><b>Mx-CL-Sub-HD5-D14-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/14 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036597	cm cm cm l
	<p><b>Mx-CL-Sub-HD5-D30-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/30 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036603	cm cm cm l
	<p><b>Mx-CL-Sub-HD5-D60-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/60 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036610	cm cm cm l



	<p><b>Mx-CL-Sub-HD5-D90-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/90 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036627	cm cm g cm l
	<p><b>Mx-CL-Sub-HD5-D180-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/180 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036634	cm cm g cm l
	<p><b>Mx-CL-Sub-HD5-D365-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/365 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036641	cm cm g cm l
	<p><b>Mx-CL-Sub-HD5-D730-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/730 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036658	cm cm g cm l
	<p><b>Mx-CL-Sub-HD5-D1095-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/1095 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036665	cm cm g cm l
	<p><b>Mx-CL-Sub-HD5-D1825-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 5MP/1825 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036672	cm cm g cm l
	<p><b>Mx-CL-Sub-HD10-D7-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/7 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036689	cm cm g cm l
	<p><b>Mx-CL-Sub-HD10-D14-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/14 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036696	cm cm g cm l

	<p><b>Mx-CL-Sub-HD10-D30-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/30 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036702	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D60-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/60 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036719	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D90-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/90 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036726	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D180-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/180 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036733	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D365-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/365 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036740	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D730-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/730 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036757	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D1095-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/1095 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036764	cm cm cm l
	<p><b>Mx-CL-Sub-HD10-D1825-1</b></p> <p><b>MOBOTIX CLOUD Camera Subscription, 10MP/1825 days</b></p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <a href="https://mobotixcloud.com">https://mobotixcloud.com</a> • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036771	cm cm cm l

**Mx-CL-Sub-ANA-001-1****MOBOTIX CLOUD Analytics Subscription, Line Cross**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Line Cross •  
Cancellation of subscription possible at any time at the end of the month

4047438036320

cm

g

cm

cm  
l**Mx-CL-Sub-ANA-002-1****MOBOTIX CLOUD Analytics Subscription, Counting**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Counting •  
Cancellation of subscription possible at any time at the end of the month

4047438036337

cm

g

cm

cm  
l**Mx-CL-Sub-ANA-003-1****MOBOTIX CLOUD Analytics Subscription, Area Intrusion**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •  
Cancellation of subscription possible at any time at the end of the month

4047438036344

cm

g

cm

cm  
l**Mx-CL-Sub-ANA-004-1****MOBOTIX CLOUD Analytics Subscription, Camera Tamper**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper  
Detect • Cancellation of subscription possible at any time at the end of the month

4047438036351

cm

g

cm

cm  
l**Mx-CL-Sub-ANA-005-1****MOBOTIX CLOUD Analytics Subscription, Loitering**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Loitering •  
Cancellation of subscription possible at any time at the end of the month

4047438036368

cm








g

cm

cm  
l

# Access Control

## T26B Camera Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-T26B-6D016</b>	4047438032025	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, White</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6N016</b>	4047438032032	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, White</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6D016-b</b>	4047438032049	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Black</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6N016-b</b>	4047438032056	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, Black</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6D016-s</b>	4047438032063	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Silver</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6N016-s</b>	4047438032070	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, Silver</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm 2,6 l
	<b>Mx-T26B-6D016-d</b>	4047438032087	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Dark Gray</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	400 g	9,0 cm 2,6 l

**Mx-T26B-6N016-d****T26 CamCore, 6MP, B016, Night, Dark Gray**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night)  
 • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray





4047438032094 19,6 cm

85258091 14,8 cm

400 g 9,0 cm

2,6 l

## KeypadRFID Module

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p><b>Mx-A-KEYC</b> <b>Keypad With RFID Technology For T26, White</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White</p>	4047438034135 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-b</b> <b>Keypad With RFID Technology For T26, Black</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black</p>	4047438034128 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-d</b> <b>Keypad With RFID Technology For T26, Dark Gray</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray</p>	4047438034111 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-s</b> <b>Keypad With RFID Technology For T26, Silver</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver</p>	4047438034104 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l



## BellRFID Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-BELLC</b> <b>BellRFID Base Module For T26, White</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438034067 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-b</b> <b>BellRFID Base Module For T26, Black</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438034074 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-d</b> <b>BellRFID Base Module For T26, Dark Gray</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438034081 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-s</b> <b>BellRFID Base Module For T26, Silver</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438034098 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-Bell1-Button-F1</b> <b>BellRFID Bell Button Set F1</b> 1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017190 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
	<b>MX-Bell1-Button-F2</b> <b>BellRFID Bell Button Set F2</b> 2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017176 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
	<b>MX-Bell1-Button-F3</b> <b>BellRFID Bell Button Set F3</b> 1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017527 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l

**MX-Bell1-Button-F4****BellRFID Bell Button Set F4**

4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

4047438017183 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l

**MX-Bell1-Button-05****BellRFID Bell Button Set 05**

5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label





4047438017534 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l

**MX-Bell1-Button-XL1****BellRFID Bell Button Set XL1**



1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

4047438017169 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l


## Info Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-Info1-EXT-PW</b>	4047438014991	19,6 cm
	<b>Info Module With LEDs, White</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	85414090	15,0 cm
		282 g	9,0 cm
			2,6 l
	<b>MX-Info1-EXT-SV</b>	4047438015035	19,6 cm
	<b>Info Module With LEDs, Silver</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	85414090	15,0 cm
		282 g	9,0 cm
			2,6 l
	<b>MX-Info1-EXT-DG</b>	4047438015028	19,6 cm
	<b>Info Module With LEDs, Dark Gray</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	85414090	15,0 cm
		282 g	9,0 cm
			2,6 l
	<b>MX-Info1-EXT-BL</b>	4047438015011	19,6 cm
	<b>Info Module With LEDs, Black</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	85414090	15,0 cm
		282 g	9,0 cm
			2,6 l





## MX-DoorMaster

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>MX-Door2-INT-ON-PW</b>  <b>DoorMaster For On-Wall Mounting</b>            Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX antitheft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white</p>	<p>4047438021876            85363010            412 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>MX-Door2-INT-PW</b>  <b>DoorMaster For In-Wall Mounting</b>            Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s</p>	<p>4047438019934            85363010            322 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>

## Access Control Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>Mx-A-FrogDisplay</b>  <b>frogblue Display Indoor Station</b>            frogblue Display for MOBOTIX Doorstation T26</p>	<p>4047438041324            85285291            220 g</p>	<p>14,0 cm            13,0 cm            6,0 cm            1,1 l</p>

## Building Automation Accessories





	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-AdminCard1</b> <b>Admin RFID Transponder Card (Red)</b> For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015288 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
	<b>MX-UserCard1</b> <b>User RFID Transponder Card (Blue)</b> For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015295 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
	<b>MX-OPT-IO1</b> <b>Extended Terminal Board (IO Module)</b> Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	4047438013307 85299065 86 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-IO2</b> <b>Ethernet Terminal Board</b> Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	4047438014786 85299065 60 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

## Frames & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-OPT-Box-1-EXT-IN-US</b> <b>Single In-Wall-Housing (USA version)</b>	4047438034463	14,5 cm
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		186 g	3,5 cm
			0,7 l
	<b>Mx-OPT-Box-2-EXT-IN-US</b> <b>Double In-Wall-Housing (USA version)</b>	4047438034470	23,5 cm
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		270 g	3,5 cm
			1,1 l
	<b>Mx-OPT-Box-3-EXT-IN-US</b> <b>Triple In-Wall-Housing (USA version)</b>	4047438034487	33,5 cm
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		362 g	3,5 cm
			1,6 l
	<b>MX-OPT-Frame-1-EXT-PW</b> <b>Single Frame, White</b>	4047438014892	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-SV</b> <b>Single Frame, Silver</b>	4047438014939	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-DG</b> <b>Single Frame, Dark Gray</b>	4047438014922	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-BL</b> <b>Single Frame, Black</b>	4047438014915	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l



	<p><b>MX-OPT-Box-1-EXT-ON-PW</b>  <b>Single On-Wall-Housing, White</b></p> <p>Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015202  90079100  286 g</p>	<p>14,5 cm  13,5 cm  3,5 cm  0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-SV</b>  <b>Single On-Wall-Housing, Silver</b></p> <p>Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015240  90079100  286 g</p>	<p>14,5 cm  13,5 cm  3,5 cm  0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-DG</b>  <b>Single On-Wall-Housing, Dark Gray</b></p> <p>Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015233  90079100  286 g</p>	<p>14,5 cm  13,5 cm  5,0 cm  1,0 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-BL</b>  <b>Single On-Wall-Housing, Black</b></p> <p>Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015226  90079100  286 g</p>	<p>14,5 cm  13,5 cm  3,5 cm  0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-IN</b>  <b>Single In-Wall-Housing</b></p> <p>Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015271  90079100  186 g</p>	<p>14,5 cm  13,5 cm  3,5 cm  0,7 l</p>
	<p><b>MX-OPT-Frame-2-EXT-PW</b>  <b>Double Frame, White</b></p> <p>Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014847  90079100  333 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Frame-2-EXT-SV</b>  <b>Double Frame, Silver</b></p> <p>Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014885  90079100  333 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Frame-2-EXT-DG</b>  <b>Double Frame, Dark Gray</b></p> <p>Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014878  90079100  333 g</p>	<p>23,5 cm  13,5 cm  5,0 cm  1,6 l</p>

	<p><b>MX-OPT-Frame-2-EXT-BL</b>  <b>Double Frame, Black</b>            Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014861            90079100            333 G</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-PW</b>  <b>Double On-Wall-Housing, White</b>            Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015158            90079100            430 G</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-SV</b>  <b>Double On-Wall-Housing, Silver</b>            Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015196            90079100            430 G</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-DG</b>  <b>Double On-Wall-Housing, Dark Gray</b>            Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015189            90079100            430 G</p>	<p>23,5 cm            13,5 cm            3,0 cm            1,0 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-BL</b>  <b>Double On-Wall-Housing, Black</b>            Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015172            90079100            430 G</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-IN</b>  <b>Double In-Wall-Housing</b>            Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015264            90079100            270 G</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Frame-3-EXT-PW</b>  <b>Triple Frame, White</b>            Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014793            90079100            426 G</p>	<p>33,5 cm            13,5 cm            5,5 cm            2,5 l</p>
	<p><b>MX-OPT-Frame-3-EXT-SV</b>  <b>Triple Frame, Silver</b>            Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014830            90079100            426 G</p>	<p>33,5 cm            13,5 cm            5,5 cm            2,5 l</p>

	<p><b>MX-OPT-Frame-3-EXT-DG</b>  <b>Triple Frame, Dark Gray</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014823  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,0 cm  2,3 l</p>
	<p><b>MX-OPT-Frame-3-EXT-BL</b>  <b>Triple Frame, Black</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014816  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,5 cm  2,5 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-PW</b>  <b>Triple On-Wall-Housing, White</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015103  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-SV</b>  <b>Triple On-Wall-Housing, Silver</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015141  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-DG</b>  <b>Triple On-Wall-Housing, Dark Gray</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015134  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,0 cm  1,4 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-BL</b>  <b>Triple On-Wall-Housing, Black</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015127  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-IN</b>  <b>Triple In-Wall-Housing</b></p> <p>Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015257  90079100  362 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-FlatMount-EXT-PW</b>  <b>FlatMount Frame, white</b></p> <p>For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white</p>	<p>4047438019811  90079100  190 g</p>	<p>14,7 cm  13,7 cm  5,5 cm  1,1 l</p>

**MX-OPT-FlatMount-EXT-BL****FlatMount Frame, black**

For flush-mounting of MxDisplay and door station modules in wall cavities •  
Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black

4047438019835	14,7 cm
90079100	13,7 cm
190 g	5,5 cm
	1,1 l

**MX-OPT-FlatMount-Box-EXT-IN****FlatMount Frame In-Wall Housing**

In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or  
brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm

4047438019866	13,8 cm
90079100	6,5 cm
130 g	13,8 cm
	1,2 l

# Software & Services

BeyondHumanVision

MOBOTIX


## MOBOTIX HUB Video Management System

### MOBOTIX HUB

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-HUB-L1-BAS</b> <b>L1 Base License (8 Device Licenses incl)</b> MOBOTIX HUB L1 is available as a free version. The license includes the basic license and device license with the support of up to eight cameras	4047438039208  g	cm cm cm l
	<b>Mx-HUB-L2-BAS</b> <b>MOBOTIX HUB L2 Base License (BL)</b> MOBOTIX HUB L2 for smaller companies with one location manages up to 48 surveillance cameras	4047438038584  g	cm cm cm l
	<b>Mx-HUB-L2-DEV</b> <b>MOBOTIX HUB L2 Device License (DL)</b> Device licenses for MOBOTIX HUB L2. Up to 48 device licenses can be linked to the HUB L2	4047438038591  g	cm cm cm l
	<b>Mx-HUB-L2-1MDEV</b> <b>1 Month Advanced Services for MOBOTIX HUB L2 Device</b> 1 month MOBOTIX HUB L2 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L2 Advanced Service for 1, 2, 3 and 5 years.	4047438039215  g	cm cm cm l
	<b>Mx-HUB-L2-1YDEV</b> <b>One year MOBOTIX HUB Advanced Services for L2 Device</b> 1 Year MOBOTIX HUB L2 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.	4047438038607  g	cm cm cm l
	<b>Mx-HUB-L2-2YDEV</b> <b>Two years MOBOTIX HUB Advanced Services for L2 Device</b> 2 Year MOBOTIX HUB L2 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.	4047438038614  g	cm cm cm l
	<b>Mx-HUB-L2-3YDEV</b> <b>Three years MOBOTIX HUB Advanced Services for L2 Device</b> 3 Year MOBOTIX HUB L2 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.	4047438038621  g	cm cm cm l

	<p><b>Mx-HUB-L2-5YDEV</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L2 Device</b></p> <p>5 Year MOBOTIX HUB L2 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038638	cm cm g cm l
	<p><b>Mx-HUB-L2-3YOPT-DEV</b></p> <p><b>Three years opt-in MOBOTIX HUB Advanced Services for L2</b></p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L2 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L2 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039031	cm cm g cm l
	<p><b>Mx-HUB-L2-UP-BASWO</b></p> <p><b>Version Upgrade HUB L2 BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L2 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039277	cm cm g cm l
	<p><b>Mx-HUB-L2-UP-DEVWO</b></p> <p><b>Version Upgrade HUB L2 DL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L2 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039284	cm cm g cm l
	<p><b>Mx-HUB-L3-BAS</b></p> <p><b>MOBOTIX HUB L3 Base License (BL)</b></p> <p>MOBOTIX HUB L3 is the solution for medium-sized companies. The number of cameras is unlimited and can be distributed across multiple locations.</p>	4047438038645	cm cm g cm l
	<p><b>Mx-HUB-L3-DEV</b></p> <p><b>MOBOTIX HUB L3 Device License (DL)</b></p> <p>Device licenses for MOBOTIX HUB L3. Unlimited number of devices can be integrated into one L3 installation.</p>	4047438038652	cm cm g cm l
	<p><b>Mx-HUB-L3-1MDEV</b></p> <p><b>1 Month Advanced Services for MOBOTIX HUB L3 Device</b></p> <p>1 month MOBOTIX HUB L3 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L3 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039222	cm cm g cm l
	<p><b>Mx-HUB-L3-1YDEV</b></p> <p><b>One year MOBOTIX HUB Advanced Services for L3 Device</b></p> <p>1 Year MOBOTIX HUB L3 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038669	cm cm g cm l









	<p><b>Mx-HUB-L3-2YDEV</b></p> <p><b>Two years MOBOTIX HUB Advanced Services for L3 Device</b></p> <p>2 Year MOBOTIX HUB L3 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038676	cm cm cm l
	<p><b>Mx-HUB-L3-3YDEV</b></p> <p><b>Three years MOBOTIX HUB Advanced Services for L3 Device</b></p> <p>3 Year MOBOTIX HUB L3 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038683	cm cm cm l
	<p><b>Mx-HUB-L3-5YDEV</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L3 Device</b></p> <p>5 Year MOBOTIX HUB L3 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038690	cm cm cm l
	<p><b>Mx-HUB-L3-3YOPT-DEV</b></p> <p><b>Three years opt-in MOBOTIX HUB Advanced Services for L3</b></p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L3 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L3 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039048	cm cm cm l
	<p><b>Mx-HUB-TRAD-BAS-L2-L3-W</b></p> <p><b>Trade-in BL L2-&gt;L3 w/ ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).</p>	4047438039369	cm cm cm l
	<p><b>Mx-HUB-TRAD-DEV-L2-L3-W</b></p> <p><b>Trade-in DL L2-&gt;L3 w/ ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).</p>	4047438039376	cm cm cm l
	<p><b>Mx-HUB-TRAD-BAS-L2-L3-WO</b></p> <p><b>Trade-in BL L2-&gt;L3 w/o ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039383	cm cm cm l
	<p><b>Mx-HUB-TRAD-DEV-L2-L3-WO</b></p> <p><b>Trade-in DL L2-&gt;L3 w/o ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039390	cm cm cm l








	<p><b>Mx-HUB-L3-UP-BASWO</b></p> <p><b>Version Upgrade HUB L3 BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L3 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039291	cm cm g cm l
	<p><b>Mx-HUB-L3-UP-DEWVO</b></p> <p><b>Version Upgrade HUB L3 DL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L3 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039307	cm cm g cm l
	<p><b>Mx-HUB-L4-BAS</b></p> <p><b>MOBOTIX HUB L4 Base License (BL)</b></p> <p>MOBOTIX HUB L4 is made for medium and large installations. In addition to the features of MOBOTIX HUB L3, L4 provides access to failover recording servers in case of server failure. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038706	cm cm g cm l
	<p><b>Mx-HUB-L4-DEV</b></p> <p><b>MOBOTIX HUB L4 Device License (DL)</b></p> <p>Device licenses for MOBOTIX HUB L4. Unlimited number of devices can be integrated into one L4 installation. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038713	cm cm g cm l
	<p><b>Mx-HUB-L4-1MBAS</b></p> <p><b>1 Month Advanced Services for MOBOTIX HUB L4 Base</b></p> <p>1 month MOBOTIX HUB L4 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039239	cm cm g cm l
	<p><b>Mx-HUB-L4-1YBAS</b></p> <p><b>One year MOBOTIX HUB Advanced Services for L4 Base</b></p> <p>1 year MOBOTIX HUB L4 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038720	cm cm g cm l
	<p><b>Mx-HUB-L4-2YBAS</b></p> <p><b>Two years MOBOTIX HUB Advanced Services for L4 Base</b></p> <p>2 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038737	cm cm g cm l
	<p><b>Mx-HUB-L4-3YBAS</b></p> <p><b>Three years MOBOTIX HUB Advanced Services for L4 Base</b></p> <p>3 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038744	cm cm g cm l

	<p><b>Mx-HUB-L4-5YBAS</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L4 Base</b></p> <p>5-year MOBOTIX HUB L4 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038751	cm cm g cm l
	<p><b>Mx-HUB-L4-3YOPT-BAS</b></p> <p><b>Three years opt-in MOBOTIX HUB Advanced Services for L4</b></p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L4 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039055	cm cm g cm l
	<p><b>Mx-HUB-L4-1MDEV</b></p> <p><b>1 Month Advanced Services for MOBOTIX HUB L4 Device</b></p> <p>1 month MOBOTIX HUB L4 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039246	cm cm g cm l
	<p><b>Mx-HUB-L4-1YDEV</b></p> <p><b>One year MOBOTIX HUB Advanced Services for L4 Device</b></p> <p>1 year MOBOTIX HUB L4 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038768	cm cm g cm l
	<p><b>Mx-HUB-L4-2YDEV</b></p> <p><b>Two years MOBOTIX HUB Advanced Services for L4 Device</b></p> <p>2 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038775	cm cm g cm l
	<p><b>Mx-HUB-L4-3YDEV</b></p> <p><b>Three years MOBOTIX HUB Advanced Services for L4 Device</b></p> <p>3 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038782	cm cm g cm l
	<p><b>Mx-HUB-L4-5YDEV</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L4 Device</b></p> <p>5-year MOBOTIX HUB L4 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038799	cm cm g cm l
	<p><b>Mx-HUB-L4-3YOPT-DEV</b></p> <p><b>Three years opt-in MOBOTIX HUB Advanced Services for L4</b></p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L4 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039062	cm cm g cm l







	<p><b>Mx-HUB-TRAD-BAS-L2-L4-W</b></p> <p><b>Trade-in BL L2-&gt;L4 w/ ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039406	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L2-L4-W</b></p> <p><b>Trade-in DL L2-&gt;L4 w/ ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039413	cm cm g cm l
	<p><b>Mx-HUB-TRAD-BAS-L2-L4-WO</b></p> <p><b>Trade-in BL L2-&gt;L4 w/o ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039420	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L2-L4-WO</b></p> <p><b>Trade-in DL L2-&gt;L4 w/o ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039437	cm cm g cm l
	<p><b>Mx-HUB-TRAD-BAS-L3-L4-W</b></p> <p><b>Trade-in BL L3-&gt;L4 w/ ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039444	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L3-L4-W</b></p> <p><b>Trade-in DL L3-&gt;L4 w/ ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039451	cm cm g cm l
	<p><b>Mx-HUB-TRAD-BAS-L3-L4-WO</b></p> <p><b>Trade-in BL L3-&gt;L4 w/o ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039468	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L3-L4-WO</b></p> <p><b>Trade-in DL L3-&gt;L4 w/o ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039475	cm cm g cm l








	<p><b>Mx-HUB-L4-UP-BASWO</b></p> <p><b>Version Upgrade HUB L4 BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L4 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039314	cm cm g cm l
	<p><b>Mx-HUB-L4-UP-DEWVO</b></p> <p><b>Version Upgrade HUB L4 DL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L4 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039321	cm cm g cm l
	<p><b>Mx-HUB-L5-BAS</b></p> <p><b>MOBOTIX HUB L5 Base License (BL)</b></p> <p>MOBOTIX HUB L5 is the video management platform for large and extremely security-oriented applications. In addition to centralized management of all servers, cameras and users across multiple sites, L5 also includes control for a professional video wall as standard. The use of MOBOTIX HUB L5 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038805	cm cm g cm l
	<p><b>Mx-HUB-L5-DEV</b></p> <p><b>MOBOTIX HUB L5 Device License (DL)</b></p> <p>Device licenses for MOBOTIX HUB L5. Unlimited number of devices can be integrated into one L5 installation.</p>	4047438038812	cm cm g cm l
	<p><b>Mx-HUB-L5-INTCON</b></p> <p><b>MOBOTIX HUB Interconnect Device License (DL)</b></p> <p>Interconnect licenses for MOBOTIX HUB L5. Unlimited number of Interconnect licenses can be used into one L5 installation.</p>	4047438038829	cm cm g cm l
	<p><b>Mx-HUB-L5-1MBAS</b></p> <p><b>1 Month Advanced Services for MOBOTIX HUB L5 Base</b></p> <p>1 month MOBOTIX HUB L5 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039253	cm cm g cm l
	<p><b>Mx-HUB-L5-1YBAS</b></p> <p><b>One year MOBOTIX HUB Advanced Services for L5 Base</b></p> <p>1 year MOBOTIX HUB L5 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038836	cm cm g cm l
	<p><b>Mx-HUB-L5-2YBAS</b></p> <p><b>Two years MOBOTIX HUB Advanced Services for L5 Base</b></p> <p>2 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038843	cm cm g cm l

	<p><b>Mx-HUB-L5-3YBAS</b></p> <p><b>Three years MOBOTIX HUB Advanced Services for L5 Base</b></p> <p>3 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038850	cm cm cm l
	<p><b>Mx-HUB-L5-5YBAS</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L5 Base</b></p> <p>5-year MOBOTIX HUB L5 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038867	cm cm cm l
	<p><b>Mx-HUB-L5-3YOPT-BAS</b></p> <p><b>Three years opt-in MOBOTIX HUB Advanced Services for L5</b></p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L5 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039079	cm cm cm l
	<p><b>Mx-HUB-L5-1MDEV</b></p> <p><b>1 Month Advanced Services for MOBOTIX HUB L5 Device</b></p> <p>1 month MOBOTIX HUB L5 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039260	cm cm cm l
	<p><b>Mx-HUB-L5-1YDEV</b></p> <p><b>One year MOBOTIX HUB Advanced Services for L5 Device</b></p> <p>1 year MOBOTIX HUB L5 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038874	cm cm cm l
	<p><b>Mx-HUB-L5-2YDEV</b></p> <p><b>Two years MOBOTIX HUB Advanced Services for L5 Device</b></p> <p>2 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038881	cm cm cm l
	<p><b>Mx-HUB-L5-3YDEV</b></p> <p><b>Three years MOBOTIX HUB Advanced Services for L5 Device</b></p> <p>3 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038898	cm cm cm l
	<p><b>Mx-HUB-L5-5YDEV</b></p> <p><b>Five years MOBOTIX HUB Advanced Services for L5 Device</b></p> <p>5-year MOBOTIX HUB L5 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038904	cm cm cm l

	<b>Mx-HUB-L5-3YOPT-DEV</b> <b>Three years opt-in MOBOTIX HUB Advanced Services for L5</b> The MOBOTIX HUB Advanced Service Opt-in for HUB L5 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.	4047438039086	cm cm cm l
	<b>Mx-HUB-TRAD-BAS-L2-L5-W</b> <b>Trade-in BL L2-&gt;L5 w/ ASP</b> Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).	4047438039482	cm cm cm l
	<b>Mx-HUB-TRAD-DEV-L2-L5-W</b> <b>Trade-in DL L2-&gt;L5 w/ ASP</b> Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).	4047438039499	cm cm cm l
	<b>Mx-HUB-TRAD-BAS-L2-L5-WO</b> <b>Trade-in BL L2-&gt;L5 w/o ASP</b> Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).	4047438039505	cm cm cm l
	<b>Mx-HUB-TRAD-DEV-L2-L5-WO</b> <b>Trade-in DL L2-&gt;L5 w/o ASP</b> Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).	4047438039512	cm cm cm l
	<b>Mx-HUB-TRAD-BAS-L3-L5-W</b> <b>Trade-in BL L3-&gt;L5 w/ ASP</b> Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).	4047438039529	cm cm cm l
	<b>Mx-HUB-TRAD-DEV-L3-L5-W</b> <b>Trade-in DL L3-&gt;L5 w/ ASP</b> Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).	4047438039536	cm cm cm l
	<b>Mx-HUB-TRAD-BAS-L3-L5-WO</b> <b>Trade-in BL L3-&gt;L5 w/o ASP</b> Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).	4047438039543	cm cm cm l



	<p><b>Mx-HUB-TRAD-DEV-L3-L5-WO</b></p> <p><b>Trade-in DL L3-&gt;L5 w/o ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039550	cm cm g cm l
	<p><b>Mx-HUB-TRAD-BAS-L4-L5-W</b></p> <p><b>Trade-in BL L4-&gt;L5 w/ ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).</p>	4047438039567	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L4-L5-W</b></p> <p><b>Trade-in DL L4-&gt;L5 w/ ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).</p>	4047438039574	cm cm g cm l
	<p><b>Mx-HUB-TRAD-BAS-L4-L5-WO</b></p> <p><b>Trade-in BL L4-&gt;L5 w/o ASP</b></p> <p>Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039581	cm cm g cm l
	<p><b>Mx-HUB-TRAD-DEV-L4-L5-WO</b></p> <p><b>Trade-in DL L4-&gt;L5 w/o ASP</b></p> <p>Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039598	cm cm g cm l
	<p><b>Mx-HUB-L5-UP-BASWO</b></p> <p><b>Version Upgrade HUB L5 BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L5 base licenses that are not in possession of an Advanced Service Product</p>	4047438039338	cm cm g cm l
	<p><b>Mx-HUB-L5-UP-DEVWO</b></p> <p><b>Version Upgrade HUB L5 DL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L5 device licenses that are not in possession of an Advanced Service Product</p>	4047438039345	cm cm g cm l
	<p><b>Mx-HUB-L5-UP-INTWO</b></p> <p><b>Version Upgrade HUB L5 Intercon. DL w/o ASP</b></p> <p>Software update for MOBOTIX HUB L5 interconnect licenses that are not in possession of an Advanced Service Product</p>	4047438039352	cm cm g cm l

	<p><b>Mx-HUB-ACC-WALL</b></p> <p><b>MOBOTIX HUB Video Wall Base License (BL)</b></p> <p>MOBOTIX HUB Video Wall is an advanced add-on video wall product that improves response time by displaying all the video data in your installation and giving a complete overview of large surveillance centers.</p>	4047438039116	cm
		g	cm cm l
	<p><b>Mx-HUB-ACC-WALL-UP</b></p> <p><b>Version Upgrade HUB Video Wall BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB Video Wall license that are not in possession of an Advanced Service Product</p>	4047438039604	cm
		g	cm cm l
	<p><b>Mx-HUB-ACS-BASE</b></p> <p><b>MOBOTIX HUB Access Base License (BL)</b></p> <p>MOBOTIX HUB Access is an Add-on product that video enables physical security through integration of access control and intrusion systems</p>	4047438039178	cm
		g	cm cm l
	<p><b>Mx-HUB-ACS-BASE-UP</b></p> <p><b>Version Upgrade HUB Access BL w/o ASP</b></p> <p>Software update for MOBOTIX HUB Access Basic license, which are not in possession of an Advanced Service product.</p>	4047438039611	cm
		g	cm cm l
	<p><b>Mx-HUB-ACS-DOOR</b></p> <p><b>MOBOTIX HUB Access Door License (DL)</b></p> <p>Device license for MOBOTIX HUB Access.</p>	4047438039185	cm
		g	cm cm l
	<p><b>Mx-HUB-ACS-DOOR-UP</b></p> <p><b>Version Upgrade HUB Access DL w/o ASP</b></p> <p>Software Update for MOBOTIX HUB Access Devices License, which are not in possession of an Advanced Service Product.</p>	4047438039628	cm
		g	cm cm l
	<p><b>Mx-HUB-XP-TRA-BAS</b></p> <p><b>Xprotect Transaction Base License Server incl. 1 Connection</b></p> <p>XProtect Transact Base Server incl. 1 Connection License. XProtect Transact video enables different types of transaction-based processes. Combining transaction data from point of sales systems, scanners, cash point machines, or similar systems with corresponding video, XProtect Transact enables real-time monitoring, exception handling and documentation of transactions.</p>	4047438039154	cm
		g	cm cm l
	<p><b>Mx-HUB-XP-TRA-BAS-UP</b></p> <p><b>Version Upgrade Xprotect Transaction BL w/o ASP</b></p> <p>Software Update for XProtect Transaction Base License, which are not in possession of an Advanced Service Product.</p>	4047438039635	cm
		g	cm cm l

	<b>Mx-HUB-XP-TRA-CON</b> <b>Xprotect Transaction Connection License</b> Connection licence for Xprotect Transact.	4047438039161	cm
		g	cm l
	<b>Mx-HUB-XP-TRA-CON-UP</b> <b>Version Upgrade Xprotect Transaction CL w/o ASP</b> Software update for XProtect Transaction Connection license, which are not in possession of an Advanced Service Product	4047438039642	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-BAS</b> <b>Xprotect LPR Base License incl. 5 Country Modules</b> XProtect LPR Base License, incl. 5 Country Modules. XProtect LPR is license plate recognition (LPR) software that detects license plate information from any vehicle around the world and links the license plate number with video.	4047438039123	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-BAS-UP</b> <b>Version Upgrade Xprotect LPR BL w/o ASP</b> Software update for XProtect LPR Basic license, which are not in possession of an Advanced Service Product.	4047438039659	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-DEV</b> <b>XProtect LPR Device License (DL)</b> Device licence for Xprotect LPR.	4047438039130	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-DEV-UP</b> <b>Version Upgrade Xprotect LPR DL w/o ASP</b> Software update for XProtect LPR devices license, which are not in possession of an Advanced Service Product.	4047438039666	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-CTY</b> <b>Xprotect LPR Country Modul</b> Country modul for Xprotect LPR.	4047438039147	cm
		g	cm l
	<b>Mx-HUB-XP-LPR-CTY-UP</b> <b>Version Upgrade Xprotect LPR CM w/o ASP</b> Software update for XProtect LPR Country Module not in possession of an Advanced Service Product.	4047438039673	cm
		g	cm l





## MxManagementCenter and Additional Licences

### ONVIF-compliant Video Management System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras or storage media. It was designed to be user-friendly, high-performing and secure.

Please follow this link for further license-related informations: <https://www.mobotix.com/de/support/download-center/software-downloads/lizenz-portal>

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-SW-MC-ADCON-VM</b> <b>MxMC Advanced Config License for virtual machines (VM)</b> Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required) • released for virtual machines (VM)	4047438035071	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC</b> <b>MxManagementCenter VMS For Windows/macOS</b> Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Versions 2.2 for Windows (Windows 8 or later) or macOS (10.12 or higher) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support > Download Center > Software Downloads > Cameras > MxManagementCenter	4047438034456	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-ADCON</b> <b>MxMC Advanced Config License</b> Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034197	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-STARTER</b> <b>MxMC Integration Starter License</b> MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	4047438034142	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-CHAN</b> <b>MxMC Integration Channel License</b> MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034159	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-SDATA</b> <b>MxMC Smart Data License</b> MOBOTIX license for connecting an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034449	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l

	<p><b>Mx-SW-MC-POS</b></p> <p><b>MxMC POS Single Cash Point License</b></p> <p>MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438031615</p> <p>0 9</p>	<p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 l</p>
	<p><b>Mx-SW-MC-AS-1</b></p> <p><b>MxMC Advanced Service License, 1 Year</b></p> <p>MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034166</p> <p>0 9</p>	<p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 l</p>
	<p><b>Mx-SW-MC-AS-2</b></p> <p><b>MxMC Advanced Service License, 2 Years</b></p> <p>MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034173</p> <p>0 9</p>	<p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 l</p>
	<p><b>Mx-SW-MC-AS-5</b></p> <p><b>MxMC Advanced Service License, 5 Years</b></p> <p>MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034180</p> <p>0 9</p>	<p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 cm</p> <p>0,0 l</p>

## Certified Apps for MOBOTIX 7









### Certified Apps for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-APP-AI-B-FIR</b> <b>Bundle of A.I. Tech Fire &amp; Smoke Apps</b> Bundle of A.I. Tech Fire & Smoke Apps: AI-FIRE + AI-SMOKE	4047438035279 g	cm cm cm l
	<b>Mx-APP-AI-B-RET</b> <b>Bundle of A.I. Tech Retail Apps</b> Bundle of A.I. Tech Retail Apps: AI-PEOPLE, AI-HEAT, AI-OCCUPANCY, AI-OVEROCCUPANCY, AI-CROWD and AI-OVERCROWD	4047438035262 g	cm cm cm l
	<b>Mx-APP-AI-B-SEC</b> <b>Bundle of A.I. Tech Security Apps</b> Bundle of A.I. Tech Security Apps: AI-INTRUSION-PRO + AI-LOITERING + AI-LOST	4047438035248 g	cm cm cm l
	<b>Mx-APP-AI-B-TRA</b> <b>Bundle of A.I. Tech Traffic Apps</b> Bundle of A.I. Tech Traffic Apps: AI-ROAD3D and AI-INCIDENT	4047438035255 g	cm cm cm l
	<b>Mx-APP-AI-BIO</b> <b>AI-Bio Certified App</b> Biometric analysis of gender, age and length of stay of customers/visitors as a basis for customer and stock management in the retail sector.	4047438035132 g	cm cm cm l
	<b>Mx-APP-AI-CRO</b> <b>AI-Crowd Certified App</b> Appraises the number of people in busy areas, recognizes queue situations, among other things.	4047438035118 g	cm cm cm l
	<b>Mx-APP-AI-CRO-D</b> <b>AI-Crowd Deep Certified App</b> Estimation of number of people within a monitored area (indoor / outdoor) • Identification of overcrowded areas based on a defined threshold • Real-time monitoring of Social Distance • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface	4047438037334 g	cm cm cm l

	<p><b>Mx-APP-AI-CROP</b>  <b>AI-Crowd Plus Certified App</b>  A.I. Tech Crowd / Overcrowd bundle including the following features: • Estimation of number of people within a monitored area (indoor / outdoor) • Identification of overcrowded areas based on a defined threshold • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface</p>	<p>4047438037341  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-FD-D</b>  <b>AI-Facedetect Deep Certified App</b>  A.I. Tech Face Detection App including the following features: • Detection of faces within the live stream • People counting based on face detection • Detection of persons wearing masks / not wearing masks (e.g. mouth-nose-protection) • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface</p>	<p>4047438037327  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-FIRE</b>  <b>AI-Fire Certified App</b>  Early detection of flames indoors and outdoors (e.g., vehicles, containers). No thermal sensor required.</p>	<p>4047438035187  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-HEA</b>  <b>AI-Heat Certified App</b>  Classifies most visited areas (hot spots) and the less crowded ones (dead areas) depending on the time spent by people inside.</p>	<p>4047438035293  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-INC</b>  <b>AI-Incident Certified App</b>  Traffic monitoring: Presence of pedestrians, vehicles stopping, queues or vehicles in the wrong direction.</p>	<p>4047438035224  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-INTP</b>  <b>AI-Intrusion-PRO Certified App</b>  Shows intruders crossing a sequence of virtual lines. Setting multiple lines increases the reliability of anti-intrusion systems.</p>	<p>4047438035156  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-LOI</b>  <b>AI-Loitering Certified App</b>  Detects suspicious behaviour of people who stay in certain areas for a longer period of time.</p>	<p>4047438035170  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-APP-AI-LOS</b>  <b>AI-Lost Certified App</b>  Detects stray luggage and other objects (e.g. garbage) as well as the removal of objects (e.g. paintings in museums).</p>	<p>4047438035163  g</p>	<p>cm cm cm l</p>

	<b>Mx-APP-AI-OCC</b> <b>AI-Occupancy Certified App</b>	4047438035095	cm
	Detects „Hot Spots“ and „Dead Areas“ in defined areas.	g	cm l
	<b>Mx-APP-AI-OVER</b> <b>AI-Overcrowd Certified App</b>	4047438035125	cm
	Identifies crowded areas based on user-defined thresholds (number of people).	g	cm l
	<b>Mx-APP-AI-OVERO</b> <b>AI-Overoccupancy Certified App</b>	4047438035101	cm
	Identifies the occupancy rate in defined areas and detects overoccupied zones.	g	cm l
	<b>Mx-APP-AI-PAR-D</b> <b>AI-Parking Certified App</b>	4047438035231	cm
	Classification of vehicles. Detects whether and how many parking spaces are free or occupied.	g	cm l
	<b>Mx-APP-AI-PEO</b> <b>AI-People Certified App</b>	4047438035088	cm
	Counts people crossing a virtual line (e.g. door/corridor) in a certain direction.	g	cm l
	<b>Mx-APP-AI-ROA3</b> <b>AI-Road3D Certified App</b>	4047438035217	cm
	Traffic monitoring: Detection, tracking and counting of vehicles (behavior, traffic density, type [trucks, cars, cycles]). Identifies vehicles that are too fast.	g	cm l
	<b>Mx-APP-AI-SMO</b> <b>AI-Smoke Certified App</b>	4047438035194	cm
	Smoke detection inside and outside. No thermal sensor required.	g	cm l
	<b>Mx-APP-AI-SPI</b> <b>AI-Spill Certified App</b>	4047438035200	cm
	Detects situations when people fall and remain on the ground.	g	cm l








	<p><b>Mx-APP-FF-LPR-AM</b></p> <p><b>FF Group License Plate Recognition App Region Americas</b></p> <p>FF Group License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition of latin characters optimized for American license plates • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem</p>	<p>4047438037822</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-FF-LPR-EUCA</b></p> <p><b>FF Group License Plate Recognition App Region EUCA</b></p> <p>FF Group License Plate Recognition App including the following features: License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Country coverage: ALB, AUT, BEL, BIH, BGR, HRV, CYP, CZE, DNK, EST, FIN, FRA, DEU, GRC, HUN, ISL, ITA, IRL, ISR, LVA, LTU, LUX, MKD, MLT, MNE, NLD, NOR, POL, PRT, ROU, SRB, SVK, SVN, ESP, SWE, CHE, TUR, GBR, VAT, ARM, AZE, BLR, GEO, KAZ, KGZ, MDA, RUS, TJK, TKM, UKR, UZB, AUS, NZL</p>	<p>4047438036474</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-FF-LPR-ME</b></p> <p><b>FF Group License Plate Recognition App Region Middle East</b></p> <p>FF Group License Plate Recognition App including the following features: • Recognition of one- and two-line license plates • simultaneous recognition on one or more image sensors • Recognition of Latin and Arabic characters • Multiple license plate lists for individual actions (e.g. access granted, alarm, etc.) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface • meta data transfer through generic transmission protocols</p>	<p>4047438040686</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-FF-MMCR-EUCA</b></p> <p><b>FF Group App License Plate, Make, Model and Color</b></p> <p>FF Group MMCR App including the following features: • Recognition of one- and two-line license plates • Recognition of Latin and Hebrew characters • Additional recognition of vehicle brand, model, color and type • Multifactor events (e.g. license plate and vehicle brand match) • Recognition protocol (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem</p>	<p>4047438037839</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-IRIS-C-INT</b></p> <p><b>Irisity Iris Core Intrusion App</b></p> <p>Irisity Iris Core Intrusion App including the following features: • Detects the intrusion of objects of interest into user-defined detection zones / areas • Designed for reliable detection of people and vehicles covering only small portions of the field of view • Reduction of false alarms to a minimum by filtering out non-critical motion (e.g. trees, clouds, etc.) • simultaneous detection on one or more image sensors • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB</p>	<p>4047438040693</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VIS-FR-1</b></p> <p><b>Visage Technologies Face Recognition. 1 Year license</b></p> <p>Facial recognition by means of deposited image data. With 97% accuracy for access control applications. 1 year license.</p>	<p>4047438035286</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VIS-FR-2</b></p> <p><b>Visage Technologies Face Recognition. 2 Years license</b></p> <p>Facial recognition by means of deposited image data. With 97% accuracy for access control applications. 2 year license.</p>	<p>4047438035309</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-ADR</b></p> <p><b>Vaxtor App License Plate and Dangerous Goods Recognition</b></p> <p>Vaxtor App for License Plate and Dangerous Goods Recognition including the following features: • License plate recognition of one- and two-line license plates • read conventional and dangerous good plates simultaneously • support of latin, hebrew and arabic characters for global application • recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and trigger mode for LPR/ADR</p>	<p>4047438037815</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>


	<p><b>Mx-APP-VX-AIN</b></p> <p><b>Vaxtor Aircraft Identification Number Recognition App</b></p> <p>Vaxtor Aircraft Identification Number Recognition App including the following features: • Recognition of ICAO- and FAA-issued identification numbers • Operations up to a speed of 50 km/h • Real-time results: Aircraft ID, Aircraft Type, Country, etc. • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.)</p>	<p>4047438040518</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-CON</b></p> <p><b>Vaxtor App for Cargo Container Code Recognition</b></p> <p>Vaxtor App for Container Code Recognition including the following features: • Recognition of cargo container codes according to ISO 6346 • Real time results: • Container Code • Property Code • Owner • Container Type • Container Dimensions • Control Digit • Control Digit Validation • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	<p>4047438037938</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-LPR</b></p> <p><b>Vaxtor License Plate Recognition App</b></p> <p>Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Global country coverage</p>	<p>4047438037358</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-LPR-M</b></p> <p><b>Vaxtor License Plate Recognition App (multi-lens)</b></p> <p>Vaxtor License Plate Recognition App (multi-lens application) including the following features: • License plate recognition of one- and two-line license plates • simultaneous recognition on one or more image sensors • monitoring the dwell time of license plates in the detection area • support of latin, hebrew and arabic characters for global application • Recognition log • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	<p>4047438040402</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-MMC</b></p> <p><b>Vaxtor License Plate Recognition App incl. Vehicle Make,</b></p> <p>Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • support of latin, hebrew and arabic characters for global application • Additional recognition of vehicle make, model, color and class • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	<p>4047438038324</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-APP-VX-UIC</b></p> <p><b>Vaxtor App for UIC Railway Code Recognition</b></p> <p>Vaxtor App for UIC Railway Code Recognition including the following features: • Recognition of the International Union of Railways Wagon and Coach numbers (UIC Codes) • Real time results: UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel • Stop / Go and slow speed (&lt;10 km/h) applications (depending on installation and module selection) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	<p>4047438040266</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>

## Warranty Extensions

### Warranty Extensions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-WE-DTVS-1</b> <b>1 Year Warranty Extension For Dual Thermal Systems S74</b> 3+1 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031974 g	cm cm cm l
	<b>Mx-WE-DTVS-2</b> <b>2 Years Warranty Extension For Dual Thermal Systems S74</b> 3+2 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031981 g	cm cm cm l
	<b>Mx-WE-DTVS-3</b> <b>3 Years Warranty Extension For Dual Thermal Systems S74</b> 3+3 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031998 g	cm cm cm l
	<b>Mx-WE-DTVS-4</b> <b>4 Years Warranty Extension For Dual Thermal Systems S74</b> 3+4 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438032001 g	cm cm cm l
	<b>Mx-WE-DTVS-5</b> <b>5 Years Warranty Extension For Dual Thermal Systems S74</b> 3+5 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438032018 g	cm cm cm l
	<b>Mx-WE-IVS-1</b> <b>1 Year Warranty Extension For Indoor Video Systems</b> 3+1 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031820 g	cm cm cm l
	<b>Mx-WE-IVS-2</b> <b>2 Years Warranty Extension For Indoor Video Systems</b> 3+2 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031837 g	cm cm cm l

	<p><b>Mx-WE-IVS-3</b>  <b>3 Years Warranty Extension For Indoor Video Systems</b>            3+3 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031844	cm cm cm l
	<p><b>Mx-WE-IVS-4</b>  <b>4 Years Warranty Extension For Indoor Video Systems</b>            3+4 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031851	cm cm cm l
	<p><b>Mx-WE-IVS-5</b>  <b>5 Years Warranty Extension For Indoor Video Systems</b>            3+5 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031868	cm cm cm l
	<p><b>Mx-WE-OVS-1</b>  <b>1 Year Warranty Extension For Outdoor Video Systems</b>            3+1 Year Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031875	cm cm cm l
	<p><b>Mx-WE-OVS-2</b>  <b>2 Years Warranty Extension For Outdoor Video Systems</b>            3+2 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031882	cm cm cm l
	<p><b>Mx-WE-OVS-3</b>  <b>3 Years Warranty Extension For Outdoor Video Systems</b>            3+3 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031899	cm cm cm l
	<p><b>Mx-WE-OVS-4</b>  <b>4 Years Warranty Extension For Outdoor Video Systems</b>            3+4 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031905	cm cm cm l
	<p><b>Mx-WE-OVS-5</b>  <b>5 Years Warranty Extension For Outdoor Video Systems</b>            3+5 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	4047438031912	cm cm cm l

	<p><b>Mx-WE-STVS-1</b></p> <p><b>1 Year Warranty Extension For Single Thermal Systems</b></p> <p>3+1 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031929</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-WE-STVS-2</b></p> <p><b>2 Years Warranty Extension For Single Thermal Systems</b></p> <p>3+2 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031936</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-WE-STVS-3</b></p> <p><b>3 Years Warranty Extension For Single Thermal Systems</b></p> <p>3+3 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031943</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-WE-STVS-4</b></p> <p><b>4 Years Warranty Extension For Single Thermal Systems</b></p> <p>3+4 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031950</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p><b>Mx-WE-STVS-5</b></p> <p><b>5 Years Warranty Extension For Single Thermal Systems</b></p> <p>3+5 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031967</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>