

Share:



## Rack PDU 2G, Metered, ZeroU, 32A, 230V, (36) C13 & (6) C19

AP8853



Description: APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Includes : Installation guide , Rack Mounting brackets , Safety guide , Serial configuration cable

Product Overview

**Technical Specifications**

Documentation

Options

### Output

[Print Technical Specification](#)


Overload Protection	Yes
Maximum Total Current Draw	32
Output Connections	(36) IEC 320 C13 (Battery Backup) (6) IEC 320 C19 (Battery Backup)

### Input

Nominal Input Voltage	200V , 208V , 230V
Input frequency	50/60 Hz
Input Connections	IEC 309 32A 2P+E
Cord Length	3meters
Acceptable Input Voltage	220-240VAC
Number of Power Cords	1
Maximum Input Current	32A
Maximum Line Current	32A

### Physical

Maximum Height	1791mm , 179.1cm
Maximum Width	56mm , 5.6cm
Maximum Depth	44mm , 4.4cm
Net Weight	6.93kg
Shipping weight	8.56kg
Shipping Height	2000mm , 200.0cm
Shipping Width	162mm , 16.2cm
Shipping Depth	107mm , 10.7cm
Color	Black
Units per Pallet	48.0

### Environmental

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000meters

### Conformance

Approvals	IEC 60950, VDE
Standard warranty	2 years repair or replace
<b>Sustainable Offer Status</b>	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	ts_Battery_Notes

Sign up to stay up to date with best practices, new solutions and special offers.



Email

OK



CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric