

PROXIMITY Reader - KP75, MIFARE®

System specifications

| | | |
|---------------------------------|----------------------------|--|
| Cable Length | 5m/16ft | |
| Cable extension length and type | ≤ 25m/82ft ≤ 100m/328ft | Belden 9538/ Belden 5506FE (USA) Belden 9540/ Belden 5306FE (USA) |

| | |
|---------------------|---------|
| Token compatibility | MIFARE® |
| Cover material | Metal |

| | |
|----------------------|----|
| Handsfree compatible | No |
|----------------------|----|

Electrical

| | |
|---------------------|---------------|
| Operating Voltage | 12V DC |
| Current consumption | 180mA - 200mA |

Environment

| | |
|-----------------------|---------------------------------|
| Operating temperature | -35°C - +66°C -31°F - +151°F |
| Safe use temperature | -35°C - +50°C -31°F - +122°F |
| Moisture resistance | IPX7 |
| Vandal Resistance | Medium |



The KP75 MIFARE® keypad reader is a RFID/Keypad combinations device that offers the convenience of contactless authentication, or the added security of PIN/Prox entry, for system users.

They are available for use with Net2 systems.

The readers are supplied with a metal bezel.


The reader is wired as shown on the control unit label.

A token is read by holding it within close proximity of the reader.

Once a token has been read the control unit looks up the access permissions of that user. The control unit verifies the information and grants or denies access as appropriate.

By default, all 3 LEDs are lit. If access is granted, the green LED flashes. If access is denied, the red LED flashes.

KP75



Accessories and sales codes

PROXIMITY metal Keypad - KP75, MIFARE® 375-130

