

Tetherbox

5

Specification Sheet

Tether

Tetherbox 5 Specifications

- Easy and fast access to footage from any where
- Notifications in case of system health issues
- Easy back up of recordings to cloud*



Cameras	up to: 5 high definition or 10 standard definition
Dimension	56.1 mm x 107.6 mm x 114.4 mm (2.21" x 4.24" x 4.5")
CPU	Intel® Processor Quad Core
Memory	2 GB DDR3L
Hard Drive	0.5TB SSD 2.5" (possible to add external storage)
LAN	Gigabit LAN (Realtek RTL8111G)
Front I/O	1 x USB 3.0
Rear I/O	1 x HDMI (for diagnostics/testing only) 2 x USB 2.0 1 x RJ45 1 x DC-In 1 x Kensington lock slot
Side I/O	Input: AC 100-240V Output: DC 12V 2.5A
Power Supply	Input: AC 100-240V Output: DC 12V 2.5A
VESA	Bracket included Supports 75 x 75 and 100 x 100 mm
Environment	System Environment Operating Temperature: 0°C to +35°C System Storage Temperature: -20°C to +60°C

* With cloud back up service

Solid Secure Straightforward

info@tetherit.io
+44 (0)208 099 6260
Tether Technology Ltd
199 Bishopsgate
London, EC2M 3TY