

Tetherbox

Pico (gen1)

Specification Sheet

Tether Technology Ltd
info@tetherit.io
+44 (0)208 099 6260

London

199 Bishopsgate,
London,
EC2M 3TY

Devon

Electronics & Photonics
Innovation Centre, White Rock
Business Park, Waddeton Close,
Paignton, Devon, TQ4 7RZ

Tether

Tetherbox Pico (gen1) Specifications

- Easy and fast access to footage from any where
- Notifications in case of system health issues
- Easy back up of recordings to cloud*



Cameras	up to 10 x 12 Megapixel Cameras - LICENSE FOR 5 INCLUDED, UPGRADABLE TO 10
Dimension	46.8 mm x 112.6 mm x 119.4 mm
CPU	Intel® Processor Quad Core (TDP 10W)
Memory	4 GB
Storage	1TB Internal SSD (SUPPORT FOR EXTERNAL USB STORAGE)
LAN	Gigabit LAN (Realtek RTL8111G)
I/O	4 x USB 3.0 (1 x USB-C, 3 x USB-A) 1 x HDMI + Mini DisplayPort (FOR DIAGNOSTICS/TESTING ONLY) 1 x RJ45 (Gigabit LAN) 1 x DC-In 1 x Kensington lock slot 1 x Audio-out / Mic-In
Power Supply	Input: AC 100-240V Output: DC 19V 2.1A
VESA	Bracket included Supports 75 x 75 and 100 x 100 mm
Environment	System Environment Operating Temperature: 0°C to +35°C System Storage Temperature: -20°C to +60°C

* With cloud back up service

tetherit.io
sales@tetherit.io
+44 (0)208 099 6260

London
199 Bishopsgate, London,
EC2M 3TY

Devon
Electronics & Photonics
Innovation Centre, White Rock
Business Park, Waddeton Close,
Paignton, Devon, TQ4 7RZ

Solid Secure Straightforward